

To: T10 Technical Committee  
From: Rob Elliott, HP (elliott@hp.com)  
Date: 30 September 2002  
Subject: T10/02-394r0 SAS SPC-3 Protocol Specific log page

### **Revision History**

Revision 0 (30 September 2002) first revision

### **Related Documents**

spc3r09 - SCSI Primary Commands 3 revision 9  
sas-r02 - Serial Attached SCSI revision 02

### **Overview**

SPC-3 defines two protocol-specific mode pages, but no protocol-specific log pages. The protocol-specific mode pages are:

- Protocol Specific Port (19h) - controls the target port being accessed. Changes should not but may affect other target ports of the same protocol. The protocol identifier must match the protocol of the target port through which MODE SENSE is delivered.
- Protocol Specific LUN (18h) - controls the target port/logical unit combination being accessed. Changes should not but may also affect target ports using the same protocol. The protocol identifier must match the protocol of the target port through which MODE SENSE is delivered.

Mode pages offer sub\_page formats to avoid consuming mode page codes, while log pages do not have sub\_page formats yet. Since log page codes are not yet running out, it may be best to just plan on using a range of log page codes for protocol-specific usage and avoid the complication. At the moment, however, only one page code is needed for SAS.

The log page needs to be able to report parameters for different ports. The first proposed log page for SAS returns phy error logs. The port containing the phy of interest may not be operational, so the data must be retrieved through another target port.

The log page should be able to report about ports of different protocols. Devices might support ports of different protocols at the same time. Mode page 18h and 19h cannot reference other protocol's data at all. With protocol-specific parameters, this is possible.

The log parameter code is the relative target port identifier (which can be reported in the Device Identification VPD page of INQUIRY), so applications can relate the log page parameter data to a specific target port. The protocol-specific data may include other clues, like the port name or port identifier. The relative target port identifier in VPD is 4 bytes long, while the parameter code in log pages is 2 bytes long, so this stops working after 16K ports (which should be reasonable).

In a dual-ported SAS disk drive not capable of acting as a wide port, the log page would contain these parameters:

- Parameter 0001h (relative port 1), Protocol identifier 6h, 1 phy descriptor (for phy 0)
- Parameter 0002h (relative port 1), Protocol identifier 6h, 1 phy descriptor (for phy 1)

In a dual-ported SAS disk drive that is acting as a wide port, the log page would contain these parameters:

- Parameter 0001h (relative port 1), Protocol identifier 6h, 2 phy descriptors (for phy 0 and phy 1)

If a device had a 3-wide SAS port and a FC port, it would have:

- Parameter 0001h (relative port 1), Protocol identifier 6h, 3 phy descriptors (for phy 0, phy 1, and phy 2)
- Parameter 0002h (relative port 2), Protocol identifier 0h, FC details (none defined today)

**Suggested Changes to SPC-3****8.4.13 Protocol Specific log page**

The Protocol Specific Port log page provides protocol specific parameters that are associated with a SCSI port. See the SCSI protocol standard (see 3.1.69) for definition of the protocol specific log parameters.

Table xx defines the log page format.

**Table xx - Protocol Specific log page**

	7	6	5	4	3	2	1	0	
0	PAGE CODE (18h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (n-3)							
3							(LSB)		
Log parameters									
4	First protocol specific log parameter								
...									
n	Last protocol specific log parameter								

Table xx defines the log parameter format.

**Table xx - Protocol specific log parameter format**

0	(MSB)	PARAMETER CODE							
1							(LSB)		
2	DU	DS	TSD	ETC	TMC	LBIN	LP		
3	PARAMETER LENGTH (x-3)								
4	Reserved				PROTOCOL IDENTIFIER				
5	Protocol specific								
x									

The PARAMETER CODE field contains the relative target port identifier (see 8.6.4.6) of the target port for which the parameter data applies. Protocol specific log parameters for relative target ports numbered greater than 65 535 are not supported.

The PROTOCOL IDENTIFIER field defines the length of the log parameter.

The PROTOCOL IDENTIFIER field defines the SCSI transport protocol that defines this log parameter (see 8.5.1). The protocol specific data is defined by the corresponding SCSI transport protocol standard.

**Annex B Numeric order codes****B.4 Log page codes**

Add 18h Protocol Specific to all device types except B (RBC). [RBC doesn't implement the LOG SELECT and LOG SENSE commands]

**Suggested Changes to SAS**

[Modify the log page to follow this format.]

**10.1.2 SCSI log parameters****10.1.2.1 Protocol Specific log page for SAS**

The Protocol Specific log page for SAS defined in table 118 is used to report errors that have occurred on the target device's phy(s).

Table xx defines the log page format.

**Table xx - Protocol Specific log page for SAS**

	7	6	5	4	3	2	1	0	
0	PAGE CODE (18h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (n-3)							

3	(LSB)
Log parameters	
4	First protocol specific log parameter
...	...
n	Last protocol specific log parameter

Table xx defines the log parameter format.

**Table xx - Protocol specific log parameter format for SAS**

0	(MSB)	PARAMETER CODE (relative target port identifier)						(LSB)
1								
2	DU	DS	TSD	ETC	TMC	LBIN	LP	
3	PARAMETER LENGTH (y-3)							
4	Reserved				PROTOCOL IDENTIFIER (6h)			
5	Reserved							
6	Reserved							
7	NUMBER OF PHYS							
SAS phy descriptors								
8	First SAS phy log descriptor							
...	...							
y	Last SAS phy log descriptor							

The PARAMETER CODE field contains the relative target port identifier (see SPC-3) of the target port that this log parameter describes.

The NUMBER OF PHYS field contains the number of phy descriptors that follow.

Table xx defines the phy log descriptor.

**Table xx - SAS phy log descriptor**

0	Reserved							
2	Reserved							
3	PHY IDENTIFIER							
4	(MSB)	SAS ADDRESS						(LSB)
11	SAS ADDRESS							
12	(MSB)	ATTACHED SAS ADDRESS						(LSB)
19	ATTACHED SAS ADDRESS							
20	etc... [counter fields defined in sas-r02 or other proposals]							
z	etc... [counter fields defined in sas-r02 or other proposals]							

The PHY IDENTIFIER field contains the phy identifier (see 4.2.6).

The SAS ADDRESS field contains the SAS address (see 4.2.2) of the phy.

The ATTACHED SAS ADDRESS field contains the SAS address (see 4.2.2) of the currently attached device. If no device is currently attached, the field is undefined.

[The remaining counter fields remain as defined as in sas-r02 or in other proposals]