

Date: Jan 10, 2003
To: T10 Committee
From: Erich Oetting
Subject: SMC-2 letter ballot comment response.

SMC-2 revision 5a includes all changes marked as (A) and (P) in revision 0 of this document.

Response Key:

- (A) - Comment is accepted and suggested revision has been done.
- (D) - Comment accepted, document has not yet been revised.
- (R) - Comment rejected for reasons given.
- (P) - Comment accepted in part or revised in another way.
- (T) - Technical change.
- (?) - No decision yet.

Comments attached to YesC ballot from Mr. Ralph O. Weber of
ENDL Texas:

ENDL 1
PDF pg 1, Global
remove change bars

(A) Change bars and strikeouts removed.

ENDL 2
PDF pg 1, Global
SCSI-3 Media Changer Commands - 2 s/b
SCSI Media Changer Commands - 2

(A) Changed all "SCSI-3 Media" to "SCSI Media".

ENDL 3
PDF pg 1, Global
Change SPC to SPC-2.

(T)(P) Agreed, except for READ ATTRIBUTE command that must
reference SPC-3.

ENDL 4

PDF pg 3

Remove revision history before sending SMC-2 to Public Review.

(A) Revision history has been removed.

ENDL 5

PDF pg 6, Foreword, p2, s2

SCSI-3 Architecture Model (SAM) s/b either just SAM or just SCSI-3 Architecture Model. The SAM acronym should be defined in the acronyms glossary (if used).

(?)

ENDL 6

PDF pg 7, Introduction, s for clause 2

Put a period at the end of this sentence.

(A) Added a period.

ENDL 7

PDF pg 12, Clause 1, 1st bullet

Delete 'over a SCSI service delivery subsystem'.

(A) Deleted.

ENDL 8

PDF pg 12, Clause 1, 3rd bullet

commands s/b commands and parameter data

(A) Text changed.

ENDL 9

PDF pg 12, Clause 1, Figure 1

Transport Protocols s/b SCSI Transport Protocols

(A) Added SCSI.

ENDL 10

PDF pg 13, Clause 1, top of page

SCSI-3 s/b SCSI

(P) Changed text on pg 12.

ENDL 11

PDF pg 13, Clause 1

Transport Protocols s/b SCSI Transport Protocols

(?) Changed pg 12, see ENDL 9.

ENDL 12

PDF pg 13, Clause 1

The example SCSI standards need a lot of work. FC-AL is no longer

current, FC-AL-2 is. FC-PH should be replaced by FC-PI. SSA-PL2 needs a year after the NCITS.307. ...

If the intention is to take SMC-2 to ISO, it would be best to switch to ISO reference numbers wherever possible. ANSI will accept ISO references but ISO prefers not to use ANSI references.

Look at the list in SPC-3 r08.

(T)(?)

ENDL 13

PDF pg 13, Clause 1, b of pg

RE: 'The term SCSI is used wherever it is not necessary to distinguish between the versions of SCSI.'

In these modern times, SCSI refers to SCSI-3, since SCSI-2 is thought of as ancient history.

(A) Deleted offending sentence.

ENDL 14

PDF pg 14, Clause 2, p 2, s1

can be obtained s/b may be obtained

(A) Changed text.

ENDL 15

PDF pg 14, Clause 2

ANSI X3.270-1996 s/b ISO/IEC 14776-411

(A) Changed to ISO/IEC standard.

ENDL 16

PDF pg 14, Clause 2

ANSI X3.301-1997, Information Technology - SCSI-3 Primary Commands
s/b

ISO/IEC 14776-312, Information Technology - SCSI Primary Commands
- 2

(A) Text changed.

ENDL 17

PDF pg 14, Clause 2

The discussion of ports in SMC-2 requires that a reference be added to SAM-2. Currently, that would have to be a reference to a standard in development. As soon as SAM-2 goes to public review, it should be possible to make the reference a normative reference.

(?)

ENDL 18

PDF pg 14, Clause 2

The discussion of MAM in SMC-2 requires that a reference be added to SPC-3. This will have to be reference to a standard in development. MAM is discussed only in SPC-3.

(?)

ENDL 19
PDF pg 15, 3.1.1
of REQUEST SENSE command response data s/b of the sense data

(A) Text changed.

ENDL 20
PDF pg 15, 3.1.2
the SCSI-3 Architecture Model (SAM) s/b SAM

(A) Text changed.

ENDL 21
PDF pg 15, 3.1.5
So that the definition of byte is not a sentence (as is the case with most other glossary entries) 'Indicates an' s/b 'An'.

(A) Text changed.

ENDL 22
PDF pg 15, 3.1.7
command descriptor block: s/b command descriptor block (CDB):

(?)

ENDL 23
PDF pg 15, 3.1.7
To acknowledge variable length CDBs, delete 'up to 16 bytes in length'.

(A) Text removed.

ENDL 24
PDF pg 15, 3.1.11
can serve s/b may serve

(A) Text changed.

ENDL 25
PDF pg 15, 3.1.12
Delete the definition for 'extent' because the term should not be used in SMC-2.

(A) Definition removed.

ENDL 26
PDF pg 16, 3.1.15
Delete the definition for 'host' because the term should not be

used in SMC-2.

(A) Definition removed.

ENDL 27

PDF pg 16, 3.1.16

can be accessed s/b may be accessed

(A) Text changed.

ENDL 28

PDF pg 16, 3.1.18

initiator s/b SCSI initiator device [note this will move the entry to a different position in the glossary]

(?)

ENDL 29

PDF pg 16, 3.1.18

an initiator may be found in SAM s/b a SCSI initiator device may be found in SAM-2

(A) Text changed.

ENDL 30

PDF pg 16, 3.1.19

Delete 'which collectively make up a discrete I/O operation' Or at a minimum, change 'which' to 'that'.

(A) Text deleted.

ENDL 31

PDF pg 16, 3.1.20

target s/b SCSI target device

(A) Text changed.

ENDL 32

PDF pg 16, 3.1.21

Remove '64-bit'

(A) Text deleted.

ENDL 33

PDF pg 16, 3.1.26

To avoid having a glossary entry start with a complete sentence, 'Several commands use regular parameter structures that are referred to as pages.' s/b 'A regular parameter structure (or format) used by several commands.'

(?)

ENDL 34

PDF pg 16, 3.1.27

Delete the definition for 'port' because the correct term now is SCSI target port.

(A) Definition deleted.

ENDL 35

PDF pg 16, 3.1.29

SCSI-3 protocol standard s/b SCSI transport protocol standard

(A) Text changed.

ENDL 36

PDF pg 17, insert after 3.1.31

Add the following new glossary entries.

SCSI initiator port: A SCSI initiator device object that acts as the connection between application clients and the service delivery subsystem through which requests and responses are routed. A detailed definition of SCSI target port may be found in SAM-2.

SCSI target port: A SCSI target device object that acts as the connection between device servers and task managers and the service delivery subsystem through which requests and responses are routed. A detailed definition of SCSI target port may be found in SAM-2.

(?)

ENDL 37

PDF pg 17, 3.1.34

initiator s/b application client

(A) Text changed.

ENDL 38

PDF pg 17, 3.1.38

target s/b SCSI target device (note this will move the entry to a different position in the glossary)

(?)

ENDL 39

PDF pg 17, 3.1.38

initiator s/b application client

(A) Text changed.

ENDL 40

PDF pg 17, 3.1.38, s 2

target may be found in SAM s/b SCSI target device may be found in SAM-2

(A) Text changed.

ENDL 41

PDF pg 17, 3.1.40

queuing and autocontingent allegiance rules s/b queuing,
contingent allegiance, and auto contingent allegiance rules

(A) Text changed.

ENDL 42

PDF pg 17, 3.1.41

reference to RESERVE or RELEASE commands s/b
reference to the RESERVE ELEMENT or RELEASE ELEMENT commands

(?)

ENDL 43

PDF pg 17, 3.1.42

initiators s/b SCSI initiator ports

(A) Text changed.

ENDL 44

PDF pg 18, 3.2, Symbols and abbreviations

Add '= is equal to' as a symbol definition because of the frequent
use of bit=0 and bit=1 in several tables.

(?)

ENDL 45

PDF pg 18, 3.2

MMC SCSI-3 Multi-Media Commands standard s/b

MMC-3 SCSI Multi-Media Commands -3 standard

(A) Text changed.

ENDL 46

PDF pg 18, 3.2, SMC-2

SCSI-3 Media Changer Commands - 2 standard s/b

SCSI Media Changer Commands -2, this standard

(A) Text changed.

ENDL 47

PDF pg 18, 3.2

add an acronym entry for SPC-3.

(A) SPC-3 added.

ENDL 48

PDF pg 18, 3.2

The abbreviations list should just be a list, not a bulleted list.

(A) Bullets removed.

ENDL 49
PDF pg 19, 3.3.6
this standards s/b this standard

(A) Text changed.

ENDL 50
PDF pg 19, 3.3.7, s1
future extension to this standard s/b future version of this
standard

(A) Text changed.

ENDL 51
PDF pg 19, 3.4, s3
The text 'If a conflict arises between text, tables, or figures,
...'
should begin a new paragraph.

(A) Text changed.

ENDL 52
PDF pg 20, Clause 4, p1, s1 & s2
SCSI-3 s/b SCSI [twice]

(A) Text changed.

ENDL 53
PDF pg 20, Clause 4, p1, s1
they can s/b that may

(A) Text changed in p3, not p1.

ENDL 54
PDF pg 20, Clause 4, p 4, s 1 & s 3
initiators s/b SCSI initiator ports and
initiator s/b SCSI initiator port

(A) Text changed.

ENDL 55
PDF pg 21, Clause 4, Figure 2
'Port' s/b 'SCSI target port' or 'SCSI Target Port' [3 times]

(R) Making this change whould clutter up the diagram without
adding clarity. Perhaps a change in the text instead?

ENDL 56
PDF pg 21, Clause 4, last p on pg, s1
initiator s/b application client

(A) Text changed.

ENDL 57
PDF pg 22, 5.1, p2, s1
the SMC-2 standard s/b this standard

(A) Text changed.

ENDL 58
PDF pg 22, 5.1, p3
port s/b SCSI target port

(A) Text changed.

ENDL 59
PDF pg 22, 5.1, p3
independent ports s/b independent SCSI target ports

(A) Text changed.

ENDL 60
PDF pg 22, 5.3, bulleted list
The list should be an a,b,c list.

(A) List format changed.

ENDL 61
PDF pg 23, 5.3, 1st p on pg, s 3
'However, multiple initiator environments may cause volumes to be moved without notifying other initiators.' s/b 'However, in configurations with multiple initiators, volumes may be moved by one application client without notification to other application clients.'

(A) Text changed.

ENDL 62
PDF pg 23, 5.3, 2nd p on pg, s2
Volumes can be s/b Volumes may be

(A) Text changed.

ENDL 63
PDF pg 23, 5.3, 3rd p on pg, s 1
an initiator s/b a SCSI initiator port

(A) Text changed.

ENDL 64
PDF pg 23, 5.3, 3rd p on pg, s2
will be lost s/b shall be released

(?)

ENDL 65
PDF pg 23, 5.3, 3rd p on pg, s3

will be retained s/b shall be retained

(?)

ENDL 66

PDF pg 23, 5.3, 4th p on pg, s2
can be s/b may be

(A) Text changed.

ENDL 67

PDF pg 23, 5.3, Note 1, s 2
could be provided by a port which allows s/b
may be provided by a port that allows

(A) Text changed.

ENDL 68

PDF pg 23, 5.4, p1, s2
can serve s/b may serve

(A) Text changed.

ENDL 69

PDF pg 23, 5.4, last p on pg, s 2
initiator s/b application client

(A) Text changed.

ENDL 70

PDF pg 24, 5.5, p1, s3
the SMC-2 device s/b the device

(A) Removed SMC-2.

ENDL 71

PDF pg 25, 5.9, p1, s2
which may be s/b that may be

(A) Text changed.

ENDL 72

PDF pg 25, 5.9, p 1, s 3
initiators s/b SCSI initiator ports & initiator s/b SCSI initiator
port [twice]

(A) Text changed.

ENDL 73

PDF pg 25, 5.9, bulleted list
The list should be an a,b,c list.

(A) List format changed.

ENDL 74
PDF pg 26, 5.10, p 1, last s
initiator s/b application client

(A) Text changed.

ENDL 75
PDF pg 27, 6.1, Table 2
Table 2 should have column titles and the key on every page.

(?)

ENDL 76
PDF pg 29, 6.3, p 4, s 1, & p 5, s 1
issued by initiators s/b received from SCSI initiators [once each
p] by initiators s/b from SCSI initiator ports [once each p]

(A) Text changed.

ENDL 77
PDF pg 29, 6.3, p 4, s 1
registrantonly s/b registrants only or all registrants

(A) Text changed.

ENDL 78
PDF pg 29, 6.3, p 5, s 1
registrants only s/b registrants only or all registrants

(A) Text changed.

ENDL 79
PDF pg 29, 6.3, p 6, s 1 & s 2
initiators s/b SCSI initiator ports [twice]

(A) Text changed.

ENDL 80
PDF pg 29, 6.3, p7 & p8
remove strikeouts text

(A) Text has been removed.

ENDL 81
PDF pg 30, 6.3, Table 4
Initiator s/b initiator [twice]

(A) Table headings changed.

ENDL 82
PDF pg 31, 6.4, p 3
Remove the paragraph describing reservation conflicts because that
subject is now covered in 6.3.

(A) Paragraph has been removed.

ENDL 83

PDF pg 31, 6.4, Table 5

Add MSB and LSB information for the MEDIUM TRANSPORT ADDRESS, SOURCE ADDRESS, FIRST DESTINATION ADDRESS, and SECOND DESTINATION ADDRESS fields.

(A) MSB and LSB added.

ENDL 84

PDF pg 31, 6.4, 1st p after table 5, s 4
which defines s/b that defines

(A) Text changed.

ENDL 85

PDF pg 32, 6.4, last p on pg, s2
a logical unit which is not capable s/b
a device sever that is not capable

(A) Text changed.

ENDL 86

PDF pg 33, 6.5, p 1, s 2
Initiator s/b application client

(A) Text changed.

ENDL 87

PDF pg 33, 6.5, 3rd p after table 6
Remove the paragraph describing reservation conflicts because that subject is now covered in 6.3.

(A) Paragraph removed.

ENDL 88

PDF pg 34, 6.6, p 1, s 1
ELEMENT STATUS WITH RANGE s/b INITIALIZE ELEMENT STATUS WITH RANGE

(P) Changed to "The INITIALIZE ELEMENT ..."

ENDL 89

PDF pg 34, 6.6, p 1, s 2
Initiator s/b application client

(A) Text changed.

ENDL 90

PDF pg 34, 6.6, p 1, s 3
power failure, or if a s/b power failure, if a [currently there are two 'or's in the sentence where there should be one]

(A) "or" removed.

ENDL 91
PDF pg 34, 6.6, Table 7
Add MSB and LSB information for the STARTING ELEMENT ADDRESS and
NUMBER OF ELEMENTS fields.

(D)

ENDL 92
PDF pg 34, 6.6, 4th p after table 7
Remove the paragraph describing reservation conflicts because that
subject is now covered in 6.3.
(A) Paragraph removed.

ENDL 93
PDF pg 35, 6.7, p 1, s 1
target s/b device server

(A) Text changed.

ENDL 94
PDF pg 35, 6.7, p 2
Remove the paragraph describing reservation conflicts because that
subject is now covered in 6.3.

(A) Paragraph removed.

ENDL 95
PDF pg 35, 6.7, Table 8
Add MSB and LSB information for the MEDIUM TRANSPORT ADDRESS,
SOURCE ADDRESS, and DESTINATION ADDRESS fields.

(A) Table format fixed.

ENDL 96
PDF pg 35, 6.7, 3rd p after table 8, s 1 & s 3
target s/b device server [twice]

(A) Text changed.

ENDL 97
PDF pg 36, 6.7, 1st p on pg, s 3, 2nd p on pg s 2, 4th p on pg, s
3 target s/b device server [3 times]

(A) Text changed in three places.

ENDL 98
PDF pg 37, 6.8, p 3
Remove the paragraph describing reservation conflicts because that
subject is now covered in 6.3.

(A) Text removed.

ENDL 99

PDF pg 37, 6.8, Table 9
Add MSB and LSB information for the MEDIUM TRANSPORT ADDRESS and
DESTINATION ADDRESS fields.

(A) Table format fixed.

ENDL 100

PDF pg 38, 6.9

Insert 6.9.1 READ ATTRIBUTE command introduction [to eliminate
hanging paragraphs]

(?)

ENDL 101

PDF pg 38, 6.9, p 3

Remove the paragraph describing reservation conflicts because that
subject is now covered in 6.3.

(A) Paragraph removed.

ENDL 102

PDF pg 38, 6.9, Table 10

Do not capitalize field names such as Element type code, First
attribute id, and Allocation length.

(A) Text in table modified.

ENDL 103

PDF pg 38, 6.9, Table 10, byte 5

Volume number s/b in small caps starting with a lower case v

(A) Format changed.

ENDL 104

PDF pg 38, 6.9, Table 10, byte 6

Capitalize Reserved so that byte 6 looks like bytes 1 and 8.

(A) Text modified.

ENDL 105

PDF pg 38, 6.9, Table 10, byte 7

Partition number s/b in small caps starting with a lower case p

(A) Format changed.

ENDL 106

PDF pg 38, 6.9, 1st p after table 10, s 1

resides (as part of a medium) s/b resides as part of a medium.

(A) Text modified.

ENDL 107

PDF pg 39, 6.9, 1st p on pg, s 2

SPC s/b SPC-3 [only SPC-3 describes MAM]

(A) Changed to SPC-3.

ENDL 108

PDF pg 39, 6.9, 1st p after table 11, s 1
'command, see SPC' s/b 'command see SPC-3'

(A) Text modified.

ENDL 109

PDF pg 39, 6.9, 2nd p after table 11
ELEMENT LIST service action s/b
6.9.2 ELEMENT LIST service action
(a subclause header)

(D)

ENDL 110

PDF pg 39, 6.9, Table 12, bytes 0-3
Available data s/b in small caps starting with a lower case a

(A) Format changed.

ENDL 111

PDF pg 39, 6.9, Table 12, byte 4
Element type code s/b in small caps starting with a lower case e

(A) Format changed.

ENDL 112

PDF pg 39, 6.9, Table 12
Add MSB and LSB information for the FIRST ELEMENT ADDRESS and
NUMBER OF ELEMENTS fields.

(A) Table format fixed.

ENDL 113

PDF pg 39, 6.9, Table 12, bytes 5 & 6
First Element Address s/b in small caps starting with a lower case
f

(A) Format changed.

ENDL 114

PDF pg 39, 6.9, Note 5
shall contain s/b contain
(or note 5 is not a note)

(D)

ENDL 115

PDF pg 40, 6.10
Insert 6.10.1 READ ELEMENT STATUS introduction [to eliminate
hanging paragraphs]

(D)

ENDL 116

PDF pg 40, 6.10, p 1, s 1

target s/b device server & initiator s/b application client

(A) Text changed.

ENDL 117

PDF pg 40, 6.10, Table 13

Add MSB and LSB information for the STARTING ELEMENT ADDRESS,
NUMBER OF ELEMENTS, and ALLOCATION LENGTH fields.

(A) Table format fixed.

ENDL 118

PDF pg 40, 6.10, 2nd p after table 13, s 1, 3rd p after table 13,
s 1 & s 2 target s/b device server [3 times]

(A) Text modified.

ENDL 119

PDF pg 40, 6.10, p 4 after table 13

Remove the paragraph describing reservation conflicts because that
subject is now covered in 6.3. (Note, this paragraph continues on
the top of PDF pg 41.)

(A) Paragraph removed.

ENDL 120

PDF pg 41, 6.10, 2nd p after table 14, s 1, 3rd p after table 14,
s 1 & s 2 target s/b device server [3 times]

(A) Text modified.

ENDL 121

PDF pg 41, 6.10, 2nd p after table 14, s3

'the target shall transfer all those descriptors that can be
completely transferred' s/b 'the device server shall transfer all
those descriptors whose complete contents fit within the
allocation length'

(A) Text modified.

ENDL 122

PDF pg 42, 6.10.1, Table 15

Add MSB and LSB information for the FIRST ELEMENT ADDRESS
REPORTED, NUMBER OF ELEMENTS AVAILABLE, and BYTE COUNT OF REPORT
AVAILABLE fields.

(A) Table format fixed.

ENDL 123

PDF pg 42, 6.10.1, Note 6
can be issued s/b may be issued

(A) Text changed.

ENDL 124
PDF pg 43, 6.10.2, Table 16
Add MSB and LSB information for the ELEMENT DESCRIPTOR LENGTH and
BYTE COUNT OF DATA AVAILABLE fields.

(A) Table format fixed.

ENDL 125
PDF pg 44, 6.10.3, Table 17
Add MSB and LSB information for the ELEMENT ADDRESS and SOURCE
STORAGE ELEMENT ADDRESS fields.

(A) Information added.

ENDL 126
PDF pg 46, 6.10.4, Table 18
Add MSB and LSB information for the ELEMENT ADDRESS and SOURCE
STORAGE ELEMENT ADDRESS fields.

(A) Information added.

ENDL 127
PDF pg 48, 6.10.5, Table 19
Add MSB and LSB information for the ELEMENT ADDRESS and SOURCE
STORAGE ELEMENT ADDRESS fields.

(A) Information added.

ENDL 128
PDF pg 48, 6.10.5, Table 19, byte 1
'Rsvd' s/b 'RSVD' and 'cmc' should be in small caps.

(A) Table changed.

ENDL 129
PDF pg 50, 6.10.6, Table 20
Add MSB and LSB information for the ELEMENT ADDRESS and SOURCE
STORAGE ELEMENT ADDRESS fields.

(A) Information added.

ENDL 130
PDF pg 50, 6.10.6, Table 20, byte 6
NOT BUS should begin with a lower case n, ID VALID should begin
with a lower case i, and LU VALID should begin with a lower case
l.

(?) It might be better to just obsolete these fields.

ENDL 131
PDF pg 51, 6.10.6, Note 8, s3
can only reflect s/b only reflects

(A) Text modified.

ENDL 132
PDF pg 53, 6.11
Insert 6.11.1 RELEASE ELEMENT (6) introduction [to eliminate
hanging paragraphs]

(D)

ENDL 133
PDF pg 53, 6.11, 1st p after table 22, s 1
The following requirement conflicts with the intentions of
approved proposal 02-108r0: 'Attached media changers shall
implement the RESERVE(6) command as defined in the SPC.' Remove
it.

(?)

ENDL 134
PDF pg 53, 6.11, note 9
Remove this note because the SPC-2 RESERVE(6) command does not
define an EXTENT bit.

(A) Note removed.

ENDL 135
PDF pg 53, 6.11, 1 st p after note 9, s 1
multiple initiator systems s/b configurations with multiple
initiators

(A) Text modified.

ENDL 136
PDF pg 53, 6.11, 1 st p after note 9, s 2
RELEASE command s/b RELEASE ELEMENT command

(A) Text modified.

ENDL 137
PDF pg 53, 6.11.1
Logical unit release is not a complementary function to the
logical unit reserve function described in 6.14.1. 6.11.1 needs
some form of counterpart for the 6.14.1 statement: 'If the ELEMENT
bit is zero, this command shall request that the entire logical
unit be reserved for the exclusive use of the initiator as defined
in SPC.' However, SPC should be replaced with SPC-2.

(?) SPC replaced with SPC-2.

ENDL 138

PDF pg 53, 6.11.1, p 1, s 1, also 6.11.2, p 1, s 1
terminate s/b release & terminated s/b released

(A) Text modified.

ENDL 139
PDF pg 53, 6.11.1, p 1, s 1
initiator s/b SCSI initiator port

(A) Text modified.

ENDL 140
PDF pg 53, 6.11.2, p 1, s 1 & s 2
initiator s/b SCSI initiator port [twice]

(A) Text modified.

ENDL 141
PDF pg 54, 6.12, subclause header
Make the 6.12 header text the same font size as the 6.11 header.

(A) Format changed.

ENDL 142
PDF pg 54, 6.12
Insert 6.12.1 RELEASE ELEMENT (10) introduction [to eliminate
hanging paragraphs]

(D)

ENDL 143
PDF pg 54, 6.12, Table 23
Add MSB and LSB information for the PARAEMTER LIST LENGTH field.

(A) Information added.

ENDL 144
PDF pg 54, 6.12.1, p 1, s 1
RELEASE ELEMENT command
s/b RELEASE ELEMENT (10) command

(A) Text modified.

ENDL 145
PDF pg 54, 6.12.1, p 1, s 1
initiator s/b application client

(A) Text modified.

ENDL 146
PDF pg 54, 6.12.1, p 1, s 1 [x2] & p 2, s 2 [x1]
unit s/b logical unit [3 times]

(A) Text modified.

ENDL 147

PDF pg 54, 6.12.1, p 2, s 2
target s/b SCSI device

(A) Text modified.

ENDL 148

PDF pg 54, 6.12.1, p 2, s 2
target s/b device server

(A) Text modified.

ENDL 149

PDF pg 54, 6.12.1, p 2, s 2
initiator s/b SCSI initiator port

(A) Text modified.

ENDL 150

PDF pg 55, 6.12.1, 2nd p on pg, s 1
In 'the PARAMETER LIST LENGTH', parameter list length should not
be in small caps because it is not followed by the word 'field'.
[twice]

(?) Will adding the word 'field' fix this?

ENDL 151

PDF pg 55, 6.12.1, Table 24
Add MSB and LSB information for the THIRD PARTY DEVICE ID field.

(A) Information added.

ENDL 152

PDF pg 55, 6.13, p 3
Remove the paragraph describing reservation conflicts because that
subject is now covered in 6.3.

(A) Text removed.

ENDL 153

PDF pg 55, 6.13, p5, s2
will be reported s/b shall be reported

(A) Text modified.

ENDL 154

PDF pg 56, 6.13, note 10, s 1
multi-initiator environment s/b configuration with multiple SCSI
initiator devices

(A) Text modified.

ENDL 155

PDF pg 56, 6.13, note 10, s 1
initiator s/b SCSI initiator port

(A) Text changed.

ENDL 156

PDF pg 56, 6.13, Table 25
Add MSB and LSB information for the ELEMENT ADDRESS, NUMBER OF
ELEMENTS TO REPORT, and ALLOCATION LENGTH fields.

(A) Information added.

ENDL 157

PDF pg 57, 6.13, 1st p on pg, s 3
'the logical unit shall transfer all those descriptors that can be
completely transferred' s/b 'the device server shall transfer all
those descriptors whose complete contents fit within the
allocation length'

(A) Text modified.

ENDL 158

PDF pg 57, 6.13, Table 26
Add MSB and LSB information for the FIRST ELEMENT ADDRESS
REPORTED, NUMBER OF ELEMENTS REPORTED, and BYTE COUNT OF REPORT
AVAILABLE fields.

(A) Information added.

ENDL 159

PDF pg 57, 6.13, 2nd p after table 26, s 1
'see the READ ELEMENT STATUS command description' s/b 'see the
READ ELEMENT STATUS command description in 6.10'

(A) Text added.

ENDL 160

PDF pg 58, 6.14
Insert 6.14.1 RESERVE ELEMENT (6) introduction [to eliminate
hanging paragraphs]

(D)

ENDL 161

PDF pg 58, 6.14, Table 27
The line between bytes 3 and 4 should be a dash line, like the
line between bytes 3 and 4 in table 22.

(R) All dashed lines in tables have been removed to make the style
match other T10 documents.

ENDL 162

PDF pg 58, 6.14, 1 st p after table 27, s 1
multiple-initiator systems s/b configurations with multiple SCSI

initiator devices

(A) Text modified.

ENDL 163

PDF pg 58, 6.14, 2nd p after table 27, s 2

The following requirement conflicts with the intentions of approved proposal 02-108r0: 'Attached media changers shall implement the RESERVE (6) command as defined in SPC.' Remove it.

(?)

ENDL 164

PDF pg 58, 6.14, note 11

Remove this note because the SPC-2 RESERVE(6) command does not define an EXTENT bit.

(A) Note deleted.

ENDL 165

PDF pg 58, 6.14.1, p 1, s 1

initiator s/b SCSI initiator port

(A) Text changed.

ENDL 166

PDF pg 58, 6.14.1, p2 & p 3

Remove the two paragraphs describing reservation conflicts because that subject is now covered in 6.3.

(A) Text removed.

ENDL 167

PDF pg 59, 6.14.2, p 5, s 1

initiator s/b SCSI initiator port [three times]

(A) Text modified.

ENDL 168

PDF pg 59, 6.14.2, bulleted list

This list should be a 1,2,3 list.

(A) List format changed.

ENDL 169

PDF pg 59, 6.14.2, 1st p after bulleted list, s 1

the ELEMENT LIST LENGTH parameter s/b the ELEMENT LIST LENGTH field

(A) Text modified.

ENDL 170

PDF pg 60, 6.14.2, Table 28

Add MSB and LSB information for the NUMBER OF ELEMENTS and ELEMENT

ADDRESS fields.

(A) Information added.

ENDL 171

PDF pg 60, 6.14.2, 1 st p after table 28

Remove the paragraph describing reservation conflicts because that subject is now covered in 6.3.

(A) Paragraph deleted.

ENDL 172

PDF pg 60, 6.15

Insert 6.15.1 RESERVE ELEMENT (10) introduction [to eliminate hanging paragraphs]

(D)

ENDL 173

PDF pg 61, 6.15, Table 29

Add MSB and LSB information for the PARAMETER LIST LENGTH field.

(A) Information added.

ENDL 174

PDF pg 61, 6.15, 1 st p after table 29, s 1

multiple-initiator systems s/b configurations with multiple SCSI initiator devices

(A) Text modified.

ENDL 175

PDF pg 61, 6.15, note 12

Remove this note because the SPC-2 RESERVE(10) command does not define an EXTENT bit.

(A) Note removed.

ENDL 176

PDF pg 61, 6.15.1, p 1, s 1

RESERVE command s/b RESERVE ELEMENT (10) command

(A) Text changed.

ENDL 177

PDF pg 61, 6.15.1, p 2, s 3

'The target shall preserve the reservation' s/b 'The reservation shall be preserved'

(A) Text changed.

ENDL 178

PDF pg 61, 6.15.1, p 2, s 2

RESERVE command s/b RESERVE ELEMENT (10) command

(?) Text changed. Do we need to preclude using a RESERVE ELEMENT (6) command to clear a reservation made with a RESERVE ELEMENT (10)?

ENDL 179

PDF pg 61, 6.15.1, p 2, s 3 & s 4
initiator s/b SCSI initiator port [4 times]

(A) Text changed.

ENDL 180

PDF pg 61, 6.15.1, p 2, s 4
target s/b device server

(A) Text changed.

ENDL 181

PDF pg 62, 6.15.1, 1st p on pg, s 1
initiator s/b SCSI initiator port [twice]

(A) Text changed.

ENDL 182

PDF pg 62, 6.15.1, 1st p on pg, s 1, 6.15.2, p 1, s 1, & p 1, s 2
RESERVE command s/b RESERVE ELEMENT (10) command [3 times]

(?) Text changed. Should this really be RESERVE ELEMENT (6) or RESERVE ELEMENT (10)?

ENDL 183

PDF pg 62, 6.15.1, 1st p on pg, s 2
Delete the following: 'Reservation conflicts shall occur in all cases where another initiator is not allowed access due to the reservation.' because it is covered in 6.3.

(A) Text deleted.

ENDL 184

PDF pg 62, 6.15.2, p 1, s 1
initiator s/b SCSI initiator port [twice]

(?) Once instance changed. Should the word 'unit' in this sentence be replaced by 'logical unit'?

ENDL 185

PDF pg 62, 6.15.2, p 1, last s
target s/b device server

(A) Text modified.

ENDL 186

PDF pg 62, 6.15.2, note 13
remove 'principally'

(A) Word deleted.

ENDL 187

PDF pg 62, 6.15.2, 1st p after note 13, s 1

THIRD PARTY DEVICE ID is s/b THIRD PARTY DEVICE ID field is

(A) Text modified.

ENDL 188

PDF pg 62, 6.15.2, last p before table 30

extent list length s/b element descriptor list length

(A) Text modified.

ENDL 189

PDF pg 62, 6.15.2, 4th p after note 13, s 1

In 'PARAMETER LIST LENGTH minus', parameter list length should not be in small caps because it is not followed by the word 'field'.

(A) Changed font to normal from small caps.

ENDL 190

PDF pg 62, 6.15.2, Table 30

Add MSB and LSB information for the THIRD PARTY DEVICE ID field.

(A) Information added.

ENDL 191

PDF pg 63, 6.16, p 2

Remove the paragraph describing reservation conflicts because that subject is now covered in 6.3.

(A) Paragraph deleted.

ENDL 192

PDF pg 63, 6.16, Table 31

Add MSB and LSB information for the ELEMENT ADDRESS and PARAMETER LIST LENGTH fields.

(A) Information added.

ENDL 193

PDF pg 63, 6.16, 1st p after table 31, s 2 & s 4

SEND ACTION CODE s/b SEND ACTION CODE field [twice]

(A) Text modified.

ENDL 194

PDF pg 64, 6.16, 1st p on pg, s 2 & s 3

SEND ACTION CODE s/b SEND ACTION CODE field [twice]

(A) Text modified.

ENDL 195

PDF pg 65, 6.16, Table 33

Add MSB and LSB information for the VOLUME IDENTIFICATION TEMPLATE, MINIMUM VOLUME SEQUENCE NUMBER, and MAXIMUM VOLUME SEQUENCE NUMBER fields.

(A) Information added.

ENDL 196

PDF pg 66, 6.16, 1st bulleted list on pg, both bullets will match s/b shall match

(A) Text changed.

ENDL 197

PDF pg 66, 6.16, bulleted list

This list should be an a,b list.

(A) List format changed.

ENDL 198

PDF pg 66, 6.16, 2nd p after bulleted list, s 2 will meet s/b meets

(A) Text modified.

ENDL 199

PDF pg 67, 6.17, Table 34

Add MSB and LSB information for the ELEMENT ADDRESS and PARAMETER LIST LENGTH fields. Also VOLUME NUMBER should begin with a lower case v and PARTITION NUMBER should begin with a lower case p.

(A) Changed case in two places. Added MSB and LSB.

ENDL 200

PDF pg 67, 6.17, 1st p after table 34, s 1

resides (as part of a medium) s/b resides as part of a medium

(A) Text changed.

ENDL 201

PDF pg 67, 6.17, 3rd p after table 34, s 1

SPC-2 s/b SPC-3 [the MAM commands are not defined in SPC-2]

(A) Text changed.

ENDL 202

PDF pg 69, 7.2.2, heading

page. s/b page (remove the period)

(A) Period removed.

ENDL 203

PDF pg 69, 7.2.2, p 1, s 2

of this document s/b of this standard

(A) Text changed.

ENDL 204

PDF pg 69, 7.2.2, p 2

Regarding: 'EDITORS NOTE: TapeAlert log page description should be moved here and renamed to avoid the reference to SSC.'

At a minimum, remove this paragraph. If it is still desirable to move the TapeAlert log page description to SMC-2, then do so.

(?)

ENDL 205

PDF pg 70, 7.3

Insert 7.3.1 Mode parameters overview [to eliminate hanging paragraphs]

(D)

ENDL 206

PDF pg 72, 7.3.1, heading, p1, and table 38 title

The current editorial agreement is that 'Device Capabilities' may be capitalized when it is followed by the exact words 'mode page'.

(A) Used 'Device Capabilities mode page' in three places.

ENDL 207

PDF pg 72, 7.3.1, p 1, s 3

initiator s/b application client

(A) Text modified.

ENDL 208

PDF pg 72, 7.3.1, 1st p after table 38, s 3

target s/b SCSI device

(A) Text modified.

ENDL 209

PDF pg 73, 7.3.1, bulleted list

This list should be an a,b,c list.

(A) List format changed.

ENDL 210

PDF pg 73, 7.3.1, 2 nd & 3 rd p after bulleted list, last s

In both paragraphs... 'Those which are not valid will be rejected with ILLEGAL REQUEST.' s/b 'Those that are not valid shall be rejected with a CHECK CONDITION status and ILLEGAL REQUEST sense key.'

(A) Text modified.

ENDL 211

PDF pg 74, 7.3.2, heading, p1, and table 39 title
The current editorial agreement is that 'Element Address Assignment' may be capitalized when it is followed by the exact words 'mode page'.

(A) Changed all three to 'Element Address Assignment mode page'.

ENDL 212

PDF pg 74, 7.3.2, Table 39
Add MSB and LSB information for the FIRST MEDIUM TRANSPORT ELEMENT ADDRESS, NUMBER OF MEDIUM TRANSPORT ELEMENTS, FIRST STORAGE ELEMENT ADDRESS, NUMBER OF STORAGE ELEMENTS, FIRST IMPORT/EXPORT ELEMENT ADDRESS, NUMBER OF IMPORT/EXPORT ELEMENTS, FIRST DATA TRANSFER ELEMENT ADDRESS, and NUMBER OF DATA TRANSFER ELEMENTS fields.

(A) Information added.

ENDL 213

PDF pg 74, 7.3.2, 1st p after table 33, s 3
target s/b SCSI device

(?) Changed target to device server. Is SCSI device really correct?

ENDL 214

PDF pg 75, 7.3.2, global on pg
target s/b device server [4 times]

(A) Text changed.

ENDL 215

PDF pg 75, 7.3.2, last p before 7.3.3, s 1
must have s/b shall have

(A) Text changed.

ENDL 216

PDF pg 75, 7.3.3, heading, p1, and table 40 title
The current editorial agreement is that 'Transport Geometry Parameters' may be capitalized when it is followed by the exact words 'mode page'.

(A) Changed to 'Transport Geometry Parameters mode page' in three places.

ENDL 217

PDF pg 75, 7.3.3, p 1, s 1
defines s/b indicates

(A) Text modified.

ENDL 218

PDF pg 75, 7.3.3, p 1, s 1

'that share a common robotics subsystem' s/b 'that share common robotics'

(A) Text modified.

ENDL 219

PDF pg 75, 7.3.3, p 1, s 2 & 3

'element. (Other than the default transport element address of zero.)' s/b 'element (other than the default medium transport address of zero).' as is the case in the description of FIRST MEDIUM TRANSPORT ELEMENT ADDRESS.

(A) Text modified.

ENDL 220

PDF pg 75, 7.3.3, p 1, last s

Regarding: 'An attached media changer shall not return this page.'

Remove this sentence because the requirement it states is already stated in 7.3 and because none of the other mode page descriptions contain a similar sentence.

(A) Text removed.

ENDL 221

PDF pg 76, 7.3.3, 1st p after table 40, s 3
target s/b SCSI device

(A) Text modified.

ENDL 222

PDF pg 76, 7.3.3, 2nd p after table 41, s 1 'that share a common robotics subsystem' s/b 'that share common robotics'

(A) Text modified.

ENDL 223

PDF pg 76, 7.3.3, Note 15

'(The individual transport element is addressed [not the robotics subsystem]. An element is defined to be a place where a unit of media may be at any point in time. See clause 5.)' s/b 'The individual transport element is addressed, not the robotics subsystem. An element is defined to be a place where a unit of media may be at any point in time. See clause 5.'

(A) Text modified.

ENDL 224

PDF pg 77, Annex A, Table

The table in Annex A should have a title, including a table number of 'Table A.1'. The table should have column headings and key

information on every page.

(D)

ENDL 225

PDF pg 77, Annex A, code 05h
which s/b that

(A) Text modified.

ENDL 226

PDF pg 77, Annex A, code 06h
Replace 'host interface' with a more specific term, e.g., 'service
delivery subsystem'.

(?)

ENDL 227

PDF pg 79, Annex A, code 12h
can not s/b cannot

(A) Space removed.

ENDL 228

PDF pg 81, Annex A
Remove the periods from the list entries in the Type Key and Flag
Type Key lists in the Annex A table note.

(A) Periods removed.

Comments attached to YesC ballot from Mr. Joe Breher of
Exabyte Corp.:

Exabyte 1

E

doc page 3 - Revision History, Rev 0 "Restored Third Party ID
field in Table 24, Reserve Element (10) command." s/b "...Table
29..."

(R) Revision History has been removed.

Exabyte 2

T

doc page 15 - 3.1.7
"3.1.7 command descriptor block: The structure up to 16 bytes in
length used to communicate commands from an application client to
a device server." CDBs may be over 16 bytes.

(A) 'up to 16 bytes' removed.

Exabyte 3

E

doc page 19 - 3.3.x

Add definition of 'restricted' as per SPC

(?)

Exabyte 4

E

doc page 20 - 4 Overview, several other places "data transport element" s/b "data transfer element"

The (undefined) term data transport element is used in several places in the document.

So is the (defined) term data transfer element. Data transport element seems to be an alias for data transfer element. Suggest replace throughout.

(A) Replaced three cases of 'data transport'.

Exabyte 5

E

doc page 22 - 5.1 Independent media changer, 1st sentence:

"An independent mediachanger is a device server that returns..."
s/b "An independent media changer is a device server that returns..."

(A) Space added.

Exabyte 6

T

doc page 23 - 5.4 Medium transport element, 1st para, last sentence

"The maximum number of medium transport elements is 127."

Why? This seems like a totally arbitrary restriction.

Suggest removing this bound.

(R) Structure of Transport Geometry Parameters mode page places a limit on number of transports. The one byte length field and two bytes of information per transport leaves room for only 127 elements.

Exabyte 7

E

doc page 24 - 5.6 Import/export element, 1st sentence

"Import/export elements are locations of volumes that are being inserted into or..."

s/b

"Import/export elements are locations of volumes that are being

inserted into or..."

(A) Space added.

Exabyte 8

E

doc page 24 - 5.6 Import/export element, 2nd sentence

"...(i.e., cascaded media changer devices)."

Should "cascaded" be replaced with "connected"? This is the only place in the entire doc where "cascade*" is used.

(?)

Exabyte 9

T

doc page 27 - Table 2

CHANGE DEFINITION is obsolete in SPC-2, SPC-3. We should probably remove it from this table.

(A) Command removed from table.

Exabyte 10

T

doc page 27 - Table 2

Opcode for RELEASE ELEMENT (6) is listed as 16h.

s/b 17h

(A) Changed opcode.

Exabyte 11

E

doc page 28 - Table 2

"SEND DIAGNOSTIC" is in different font from other entries.

(A) Changed format.

Exabyte 12

T

doc page 28 - 2nd sentence after Table 2

"All other operation codes are reserved."

s/b

"All other operation codes are restricted."

(?)

Exabyte 13

E

doc page 29 - 6.3, 4th para

"allowed: Commands issued by initiators not holding the reservation or by initiators not registered when a registrant only persistent reservation is present should complete normally."

s/b

"...not registered when a registrants only persistent..."

(A) Inserted space.

Exabyte 14

E

doc page 34 - 6.6 INITIALIZE ELEMENT STATUS WITH RANGE, 1st sentence Word "INITIALIZE" missing

Also, why is the 1st para not similar text to that for 6.5

INITIALIZE ELEMENT STATUS?

(P) Added 'INITIALIZE'.

Exabyte 15

T

doc page 38 - 6.9 READ ATTRIBUTE command SPC-3 defines this as a 16 byte CDB - we should match.

(A)(T) Fixed table to match SPC-3.

Exabyte 16

E

doc page 38 - 6.9 READ ATTRIBUTE command, para after Table 10, last sentence

"Not that this field forms an additional..." s/b "Note that this field forms an additional..."

(A) Changed 'Not' to 'Note'.

Exabyte 17

E

doc page 39 - 6.9 READ ATTRIBUTE, 1st sentence on page, sentence after Table 11

READ ATTRIBUTE does not appear in SPC, SPC-2. Should the reference therefore be to SPC-3?

(A) Changed to SPC-3.

Exabyte 18

?

doc page 39 - Table 12

Should this table be formatted as descriptors?

(?)

Exabyte 19

E

doc page 48, Table 19

cmc bit s/b capitalized - it is a field name.

(A) Changed to small caps.

Exabyte 20

E

doc page 56, last sentence

"When the SEND ACTION CODE is assert, replace, and undefine, the ELEMENT ADDRESS field gives the particular element whose volume tag information was modified."

s/b

"When the SEND ACTION CODE is assert, replace, or undefine, ..."

(A) Changed 'and' to 'or'.

Exabyte 21

E

doc page 67, last sentence "For the definitions of all other fields, and parameter data format, see SPC-2."

s/b

"...see SPC-3." WRITE ATTRIBUTE not in SPC-2

(A) Changed to SPC-3.

Exabyte 22

E

doc page 69, Table 36

Log page codes 01h-05h, 08h-0Ah, 0Ch are listed as reserved

s/b listed as restricted.

(?)

Exabyte 23

E

doc page 69, last sentence

resolve and remove editor's note

(?)

Exabyte 24

E

doc page 71, Table 37

Log page codes 01h, 03h-09h, 0Bh-17h, 1Bh are listed as reserved

s/b listed as restricted.
Log page code 2Ah is listed as Vendor-specific (page format required) s/b listed as restricted.

(?)

Exabyte 25

?

doc page 71, Table 37

I think this is really an issue with SPC-x, but I bring it up here.

SPC, SPC-2, and SPC-3 each have a numerically ordered listing of mode page codes. In each of these docs, they list code 1Dh as associated with Transport

geometry parameters page and 1Eh as associated with Element address assignment page. SPC-x explicitly defers the assignment of these codes to device type specific documents elsewhere within SPC-x. I believe SPC-x is therefore in error.

As the usage in SMC and SMC-2 reflect industry practice (at least to my knowledge), I would like SMC and SMC-2 to remain as they are on this point.

(?)

Comments attached to No ballot from Mr. Michael Banther of Hewlett Packard Co.:

HP #1

PDF Page 1

Cover page and global

Change "SCSI-3 Media Changer Commands - 2" to "SCSI Media Changer Commands - 2". All the second revisions of the command standards have dropped the -3 from the SCSI prefix in their titles.

(A) Text changed.

HP #2

PDF Page 1

Cover page

Change "SMC Technical Editor" to "Technical editor" since this is now SMC-2

(P) Changed to T10 Technical Editor to match ESG.

HP #3

PDF Page 1

Cover page

Change Accredited to Accredited

(A) Text changed.

HP #4

PDF Page 1

Cover page

Remove comma after CO in the address

(A) Comma deleted.

HP #5

PDF Page 2

Points of Contact

Remove trailing / from all web site addresses

Change the T10 information to:

Web Site: <http://www.t10.org>

E-mail reflector:

Server: majordomo@t10.org

To subscribe, send e-mail with 'subscribe t10' in the message body

To unsubscribe, send e-mail with 'unsubscribe t10' in the message body

(D) Will modify to match ESG (T10/03-049r0).

HP #6

PDF Page 6

Foreword

Update the "SCSI-3 Architecture Model (SAM)" reference to SAM-2

(?)

HP #7

PDF Page 6

Foreword

Change "device type" to "peripheral device type" in small caps.

(A) Text modified.

HP #8

PDF Page 7

Introduction

Change "seven clauses" to "the following clauses" since the annexes are also listed

(?) ESG example has a count of clauses, a list of clauses, a count of annexes and a list of annexes.

HP #9

PDF Page 9

Figures and Tables

Remove blank lines between rows in the lists of figures and tables

(D)

HP #10

PDF Page 10

Tables

Spacing around the emdash is inconsistent in the table headers. 4 and 5 have no space after the table number. 11 and 14 have no space before the table title. There should be spaces on both sides for all of them.

(D)

HP #11

PDF Page 11

Annexes

Include the annexes (if any remain) as part of the Contents section.

(D)

HP #12

PDF Page 12

1 Scope

Page 12 should be page 1. All preceding pages should be numbered i, ii, iii, etc.

(D)

HP #13

PDF Page 12

1 Scope

Change sets "the MCHNGR bit in" to "the MCHNGR bit to one in the"

(A) Added 'to one'.

HP #14

PDF Page 12

1 Scope

Delete "over a SCSI service delivery subsystem."

(A) Text deleted.

HP #15

PDF Page 12

1 Scope

Change bulleted list into an a) b) c) list.

(?)

HP #16

PDF Page 12

1 Scope

Change "DEVICE TYPE" to "PERIPHERAL DEVICE TYPE"

(A) Text modified.

HP #17

PDF Page 13

1 Scope

I suggest removing page 13, the page with the "At the time this standard was generated examples of the SCSI-3 general structure included:" list of other standards. This kind of list is always out of date and incomplete.

(?)

HP #18

PDF Page 14

2 Normative references

Update to SAM-2 and SPC-2.

Add References under development listing SAM-3 and SPC-3. Then globally change references to SAM and SPC to SAM-2 and SPC-2 (or SPC-3)

(P) SPC changed to SPC-2 or SPC-3 as appropriate. Still need to decide if SAM-2 should be referenced.

HP #19

PDF Page 14

2 Normative References

Uncapitalize References in the section header.

(?)

HP #20

PDF Page 15

3.1 Definitions

Remove "This clause contains a glossary of special terms used in this standard. These terms apply to SMC-2 and do not constitute a comprehensive glossary for SCSI-3." This is a hanging paragraph and is not really necessary.

(?)

HP #21

PDF Page 15

3.1.4 autosense data

Remove this definition - only used by the definition of "sense data."

(A) Definition removed.

HP #22

PDF Page 15

3.1.7 command descriptor block

Add (CDB) to the bold part of the definition. The phrase "up to 16 bytes in length" is no longer true; see SPC-2 for the latest definition.

(A) Text modified.

You may not need to include any of the terms that are already defined in SAM-2 and SPC-2, since those documents are listed as normative references. Additional sense code, application client, byte, command, command descriptor block, etc. could all be deleted.

(?)

HP #23
PDF Page 17
3.1.32 sense data
Remove this definition. Not used in text.

(?)

HP #24
PDF Page 18
3.2 Symbols and abbreviations
Format the abbreviations list as a table without row or column lines showing.

(?)

HP #25
PDF Page 18
3.3.4 may
Add a definition of "may not: Keywords indication flexibility of choice with no implied preference."

(?)

HP #26
PDF Page 19
3.3.9 should
Put the period inside the quotes in recommended".

(?)

HP #27
PDF Page 20
4 Overview
1st paragraph
Change "multi-media" to "multimedia"

(?)

HP #28
PDF Page 20
4 Overview
1st paragraph
Change SBC, MMC and SSC to SBC-2, MMC-4, and SSC-2.

(?)

HP #29

PDF Page 20

4 Overview

3rd paragraph

Change "maintains an inventory of volumes and the element address they can be found" to "maintains an inventory of volumes and the element addresses with which they may be accessed."

(?)

HP #30

PDF Page 20

4 Overview

3rd paragraph

Change "identifying" to "identifies"

(R) Sentence does not parse correctly if changed.

HP #31

PDF Page 20

4 Overview

2nd paragraph

"The element types are storage, data transfer, medium transport, and import/export."

Make this into an a) b) c) list, sorted like other references:

a) medium transport;

b) storage;

c) import/export; and

d) data transfer

(?)

HP #32

PDF Page 21

4 Overview

Figure 2 Example independent media changer and several places in the text "Data Transport Element" should be "Data transfer element"

(A) Changed 'transport' to 'transfer'.

HP #33

PDF Page 21

4 Overview

Figure 2

Move the "Medium Changer Logical Unit" closer to the shaded box on the bottom (perhaps make the box bigger so the label fits inside the box) and change it to "Media changer logical unit."

(A) Changed 'Medium' to 'Media' and moved label.

HP #34

PDF Page 21

4 Overview

Figure 2 - Example independent media changer device.

Remove the period at the end of the figure title

(A) Period removed.

HP #35

PDF Page 21

4 Overview

Figure 2 - Example independent media changer device

Add some "volume"s to the picture.

(R) I wish to avoid clutter in this diagram.

HP #36

PDF Page 21

4 Overview

In "via the same SCSI ID as the primary device, or via a different SCSI ID." SCSI ID is a parallel-SCSI specific term. Use "target port identifier" instead.

(?)

HP #37

PDF Page 21

4 Overview

Figure 2 - Example independent media changer device

Add a "primary device" connected to each "data transport element".

The "port" is part of the primary device rather than the element.

Add a "media changer" box around all the elements and the medium changer logical unit, but not around the primary devices.

(?)

HP #38

PDF Page 21

4 Overview

Add a figure showing the attached media changer model too.

(?)

HP #39

PDF Page 21

4 Overview and global

The document uses "domain" or "media changer's domain" a few times. This is easily confused with SCSI domain. I think you can phrase it such that the elements are just part of the media changer device itself rather than its domain. For example, the sentence on the bottom of page 21 could just be "Media changers shall be capable of reporting the full or empty status of any element."

(?)

HP #40

PDF Page 21

4 Overview

Bottom of page 21

Change "several element types" to "several elements" - movement is by specific address, not element type.

(P) Changed 'several element types' to 'elements'.

HP #41

PDF Page 21

4 Overview

Bottom of page 21

"Media changers shall be.. in its domain" mixes plural and singular. Change to "Media changers...in their domains" or "A media changer...in its domain"

(?)

HP #42

PDF Page 21

4 Overview

Mention that multiple media changers may be cascaded with their import/export elements in this section.

(?)

HP #43

PDF Page 22

5.1 Independent media changer

Change "Independent media changers for the SMC-2 standard respond to" to "Independent media changers respond to"

(A) Text changed.

HP #44

PDF Page 22

5.1 Independent media changer

Add command after LUN in the 3rd paragraph

(?)

HP #45

PDF Page 22

5.2 Attached media changer

The definition of primary device includes that it is not a media changer, so "a primary device that is not a media changer." can just be "the primar device." Somewhere in this section, add a list of primary device types (block, sequential, multimedia)

(?)

HP #46

PDF Page 22

5.3 Media changer elements

Move this text into 5.3.1(Overview)

Move 5.4 into 5.3.2 (Medium transport element)

Move 5.5 into 5.3.3 (Storage element)

Move 5.6 into 5.3.4 (Import/export element)

Move 5.7 into 5.3.5 (Data transfer element)

Move 5.8 into 5.3.6 (Element status maintenance requirements)

(D)

HP #47

PDF Page 22

5.3 Media changer elements

Make the bulleted list into an a) b) c) list, and don't capitalize each word.

(A) Changed list format.

HP #48

PDF Page 22

5.3 Media changer elements

Change "may provide storage for zero or one volume." to "is capable of storing one volume."

(R) SMC-2 allows configurations with import/export or medium transport elements that are not capable of storing a volume.

HP #49

PDF Page 23

Global (technical)

Remove:

RESERVE ELEMENT (6)

RESERVE ELEMENT (10)

RELEASE ELEMENT (6)

RELEASE ELEMENT (10)

in favor of PERSISTENT RESERVE OUT for all the same reasons that they have been obsoleted from SPC-3 and other command set standards. SPC-3 section 5.9 also needs to be updated to remove its references to them.

(?)(T) I am not aware of any host software that depends on either version of the RESERVE ELEMENT and RELEASE ELEMENT commands. It may be possible to obsolete RESERVE ELEMENT and RELEASE ELEMENT, and have Table 2 point to SMC-2 for RESERVE (6)/(10), RELEASE (6)/(10).

HP #50

PDF Page 23

5.3 Media changer elements

Change "import export" to "import/export"

(A) Text changed.

HP #51

PDF Page 23

5.3 Media changer elements

Change "device capabilities page" to "Device Capabilities mode page"

(A) Text changed.

HP #52

PDF Page 23

5.3 Media changer elements

Change "Each element type shall be assigned a contiguous number range" to "Each element type shall be assigned a contiguous range of element addresses" and adjust the rest of the paragraph accordingly

(?)

HP #53

PDF Page 23

5.4 Medium transport element

Change "transport geometry mode parameters." to "Transport Geometry Parameters mode page."

(A) Text changed.

HP #54

PDF Page 24

5.4 Medium transport element

Change "medium transport element address" to "medium transport address" in small caps

(A) Text changed.

HP #55

PDF Page 24

5.5 Storage element

Change "SMC-2 device" to "media changer"

(P) Changed to "device".

HP #56

PDF Page 24

5.6 Import/export element

Add space to "that are"

(A) Space added.

HP #57

PDF Page 24

5.6 Import/export element

Remove "when present in a media changer logical unit."

(A) Text removed.

HP #58

PDF Page 25

5.7 Data transfer element

Change "media, see the device capabilities mode parameters." to media; the Device Capabilities mode page indicates whether independent storage is provided."

(P) Name of page changed and clause reference added.

HP #59

PDF Page 25

5.8 Element status maintenance requirements

Change i.e., to e.g.,

(?)

HP #60

PDF Page 25

5.9 Volume tag information

Move the 5.9 text into 5.9.1 Overview

Move 5.10 into 5.9.2 (Primary and alternate volume tag information) Move 5.11 into 5.9.3 (Volume tag information format)

(?)

HP #61

PDF Page 25

5.9 Volume tag information

Change "or by other means which may be vendorspecific." to "or by vendor-specific means."

(R) Text was changed, but we need to leave open the possibility of other not vendor specific means.

HP #62

PDF Page 25

5.9 Volume tag information

Change "whether" to "regardless of whether"

(?)

HP #63

PDF Page 25

5.9 Volume tag information

Remove "or a volume."

(A) Text removed.

HP #64

PDF Page 25

5.9 Volume tag information

Change "The media changer command set definition" to "This standard"

(A) Text changed.

HP #65

PDF Page 25

5.9 Volume tag information

Change bulleted list to an a) b) c) list.

(A) List format changed.

HP #66

PDF Page 26

5.10 Primary and alternate volume tag information

Change "partition of a volume" to "other side of a volume"

(P) Changed "partition" to "side".

HP #67

PDF Page 26

5.10 Primary and alternate volume tag information

Change "All volumes have" to "All volumes shall have"

(A) Added "shall".

HP #68

PDF Page 26

5.11 Volume tag information format

Table 1 - Volume tag information format

Add (MSB) and (LSB) to the volume sequence number field (but not to the volume identification field)

(A) Information added to table.

HP #69

PDF Page 26

5.10 Primary and alternate volume tag information

Change "MOVE MEDIUM" to "MOVE MEDIUM or EXCHANGE MEDIUM" since both have INVERT bits.

(A) Changed in two places.

HP #70

PDF Page 26

5.10 Primary and alternate volume tag information

Once a volume is loaded inverted, do the primary and alternate volume tags swap roles? Or is the primary tag always the primary tag?

(?) Good question.

HP #71

PDF Page 27

6.1 Summary of commands for independent media changers
Table 2 - Commands for independent media changers
This table should fit on one page if the rows are separated by less whitespace.

(?)

HP #72

PDF Page 27

6.1 Summary of commands for independent media changers

Table 2 - Commands for independent media changers

Delete:

CHANGE DEFINITION 40h O SPC

Add "Operation code 40h is obsolete" after the table.

(?) Is it ok to just delete the line? CHANGE DEFINITION was never defined in SMC, only referenced by it.

HP #73

PDF Page 27

6.1 Summary of commands for independent media changers

Table 2 - Commands for independent media changers

Change Subclause to Reference

(?)

HP #74

PDF Page 27

6.1 Summary of commands for independent media changers

Table 2 - Commands for independent media changers

Make PERSISTENT RESERVE IN and OUT mandatory (and have SPC-3 updated to match)

(R)(T) - I would like to release SMC-2 with SPC-2 as the primary command set, not SPC-3 (except for the optional READ and WRITE ATTRIBUTE commands.

HP #75

PDF Page 27

6.1 Summary of commands for independent media changers

Table 2 - Commands for independent media changers

SPC-3 Table B.2 lists RESERVE/RELEASE ELEMENT 6/10 as mandatory.

SPC-3 and SMC-2 should match.

(R) SMC-2 uses SPC-2 for the primary command set.

HP #76

PDF Page 27

6.1 Summary of commands for independent media changers

Table 2 - Commands for independent media changers

Add the following optional commands:

REZERO UNIT 01h SPC-3

ACCESS CONTROLS IN 86h SPC-3

ACCESS CONTROLS OUT 87h SPC-3

MAINTENANCE IN A3h SCC-2
MAINTENANCE OUT A4h SCC-2
REDUNDANCY GROUP IN BAh SCC-2
REDUNDANCY GROUP OUT BBh SCC-2
SPARE IN BCh SCC-2
SPARE OUT BDh SCC-2
VOLUME SET IN BEh SCC-2
VOLUME SET OUT BFh SCC-2
REPORT DEVICE IDENTIFIER A3h/05h SPC-3
REPORT TARGET PORT GROUPS A3h/0Ah SPC-3
REPORT ALIASES A3h/0Bh SPC-3
REPORT SUPPORTED OPERATION CODES A3h/0Ch SPC-3
SET DEVICE IDENTIFIER A4h/06h SPC-3
SET TARGET PORT GROUPS A4h/0Ah SPC-3
CHANGE ALIASES A4h/0Bh SPC-3

(?)

HP #77

PDF Page 28

6.2 Summary of commands for attached media changers

Change MOVE MEDIUM ATTACHED * to MOVE MEDIUM *

Change READ ELEMENT STATUS ATTACHED * to READ ELEMENT STATUS *

(?) I think this can be done once the A5 and B8 opcodes are made obsolete.

HP #78

PDF Page 28

6.2 Summary of commands for attached media changers

SPC-3 lists A7h and B4h as "M" for media changer devices. They are really not allowed for independent changers (meaning they should not be in the SPC-3 column at all), but are mandatory for attached changers. SPC-3 may need another column to differentiate attached media changers from independent.

(?)(T) At this point, making the A5 and B8 opcodes obsolete is appropriate.

HP #79

PDF Page 28

6.1 Summary of commands for independent media changers

This is incomplete:

"Operation codes 0Ch and C0h through FFh are vendor-specific." It should say:

"Operation codes 02h, 05h, 06h 08h, 09h, 0Ah, 0Bh, 0Ch, 0Dh, 0Eh, 0Fh, and C0h through FFh are vendor-specific." to match SPC-3.

(?) Update list to match SPC-2.

HP #80

PDF Page 28

6.1 Summary of commands for independent media changers

The sentence "All other operation codes are reserved." needs to be preceded by a list of obsolete operation codes: "Operation code 40h (CHANGE DEFINITION) is obsolete."

(?)

HP #81

PDF Page 28

6.2 Summary of commands for attached media changers

Table 3 - Commands for attached media changers

Rather than use * in the command name column, create a new type code other than 0 that represents "optional operation codes for use by sequential devices only."

(?) Not needed if the codes are made obsolete.

HP #82

PDF Page 30

6.3 Commands allowed in the presence of various reservations

Table 4 - Reservation table

Remove Column A if RESERVE ELEMENT/RELEASE ELEMENT are obsoleted.

(?)

HP #83

PDF Page 30

6.3 Commands allowed in the presence of various reservations

Table 4 - Reservation table

If RESERVE ELEMENT/RELEASE ELEMENT remain, The "Allowed" for RELEASE ELEMENT needs a note that "The reservation is not released." (as done in SPC-2)

(?) Not needed if we obsolete RESERVE/RELEASE element.

HP #84

PDF Page 31

6.4 EXCHANGE MEDIUM command

and globally in all the command descriptions

Delete the paragraph: "A reservation conflict shall occur if an EXCHANGEMEDIUM command is received from an initiator other than the one holding a logical unit or element reservation." This is covered by the big reservation table in 6.3.

(A) Paragraph deleted for all commands.

HP #85

PDF Page 31

6.4 EXCHANGE MEDIUM command

Remove comma from "address," in the second line.

(A) Comma deleted.

HP #86

PDF Page 32

6.4 EXCHANGE ELEMENT command

On Page 32 define "empty," as "empty (i.e., set to zero)".

(R) Empty indicates there is no medium stored in the element, not the contents of the parameter field.

HP #87

PDF Page 32

6.4 EXCHANGE MEDIUM command

Add period after FULL on page 32.

(A) Period added.

HP #88

PDF Page 32

6.4 EXCHANGE MEDIUM command

Change INV1 to INVERT FIRST and INV2 to INVERT SECOND to better match wording in 5.10 and MOVE MEDIUM.

(R) No room in the table for a longer name for these one bit fields.

HP #89

PDF Page 33

6.5 INITIALIZE ELEMENT STATUS command and global

Change "Initiator" to "initiator" or "application client".

(A) Changed to "application client".

HP #90

PDF Page 34

6.6 INITIALIZE ELEMENT STATUS WITH RANGE command

First paragraph is missing "The INITIALIZE" before "ELEMENT"

(A) Text modified.

HP #91

PDF Page 35

6.7 MOVE MEDIUM command

Table 8 - MOVE MEDIUM command

Change "INV" to "INVERT" to match text throughout the document

(A) Field name changed in table.

HP #92

PDF Page 35

6.7 MOVE MEDIUM command

Change title to "MOVE MEDIUM and MOVE MEDIUM ATTACHED commands" in the section header and table 8 header

(?) This is moot if we drop the MOVE MEDIUM ATTACHED name.

HP #93

PDF Page 35

6.7 MOVE MEDIUM command
Add to "OPERATION CODE" "(A5h or A7h)

(?) Moot if A5 opcode is obsoleted.

HP #94
PDF Page 35
6.7 MOVE MEDIUM command and global
Change "target" to "media changer" in first sentence of this section and elsewhere in the document where appropriate.

(P) Change most instances of "target" to "device server".

HP #95
PDF Page 35
6.7 MOVE MEDIUM command and globally
Change "target" to "logical unit" near bottom of page (twice) and elsewhere in the document where discussing CHECK CONDITIONS and other logical unit states.

(P) Changed "target" to "device server" in these cases.

HP #96
PDF Page 38
6.9 READ ATTRIBUTE command
Table 10 - READ ATTRIBUTE command and
6.17 WRITE ATTRIBUTE command
Table 34 WRITE ATTRIBUTE command
Make Volume number and Partition number small caps

(A) Format changed.

HP #97
PDF Page 38
6.9 READ ATTRIBUTE command
Make "element address" small caps below the table

(A) Changed to small caps.

HP #98
PDF Page 38
6.9 READ ATTRIBUTE command
Table 10 - READ ATTRIBUTE command
Change mixed capital/small cap in ELEMENT TYPE CODE and ALLOCATION LENGTH to all small cap

(A) Format changed.

HP #99
PDF Page 39
6.9 READ ATTRIBUTE command
The ELEMENT LIST service action line looks like a section header. If that's the intention, move the previous text into 6.9.1 and make this 6.9.2 to avoid hanging paragraphs.

(D)

HP #100

PDF Page 39

6.9 READ ATTRIBUTE command

Table 12 - Parameter data for ELEMENT LIST service action

Make Element type code and First Element Address small caps

(A) Changed to small caps.

HP #101

PDF Page 39

6.9 READ ATTRIBUTE command

Table 11 - READ ATTRIBUTE service action code

Add a double line below the header row.

(A) Table format changed.

HP #102

PDF Page 40

6.10 READ ELEMENT STATUS command

Table 13 - READ ELEMENT STATUS command

After "OPERATION CODE" add "(B8h or B4h)"

(?) Not needed if we obsolete optional codes.

HP #103

PDF Page 40

6.10 READ ELEMENT STATUS command

Move the hanging paragraphs into a new 6.10.1

(?)

HP #104

PDF Page 40

6.7 READ ELEMENT STATUS command

Change title to "READ ELEMENT STATUS and READ ELEMENT STATUS ATTACHED commands" in the section header, table 13 header, and appropriate text

(?)

HP #105

PDF Page 41

6.9 READ ATTRIBUTE command

Table 14 - Element type code

Left justify Description

(A) Left justified header.

HP #106

PDF Page 41

6.9 READ ATTRIBUTE command

Table 14 - Element type code

In table 10, table 12, table 16, etc. ELEMENT type code is an 8 bit field. In table 13 and 14, it's treated as a 4 bit field. If Table 14 is the reference for all locations, it needs to mention the disposition of values 10h-FFh.

(P)(T) Changed Element type code fields in Table 10, 12 and 16 to 4 bits.

HP #107

PDF Page 41

6.10 READ ELEMENT STATUS command

Table 14 - Element type code

Remove comma in "reported,"

(A) Comma deleted.

HP #108

PDF Page 41

6.10 READ ELEMENT STATUS command

After "device identifiers," add "(see 6.10.7)" - this is the first time the term is used. Since SAM-2 now has a well defined "SCSI device identifier", a name change for element device identifiers may be a good idea.

(P) Clause reference added. Since the device identifiers returned are the same as defined by SAM, there is no need to change names.

HP #109

PDF Page 41

6.10 READ ELEMENT STATUS command

6.13 REQUEST VOLUME ELEMENT ADDRESS command (technical)

This is misleading:

"If the ALLOCATION LENGTH is not sufficient to transfer all the elementdescriptors, the logical unit shall transfer all those descriptors that can be completely transferred and this shall not be considered an error."

If a descriptor cannot be "completely transferred" it should be partially transferred. The data structure returned must not change at all based on allocation length.

The same wording is on page 14 and 57. Page 42 may need some clarification too.

(P) Wording changed based on comments from RW.

HP #110

PDF Page 42

6.10 READ ELEMENT STATUS command,

6.10.1 Element status data and globally

Change "6.10.2 through 6.10.7" to "6.10.2, 6.10.3, 6.10.4, 6.10.5, 6.10.6, and 6.10.7"

(?)

HP #111
PDF Page 42
6.10 READ ELEMENT STATUS command
6.10.1 Element status data
NOTE 6
Change "can" to "may"

(A) Text changed.

HP #112
PDF Page 45
6.10.3 Medium transport element descriptor
Page 45 and global
Change IDENTIFIER LENGTH to IDENTIFIER LENGTH

(A) Changed in four places.

HP #113
PDF Page 45
6.10.3 Medium transport element descriptor (technical)
If you invert the same volume twice, does this bit go back to zero? Or it is always one after the first inversion?

(?)

HP #114
PDF Page 51
6.10.6 Data transfer element descriptor (technical)
The 8-bit SCSI BUS ADDRESS field is unsuitable for Fibre Channel, Serial Attached SCSI, iSCSI, and other modern SCSI transport protocols. The 3-bit LOGICAL UNIT NUMBER field is out of date even for parallel SCSI (non-packetized has a 6-bit LUN field). All other protocols support 8-byte LUNs. Both these fields should be obsoleted in favor of a new solution using the EXTENDED COPY target descriptor (aka logical unit descriptor) data format (with alias list support for iSCSI). For compatibility with old software, require that NOT BUS be set to one and LU VALID (should be called LUN VALID) be set to zero.

(?)(T) Device Identifiers already provide a method for determining how devices are interconnected. We should just obsolete these old fields.

HP #115
PDF Page 56
6.13 REQUEST VOLUME ELEMENT ADDRESS command (technical)
How about making this command fail if it is run by an initiator different than the one that send the SEND VOLUME TAG command. Add an additional sense code to report this reason, like WRITE BUFFER/READ BUFFER do for accesses to the echo buffer in SPC-3.

(?)

HP #116
PDF Page 56
6.13 REQUEST VOLUME ELEMENT ADDRESS command
In element address description, change "gives" to "specifies"

(?)

HP #117
PDF Page 56
6.13 REQUEST VOLUME ELEMENT ADDRESS command
Table 25 - REQUEST VOLUME ELEMENT ADDRESS command
Move Table 25 up under the first paragraph of the section where it is introduced. It is currently floating on the next page.

(?)

HP #118
PDF Page 57
6.13 REQUEST VOLUME ELEMENT ADDRESS command
Table 26 - Volume element address header
Move Table 26 up after the paragraph in which it is introduced.

(?)

HP #119
PDF Page 66
6.16 SEND VOLUME TAG command
On page 66, change "will match" to "matches" twice and "will meet" to "meets"

(P) Changed "will match" to "shall match", "will meet" to "meets".

HP #120
PDF Page 67
6.17 WRITE ATTRIBUTE command.
Remove period from section header.

(A) Period removed.

HP #121
PDF Page 68
7 Parameters
Move the hanging paragraph into a new 7.1.

(?)

HP #122
PDF Page 68
7.1 Diagnostic parameters
Change table contents to:
00h Supported diagnostic pages
01h - 1Fh SES diagnostic pages (Reference SES)
10h - 3Fh Diagnostic pages assigned by SPC-3 (Reference SPC-3)

40h - 7Fh Reserved (for this standard)
80h - FFh Vendor-specific diagnostic pages
(note: SES is trying to take ownership of 10h-1Fh too)

(?)

HP #123
PDF Page 68
7.1 Diagnostic parameters
Table 35 - Diagnostic page codes
Change Subclause to Reference

(A) Header changed.

HP #124
PDF Page 68
7.2.1 Log page codes for independent media changers.
The log page section header includes "for independent media changers" but diagnostic pages and mode pages do not. They should be consistent, since all of the pages are for independent media changers.

(?)

HP #125
PDF Page 69
7.2.2 TapeAlert page.
Change title to "TapeAlert log page"

(A) Title changed.

HP #126
PDF Page 69
7.2.1 Log page codes for independent media changers
Table 36 - Log page codes
Make capitalization match new rules (mixed case; always say "log page" afterwards). Make sure all the page codes use h rather than H.
The log pages should be:
00h Supported Log Pages
06h Non-Medium Error log page
07h Last n Error Events log page
0Bh Last n Deferred Errors log page
0Dh Temperature log page
0Eh Start-Stop Cycle Counter log page
0Fh Application Client log page
10h Self-Test Results log page
2Eh TapeAlert log page (this must be added to SPC-3)
2Fh Informational Exceptions log page
30h - 3Fh Vendor-specific
All others Reserved

(?)

HP #127

PDF Page 69

7.2.2 TapeAlert page

This should be done "EDITORS NOTE: TapeAlert log page description should be moved here and renamed to avoid the reference to SSC."

(?)

HP #128

PDF Page 69

7.2.1 Log page codes for independent media changers

Table 36 - Log page codes

Subclause to Reference

(A) Header changed.

HP #129

PDF Page 70

7.3 Mode parameters

Move the hanging paragraphs into a new 7.3.1.

(?)

HP #130

PDF Page 71

7.3 Mode parameters

Table 37 - Mode page codes

Make capitalization match SPC-3 (mixed case; always use "mode page").

Add 02h and 0Ah to SPC-3.

1Dh and 1Eh are swapped in SPC-3.

20h-3Eh do NOT require page format.

(?)

HP #131

PDF Page 72

7.3.1 Device capabilities mode page and global

Change capitalization to "Device Capabilities mode page"

(A) Text changed.

HP #132

PDF Page 72

7.3.1 Device capabilities mode page

Change "initiator" to "application client"

(A) Text changed.

HP #133

PDF Page 73

7.3.1 Device capabilities mode page

Change "destinations, that" to "destinations and that" on page 73

(A) Text changed.

HP #134

PDF Page 73

7.3.1 Device capabilities mode page

Page 73 asserts that "The value of STORST is one by the definition of that type (see 5.5)." However, storage elements are not required to be present, so STORST is only one if a storage element exists. Reword this sentence to make that more apparent.

(?)

HP #135

PDF Page 73

7.3.1 Device capabilities mode page

Change "Those which are not valid will be rejected with ILLEGAL REQUEST." To "MODE MEDIUM commands which are not valid shall be rejected with a sense key of ILLEGAL REQUEST (see 6.7). and make a similar change in the EXCHANGE MEDIUM paragraph that follows.

(P) Text changed in two places.

HP #136

PDF Page 74

7.3.2 Element address assignment mode page and global

Change capitalization to "Element Address Assignment mode page"

(A) Text changed.

HP #137

PDF Page 75

7.3.3 Transport geometry parameters mode page and global

Change capitalization to "Transport Geometry Parameters mode page"

(A) Text changed.

HP #138

PDF Page 75

7.3.2 Element address assignment mode page and global

Change "The sense key shall be ILLEGAL REQUEST and the additional sense code PARAMETER VALUE INVALID." to "The sense key shall be set to ILLEGAL REQUEST and the additional sense code shall be set to PARAMETER VALUE INVALID." Make similar changes throughout the document.

(?)

HP #139

PDF Page 75

7.3.1 Element address assignment mode page

After "If the address ranges defined for any of the element types overlap," add "for a MODE SELECT command"

(A) Text added.

HP #140

PDF Page 75

7.3.3 Transport geometry parameters mode page

Move "(Other than the default transport element address of zero.)" into the previous sentence: "transport element (other than...zero)."

(P) Text has been modified according to comment from RW.

HP #141

PDF Page 76

7.3.3 Transport geometry parameters mode page

NOTE 15

Remove parenthesis and brackets from "(The individual transport element is addressed [not the robotics subsystem]. An element is defined to be a place where a unit of media may be at any point in time. See clause 5.)"

(A) Text changed.

HP #142

PDF Page 77

Annex A

This section needs an A.1 section with introductory text. The table needs a table title and number. Make the last horizontal line above the key a double-line.

(?) Double line added. Need to consider introductory text.

HP #143

PDF Page 82

Annex B Bibliography

Delete Annex B. The Normative references section should list other standards of import (any standard mentioned in the text can be listed there).

(?)

HP #144

PDF Page 22

5.3 Media changer elements

The sentence, 'The point in time during movement when a volume is considered in a different element is implementation dependent.' does not specify an element that a volume is in at the beginning of the movement. Hence the phrase '...when a volume is considered in a different element ...' begs the question, different from what element? Suggest changing to, 'When moving from one element to another, the point in time when the volume changes element address depends on the implementation.'

(?)

HP #145

PDF Page 29

6.3 Commands allowed in the presence of various reservations
Change 'registrantsonly' to 'registrants only'

(A) Space added.

HP #146

PDF Page 30

Table 4

Change 'RESERVE ELEMENT (6)/RELEASE ELEMENT (10)' to 'RESERVE
ELEMENT (6)/RESERVE ELEMENT (10)'

(A) Table entry changed.

HP #147

PDF Page 37

6.8 Position to element

The description of this command fails to include what happens under exception conditions. Add, 'The MEDIUM TRANSPORT ADDRESS field specifies the medium transport element used to execute this command. The default transport element address of zero may be used. If the MEDIUM TRANSPORT ADDRESS element has not been assigned or that element address has been assigned to a different element type, the logical unit shall return CHECK CONDITION status. The sense key shall be ILLEGAL REQUEST and the additional sense code INVALID ELEMENT ADDRESS.'

'The DESTINATION ADDRESS field may represent a storage element, an import/export element, a data transfer element, or a medium transport element.'

If the address specified has not been assigned to a specific element of the media changer, the target shall return CHECK CONDITION status. The sense key shall be ILLEGAL REQUEST and the additional sense code INVALID ELEMENT ADDRESS.'

'The device capabilities MODE SENSE page (see 7.3.1), provides a matrix with the supported source element or destination element combinations for the MOVE MEDIUM command.'

'An INVERT bit of one specifies that the volume shall be inverted or rotated prior to depositing the medium into the DESTINATION ADDRESS element. If the media changer does not support volume rotation for handling double-sided media, the INVERT bit should be set to zero. If this bit is one, a target that is not capable of volume rotation shall return CHECK CONDITION status. The sense key shall be ILLEGAL REQUEST and the additional sense code INVALID FIELD IN CDB.'

(D)

HP #148

PDF Page 38

6.9 Read attribute command

Change 'medium reisding in a data' to 'medium residing in a data'.

(A) Text changed.

HP #149

PDF Page 38

Table 10

Describes a fourteen byte command. Byte numbers 8 and 9 duplicated.

(A) Table has been fixed to match SPC-3.

HP #150

PDF Page 38

6.9 Read attribute command

Change 'Not' to 'Note'.

(A) Text changed.

HP #151

PDF Page 39

Table 12

Does not explain how a medium changer returns a non-contiguous list of element addresses using the Element List service action.

(?)

HP #152

PDF Page 39

Note 5

Change 'Since all the element addresses shall' to 'Since all element addresses may not'.

(?)

HP #153

PDF Page 50

Table 20

Does not provide support for multi-ported data transport element.

(R) Fields describing SCSI BUS ADDRESS, LUN etc for an attached drive should be marked obsolete. Configuration mapping can be solved using Device Identifiers.

HP #154

PDF Page 62

6.15.2 Superseding reservations

Change 'extent list' to 'element descriptor list'.

(A) Text changed.

Comments attached to Abs ballot from Mr. George O. Penokie of

IBM / Tivoli Systems:

IBM 1. Not materially affected by this standard.

(A)

Comments attached to Abs ballot from Mr. Edward A. Gardner of
Ophidian Designs:

Ophidian 1. I have no particular competence or interest in medium
changers.

(A)

Comments attached to YesC ballot from Mr. Charles Binford of
Pirus Networks:

Pirus 1. The change bars and strikeouts need to be removed.
Especially in section 6.3.

(D)

Comments attached to No ballot from Mr. Paul Entzel of
Quantum Corp.:

Q1. Section 3.1.1. The term "command response data" is not
defined in this standard, SAM, SAM-2, SPC, or SPC-2. I think the
term that should be used here is simply "data".

(P) Used "sense data" instead.

Q2. Section 3.1.2. Extent reservations were made obsolete in SPC-
2. This standard refers to Element reservations instead of Extent
reservation. Even if Extent reservations were to remain in this
standard, this definition does not make sense for a medium changer
device.

(?)

Q3. Section 4, forth paragraph. Is it possible to reserve the
Medium Transport element with an element reservation? If so, what
effect would that have on a command that otherwise would not have
reservation problems (the source and destination elements are not
reserved)?

(?) The command should be rejected with "RESERVATION CONFLICT".
Do we need to add additional text?

Q4. Section 5.1, first paragraph. "mediachanger" needs a space.

(A) Space added.

Q5. Section 5.2, first paragraph. The wording of the first sentence in this paragraph sounds as if MCHNGR will only be set if the device supports an attached medium changer. That is not consistent with SPC or SPC-2. Suggest the wording be changed to: "An attached medium changer is part of a device server that returns a value other than 8h in the PERIPHERAL DEVICE TYPE field (See SPC-2) of an INQUIRY command response data. A device that supports the attached media changer command set shall set the MCHNGR bit to one in its standard INQUIRY data (See SPC-2). This bit may also be set to one if the device server detects that the device is embedded within a independent media changer device."

(?)

Q6. Section 5.6, first paragraph. "thatare" needs a space.

(A) Space added.

Q7. Section 5.9, second paragraph. I'm not sure about this requirement anymore. With the inclusion of MAM in many devices and medium now, should we consider removing this requirement? When medium changers include MAM readers/writers can it save the SEND VOLUME TAG information in the MAM?

(?) Yes, some clarification may be needed.

Q8. Section 5.10, first paragraph. The implied definition of "partition of a volume" as the term is used here is different than other SCSI devices. A clarification of this term would be helpful.

(P) The term "partition" was changed to "side" to avoid confusion.

Q9. Section 6.1, Table 2. It seems kind of silly to release this standard based off of SPC when SPC-2 is so far along and the base for other device standards that are farther along in the process than this one (SSC-2 and SAM-2, for example).

(A) Table entries changed to SPC-2.

Q10. Section 6.2, Table 3. I don't understand this table. Under what circumstances is a device required to support the mandatory commands in this table? If a sequential device supports opcodes A7h and B4h why would it also support A5h and B8h?

(?) The A5h and B8H opcodes were used by some devices before SMC was published. They should be made obsolete in SMC-2.

Q11. Section 6.3, definition of Allowed. "registrantonly" need a space.

(A) Space added.

Q12. Section 6.3, Table 4. Since Medium Changers support reservations of elements, this table needs to describe the impact of using this feature. For instance, an INITIAILIZE ELEMENT STATUS WITH RANGE should not be affected by reservations if none of the elements in the range are reserved I would think, but it may be affected if the Medium Transport Element is reserved.

(?)

Q13. Section 6.4, first paragraph. This command can do much more than simply exchange medium between to elements. The first sentence of this paragraph should be fixed.

(?)

Q14. Section 6.4, second paragraph. This paragraph is partly redundant with Table 2 and wholly confusing. This standard is the only one I know of that explicitly states the data to be transferred with the command.

(?)

Q15. Section 6.4, third paragraph. This paragraph is redundant with Table 4 but less accurate. It could actually provide more information, such as what elements should be checked for reservation conflicts (source, first destination, second destination, and medium transport).

(P) Paragraphs describing reservation issues with each command have been removed.

Q16. Section 6.5, last paragraph. An "element reservation" for which element?

(P) Paragraph has been removed.

Q17. Section 6.9, the paragraph after Table 10. Spelling error, "reisding" should be "residing".

(A) Text changed.

Q18. Section 6.9, the paragraphs immediately before and immediately after Table 11. The WRITE ATTRIBUTES command was first defined in SPC-3.

(A) Reference changed to SPC-3.

Q19. Section 6.9. The sentence that is only "ELEMENT LIST Service Action" should be a subclause heading.

(D)

Q20. Section 6.9, the paragraph immediately preceding Table 12. It is completely unclear as to when this information is available, what to do if it changes, or how reservations affect it.

(?)

Q21. Section 6.9, Table 12. This table needs to be broken into 2 tables.

The first table contains the Available Data field and another field that is described as "Element List Element Descriptors" running from byte 4 through n. The second table is the Element List Element Descriptor table with the Element Type Code in byte 0, the First Element Address in bytes 1 and 2, and the Number Of Elements field in bytes 3 and 5. We should re-evaluate this descriptor if we don't like the odd size.

(D)

Q22. Section 6.10, first paragraph. Since this clause has subclauses, all of this stuff needs to go into a subclause 6.10.1. The same comment applies to section 6.9 (after the ELEMENT LIST Service Action header is fixed), 6.11, 6.12, 6.14, and 6.15.

(?)

Q23. Section 6.10, second paragraph. Is a Sequential device with an attached medium required to support both B4h and B8h opcodes, or only one of these?

(?) The optional B8h opcode should be made obsolete.

Q24. Section 6.10, fifth paragraph. Element reservation for which element?

(P) Paragraph has been removed.

Q25. Section 6.10.1, second paragraph. No requirement is included for the order in which the pages or descriptors are returned. Is it acceptable that the element addressed by the First Element Address Reported field is not the first element in the list?

(?)

Q26. Section 6.10.2, first paragraph. Why would an element status page that had zero descriptors be included in the data? Is there an implied requirement that pages be returned for element types that have no elements that meet the reporting criteria?

(?)

Q27. Section 6.10.5, Table 19. cmc should be small caps.

(A) Changed to small caps.

Q28. Section 6.10.6. One could argue that in the fields NOT BUS, ID VALID, SCSI BUS ADDRESS, LU VALID, and LUN are obsolete with today's transport layers. If they remain, they need their descriptions changed to accommodate other transport layers. Three bits of LUN is not nearly enough for most transport layers in use today (at least 6 bits, 8 bytes would be better).

(?) Obsolete would be the best solution.

Q29. Section 6.13, fifth paragraph. The last sentence in this paragraph is dangerous. Since the CDB contains an ELEMENT TYPE field and an ELEMENT ADDRESS field, elements can be requested out of order. This sentence does not account for that. Suggested rewording: "Once information for a given element has been reported, it will not be reported again for subsequent REQUEST VOLUME ELEMENT ADDRESS commands until another SEND VOLUME TAG command has completed".

(?)

Q30. Section 6.14, first paragraph. Since this clause has subclauses, a subclause heading is required before this first paragraph.

(D)

Q31. Section 6.14.1, second paragraph. This requirement has the effect of disallowing an initiator from reserving the entire unit if it holds any element reservations. If that is not desired, reword to: "If the unit is reserved by another initiator the target shall respond by returning RESERVATION CONFLICT. If the ELEMENT bit is set to one, and any element in the Element List is reserved by another initiator, the target shall respond with RESERVATION CONFLICT."

(?)

Q32. Section 6.12.1, third paragraph. This paragraph is redundant with subcluse 6.3. If the editor chooses to keep it, it should be reworded to:

"If, after processing a RESERVE ELEMENT command with an ELEMENT bit set to zero, any other..."

(?)

Q33. Section 6.14.2, general comment. The PERSISTENT RESERVE IN

and PR OUT commands are intended to replace RESERVE and RELEASE because they can support the transport layers of the future. For all other device types, RESERVE and RELEASE have been obsoleted recently. The one major drawback of PR IN and PR OUT with respect to SMC-2 is the inability to reserve blocks of elements with a single command. Should we fix that flaw in PR OUT and PR IN now and obsolete RESERVE and RELEASE as the other device types have done?

(?)

Q34. Section 6.14.2, first paragraph. While this feature may be most useful "in a multiple tasking environment" it is possible without such an environment. This phrase should be removed.

(?)

Q35. Section 6.14.2, fifth paragraph. How should overlapped element reservations be handled? If an initiator holds an element reservation for an element and then issues another RESERVE command with ELEMENT set to one that includes that same element but has a different RESERVATION IDENTIFICATION, what should it do? Should it transfer the reservation to the new ID, hold the reservation under both IDs (both must be released to release the element), or reject the second command?

(?)

Q36. Section 6.14.2, eighth paragraph. This implies that a single element descriptor can include elements of multiple types. Are we sure we want element descriptors to span between element types?

(?)

Q37. Section 6.14.2, eighth paragraph. Instead of "last" use "highest" since there is no specified ordering of elements.

(A) Text changed.

Q38. Section 6.14.2, general comment. A paragraph is required to describe the action on a truncated element descriptor.

(?)

Q39. Section 6.15.1. The section header claims third party support is mandatory and the first paragraph after the header claims it is an option. Since it is not even offered in the RESERVE ELEMENT (6) command, it has to be an option.

(?)

Q40. Section 6.15.2. This heading should be removed since it breaks up the 3rd party subclause. The first paragraph after it should be moved to subclause 6.14.2. Note 13 should be moved

also, or even better, removed.

(?)

Q41. Section 6.15.2, fifth paragraph. Since 3rd party support is optional (or at least it should be), the first sentence of this paragraph should be: "Device servers that support 3rd party reservations and device IDs greater..."

(?)

Q42. Section 6.15.2, sixth paragraph. There is no paragraph that describes what is expected for other combinations of LONGID and ELEMENT.

(?)

Q43. Section 6.15.2, sixth paragraph. What is the "extent list length"?

(A) Text changed to "element descriptor list length".

Q44. Section 6.15.2, Table 30. The reference in the Element Descriptors field should be Table 28, but it would be better to reference the entire subclause 6.14.2.

(?)

Q45. Section 6.16, second paragraph after Table 32. What is the ASC? How about if the element is empty or inaccessible?

(?)

Q46. Section 6.16, fifth paragraph after Table 32. What is the ASC, most likely Invalid Field in CDB?

(?) Yes.

Q47. Section 6.16, fifth paragraph after Table 33. What is the Sense Key and ASC if it does?

(?)

Q48. Section 6.17, second paragraph. What should the device do if this element address is empty? What if the medium in that element does not support MAM commands or if an error occurs accessing the MAM?

(?)

Q49. Section 7.2.2, editor's note. This sounds like good advice. However, SSC-2 is struggling with this issue still, so perhaps the editor should wait for resolution there.

(?)

Q50. Section 7.3, first paragraph. Add subclause 7.3.1 to cover these paragraphs.

(D)

Q51. Section 7.3, fifth paragraph. Add a sentence that states the Number Of Blocks and Block Length fields must be 0.

(?) Should an SMC-2 device even return a Block Descriptor?

Q52. Section 7.3.1. There is more device capability information that we would like to see standardized in its reporting. Perhaps a reserved byte from this mode page could do that. The information is: Optical Bar Code Reader Present, Volume Tag Save capable, MAM Read capable, and MAM Write capable. It would also be good to report if a SET VOLUME TAG command that modifies a VT will save that information with the device or the medium. We would also like to add a bit to report if the medium changer is managing the cleaning process.

(?)

Q53. Section 7.3.2, last paragraph. According to subclause 5.3, each element type must have a contiguous address range. Each of these paragraphs defines the action to take if MODE SELECT command changes a greater number of elements than the default number. A description of the action to take on an attempt to change the addresses of any number but all of the elements of a specific element type should also be included. It also should be invalid to change the address of any of the elements of type Medium Transport since it must be anchored at 0. Or, Perhaps it is legal to move the Medium Transport elements to another address in which case address 0 acts as an alias. If so, that should be described here, or even better in the Model section.

(?)

Comments attached to No ballot from Mr. Gerald Houlder of Seagate Technology:

Seagate Technology Comments on SMC-2, revision 5
Prepared by Paul Suhler

Editorial comments: 30
Technical comments: 1

Seagate-01
Editorial
Pg 17

Clause 3.1.44

".media and its carrier." -- "Media" is plural; "its carrier" is singular. S/b

".medium and its carrier."

(A) Text changed.

Seagate-02

Editorial

Pg 20

Clause 4, third paragraph, 1st sentence:

".address they can be found." S/b ".addresses at which they can be found."

(P) Text changed, replaced "can" with "may".

Seagate-03

Editorial

Pg 20

Clause 4, third paragraph, 2nd sentence:

".unit reports this inventory when requested as well as identifying." s/b

".unit reports this inventory when requested and identifies."

(A) Text changed.

Seagate-04

Editorial

Pg 22

Clause 5.1, first sentence:

"mediachanger" s/b "media changer"

(A) Space added.

Seagate-05

Editorial

Pg 22

Clause 5.3, first paragraph, last sentence

"INQUIRY command response data" s/b "standard Inquiry data"

(A) Text changed in 5.2, not 5.3.

Seagate-06

Editorial

Pg 24

Clause 5.6, first sentence

"thatare" s/b "that are"

(A) Space added.

Seagate-07

Pg 25

Clause 5.8, first sentence

" When a media changer receives a valid READ ELEMENT STATUS

command with a CURDATA bit of zero, the media changer shall be capable of reporting as command response data various data required by each page type (i.e., full, error, etc.)." This is very awkward and unclear. I don't have an alternative, because the intent isn't clear. ".shall be capable of." doesn't sound like good standards-ese.

(D)

Seagate-08

Editorial

Pg 25

Clause 5.9, second paragraph

" The volume tag information field values shall be independent of any volume identification information recorded on the medium or a volume."

The intent of this is unclear. If the volume tag can come from a label, then why not from information on the medium? Does "shall be independent" mean that it may or may not be the same as some information on the medium.

I see no reason for not deleting the paragraph.

(?) The intent was to state that the volume tag is not the same as the volume label recorded as the first record in some tape formats.

Seagate-09

Editorial

Pg 29

Clause 6.3, second paragraph, second sentence: Needs a comma.

". method see table 4." s/b ". method, see table 4."

(A) Comma added.

Seagate-10

Editorial

Pg 29

Clause 6.3, "allowed" keyword:

"registrantsonly" s/b "registrants only"

(A) Space added.

Seagate-11

Editorial

Pp 31 - 74

Clauses 6 and 7, various CDB and parameter tables

In SPC-2 and SPC-3, for example, tables with multiple-byte fields usually have the MSBs and LSBs indicated and horizontal lines separating bits 7 of successive bytes and bits 0 of successive bytes. This was not done in SMC and is not in SMC-2. Please change.

(A) Table format changed to match other T10 documents.

Seagate-12

Editorial

Pg 36

Clause 6.7, third paragraph

".device capabilities MODE SENSE page." s/b ".device capabilities mode page."

(P) Changed to "Device Capabilities mode page".

Seagate-13

Editorial

Pg 38

Clause 6.9, first sentence: typo:

"Auxillary" s/b "Auxiliary"

(A) Text changed.

Seagate-14

Editorial

Pg 38

Clause 6.9, Table 10: Inconsistent use of small caps.

ELEMENT TYPE CODE, VOLUME NUMBER, PARTITION NUMBER, FIRST ATTRIBUTE ID, and ALLOCATION LENGTH all need to be fixed.

(A) Use of small caps fixed.

Seagate-15

Editorial

Pg 38

Clause 6.9, Table 10

This CDB table was not modified correctly from that in SPC-3:

1. ALLOCATION LENGTH field should be four bytes, 10 - 13.
2. Reserved and CONTROL fields should be 14 and 15, respectively.

(A) Table corrected based on SPC-3.

Seagate-16

Editorial

Pg 38

Clause 6.9, First paragraph after Table 10, second sentence:

typo:

"reisding" s/b "residing"

(A) Text corrected.

Seagate-17

Editorial

Pg 38

Clause 6.9, First paragraph after Table 10, third sentence: typo:

"Not that this field." s/b "Note that this field."

(A) Text corrected.

Seagate-18

Editorial

Pg 39

Clause 6.9, last sentence before and first sentence after Table 11
References to SPC. This command is defined in SPC-3, not SPC-2.
Is a reference to SPC-3 allowed? If not, then snarf field
descriptions from SPC-3.

(A) References changed to SPC-3.

Seagate-19

Editorial

Pg 39

Clause 6.9, Table 12: inconsistent use of small caps
Correct AVAILABLE DATA, ELEMENT TYPE CODE, and FIRST ELEMENT
ADDRESS,

(A) Use of small caps corrected.

Seagate-20

Editorial

Pp 45, 47, 49, 51

Clause 6.10: repeated typo:
"IDENTIFIER LENGTH" s/b "IDENTIFIER LENGTH"

(A) Text corrected in four places.

Seagate-21

Editorial

Pg 50

Clause 6.10.1, Table 20: inconsistent use of small caps
Correct NOT BUS, ID VALID, and LU VALID.

(?) Moot if fields are marked as obsolete.

Seagate-22

Editorial

Pg 51

Clause 6.10.1, third paragraph, last sentence
"lun address" s/b "LUN address"

(A) Corrected text in clause 6.10.6.

Seagate-23

Technical

Pg 51

Clause 6.10.1, third and fourth paragraphs:
This needs an explanation of the value in the SCSI BUS ADDRESS, ID
VALID, and NOT BUS fields for transport layers other than Parallel
SCSI. Probably all fields should be set to zero in such a case.

(?) Obsoleting the fields is another option.

Seagate-24

Editorial

Pg 55

Clause 6.13, fifth paragraph, first sentence: awkward wording:
".shall be able to report." doesn't sound like proper standards-
ese.

(A) Changed to "shall report"

Seagate-25

Editorial

Pg 59

Clause 6.14.2, list bulleted with '-' characters:
Are these steps to be taken in the indicated order? If so, then
the list should be numbered, in accordance with clause 3.4.

(A) Changed to numbered list.

Seagate-26

Editorial

Pg 67

Clause 6.17, WRITE ATTRIBUTE command, last sentence
Reference to SPC-2 is incorrect. If a reference to SPC-3 cannot
be used, then snarf field descriptions from SPC-3.

(A) Changed reference to SPC-3.

Seagate-27

Editorial

Pg 67

Clause 7.2.2, editors note
This needs to be done. Note that changes are being proposed to
the TapeAlert page for SSC-2.

(D)

Seagate-28

Editorial

Pg 79

Annex A table, item 16h: typo:
"perposes" s/b "purposes"

(A) Text corrected.

Seagate-29

Editorial

Pg 80

Annex A Table, line 1Ch: repeated word:
"the the" s/b "the"

(A) Repeated word deleted.

Seagate-30

Editorial

Pg 81

Annex A Table, line 1Eh, columns 5 and 6: two typos:

"occured" s/b "occurred"

(A) Spelling corrected in two places.

Seagate-31

Editorial

Pg 81

Annex A Table, line 1Fh, column 5: typo:

"passthrought" s/b "passthrough"

(A) Text corrected.

Comments attached to No ballot from Mr. Erich Oetting of
Storage Technology Corp.:

STK 1. (T) Pg 15 - Clause 2, Replace SAM with SAM-2.

(?)

STK 2. (T) Pg 15 - Clause 2, Replace SPC with SPC-2.

(A) Reference changed to SPC-2.

STK 3. (T) Pg 18 - Clause 3.2. Replace SAM with SAM-2, and update
all occurances in the document.

(?)

STK 4. (T) Pg 18 - Clause 3.2. Replace SPC with SPC-2, change SPC
to SPC-2 in rest of document except for Read Attribute and Write
Attribute command clauses.

(A) References changed.

STK 5. (E) Pg 18 - Clause 3.2. Add abbrev. for SPC-3.

(A) SPC-3 added.

STK 6. (E) Pg 22 - Clause 5.1. Missing space in "mediachanger".

(A) Space added.

STK 7. (E) Pg 24 - Clause 5.6. Missing space in "that are".

(A) Space added.

STK 8. (E) Pg 24 - Clause 5.7. Delete note 2 and substitute a
paragraph stating that coordination between data transport and
media changer may use ADI or be vendor specific.

(D)

STK 9. (E) Pg 25 - Clause 5.9. Remove extra space in "data descriptor"

(A) Extra space removed.

STK 10.(T) Pg 27 - Clause 6.1, Table 2, Release Element (6), operation code 16h should be 17h.

(A) Opcode changed to 17h.

STK 11.(E) Pg 31 - Clause 6.4. Remove third paragraph starting "A reservation conflict ... ". Reservation rules are already defined by Table 4. Do the same for all other command definitions.

(A) Reservation paragraph removed from all command definitions.

STK 12.(E) Pg 31 - Clause 6.4. Table 2. Replace dashed lines between byte numbers and replace with hairline. Fix same table format problem in rest of document.

(A) Table format changed to match other T10 documents.

STK 13.(E) Pg 32 - Clause 6.4. Last paragraph on page, "a logical unit that is not capable" should be "a device server that is not capable".

(A) Text changed.

STK 14.(E) Pg 38 - Clause 6.9 - Change SPC to SPC-3 in this clause.

(A) Changed reference to SPC-3.

STK 15.(E) Pg 38 - Clause 6.9 - First sentence, "read attribute values to" should be "read attribute values from".

(A) Text changed.

STK 16.(T) Pg 39 - Clause 6.9 - The Element List service action should return a list of only elements with an accessible MAM, yet the format does not provide for handling a non-contiguous list.

(D)

STK 17.(E) Pg 41 - Clause 6.10, Last paragraph on page. Replace "the DVCID bit shall be treated as reserved" with "and the DVCID bit is set to one, the device server shall return Check Condition, Illegal Request, Illegal field in CDB".

(T) Do we wish to force CHECK CONDITION in this case?

STK 18.(T) Pg 51 - Clause 6.10.6 - Text describing the NOT BUS, ID VALID and SCSI BUS ADDRESS fields should be removed. (mark

these fields as obsolete in Table 20).

(?)

STK 19.(T) Pg 51 - Clause 6.10.6 -Text describing the LU VALID and LOGICAL UNIT NUMBER fields should be removed. (mark these fields obsolete in Table 20).

(?)

STK 20.(T) Pg 54 - Clause 6.12.1. Third party release should be obsolete not mandatory. Remove this clause, mark appropriate fields in Table 23 as obsolete and remove Table 24.

(?)

STK 21.(T) Pg 61 - Clause 6.15.1. Third party reservations should be obsolete, not mandatory. Remove this clause and 6.15.2, mark the appropriate fields in Table 29 as reserved and remove Table 30.

(?)

STK 22.(E) Pg 67 - Clause 6.17 - Change SPC-2 to SPC-3.

(A) Reference changed to SPC-3.

STK 23.(E) Pg 69 - Clause 7.2.2 - Remove editors note and replace with description of Tape Alert Log page from SSC.

(?)

Comments attached to YesC ballot from Mr. Paul D. Aloisi of Texas Instruments:

TI 1. Section 1 has a very outdated list of standards, example ? Fast-20 is Obsolete, SPI-3 and SPI-4 should be listed. (see SAM-2 or newer document for an updated list).

(D)

TI 2. Section 2 ? SPC-2 should be the normative reference

(A) Changed to SPC-2.

TI 3. Annex B is a very outdated list

(?)

***** End of Ballot Report *****