

Date: November 06, 2003

To: T10 Committee (SCSI)

From: George Penokie (IBM/Tivoli)

Subject: SPC-3; SBC-2; End-to-End Data Protection

1 Overview

Any inconsistencies between this section and the remaining sections in the proposal should be ignored in this section as the remaining sections are what will be placed into the relevant standards. This section is only here as a brief description of the overall proposal and should not be considered normative.

There is an need (real or imagined) for a standardized end-to-end data protection mechanism to be defined. The logical place to such a definition is the SCSI command and architecture standards, as most storage uses SCSI commands to read/write data to and from storage devices. What follows is a proposal that provides a set of SCSI tools that will enable end-to-end data protection. This set of SCSI tools are defined to accomplish this goal:

- a) without interfering with existing proprietary methods;
- b) with a minimum of options; and
- c) by defining minimal changes to CDBs while maintaining backward compatibility.

The set of SCSI tools will consist of the following:

- a) Three level data protection on each data block transferred across the interconnect that consists of;
 - A) A 2-byte CRC that covers the user data of the data block. The CRC is generated at or before the application client and preserved at the logical unit.
 - B) A 4-byte incrementing LBA tag. The incrementing LBA tag is set by the application client during write operation to the value of the least significant 4 bytes of the write command's LBA field on the first data block transferred and incremented by one on each data block transferred until all the blocks for the command have been transferred. The increment LBA tag values for each data block that is read back shall be the same value that was received for that data block.
 - C) A 2-byte application defined tag.
- b) A bit in the non-Read Read CDBs (e.g, VERIFY) to allow a logical unit to return protection information.
 - A) If zero then do not transmit any protection information. The logical unit shall not check the contents of protection information.
 - B) If one then transmit protection information. The logical unit may determine if the data block is valid by checking the contents of protection information. If the logical unit determines there is a an error it shall generate a check condition. A read to a logical unit that has not been formatted to transmit the data protection information may fail with a check condition. In the case where the logical unit has not been formatted and does not check the bit the contents of protection information is not defined by this standard and as a result should cause an error at the application client.
- c) A two bit field in the READ commands (excluding the READ (6) command) that would control the reading and checking of protection information.
 - A) If 00b then do not transmit any protection information. If the logical unit has been formatted with protection information the logical unit may determine if the data block is valid by checking the contents of protection information. If the logical unit determines there is a an error it shall generate a check condition.
 - B) If 01b then transmit protection information. The logical unit may determine if the data block is valid by checking the contents of protection information. If the logical unit determines there is a an error it shall generate a check condition. A read to a logical unit that has not been formatted to transmit the data protection information may fail with a check condition. In the case where the logical unit has not been formatted and does not check the bit the contents of protection information is not defined by this standard and as a result should cause an error at the application client.
 - C) If 10b then transmit protection information. The logical unit shall not check the contents of the DATA BLOCK GUARD field. The logical unit may determine if the data block is valid by checking the contents of protection information except for the DATA BLOCK GUARD field. If the logical unit determines there is a an error it shall generate a check condition. A read to a logical unit that has not

been formatted to transmit the data protection information may fail with a check condition. In the case where the logical unit has not been formatted and does not check the bit the contents of protection information is not defined by this standard and as a result should cause an error at the application client.

- D) If 11b then transmit protection information. The logical unit shall not check the contents of protection information. A read to a logical unit that has not been formatted to transmit the data protection information may fail with a check condition. In the case where the logical unit has not been formatted and does not check the bit the contents of protection information is not defined by this standard and as a result should cause an error at the application client.
- d) A two bit field in Write CDBs to allow protection information to be written with no checks.
 - A) If 00h then preserve the contents of protection information (e.g., write to media, store in non-volatile memory, recalculate on read back). The logical unit shall determine if the data block is valid by checking the contents of protection information. If the logical unit determines there is an error it shall generate a check condition. If the logical unit has not been formatted to accept protection information it shall generate a check condition.
 - B) If 01h then preserve the contents of protection information (e.g., write to media, store in non-volatile memory, recalculate on read back). The logical unit shall not check the contents of protection information. If the logical unit has not been formatted to accept protection information it shall generate a check condition.
 - C) If 10h then the contents of protection information shall not be preserved. The logical unit shall determine if the data block is valid by checking the contents of protection information. If the logical unit determines there is an error it shall generate a check condition. In the case where the logical unit has not been formatted with protection information and does not check the CDB protection field the logical unit's response to the command is not defined by this standard.
- e) A bit in the Format CDB to cause 8 bytes to be added to the block size of the logical unit being formatted.
 - A) If zero then format the medium to the block length defined in the mode parameter block descriptor of the Mode parameter header.
 - B) If one then format the medium to the block length defined in the mode parameter block descriptor of the Mode parameter header plus 8 (e.g., if block length = 512 the formatted block length is 520). The block length shall be a multiple of four. If the block length is not a multiple of four the logical unit shall generate a check condition.
- f) All commands that request block length information (e.g., Read Capacity, Mode Sense) shall return the block size of the data excluding the eight bytes of protection information (e.g., a 520 byte data block on a device formatted with protection information returns 512 in the block length field).
- g) A two bit field in the Standard Inquiry Data to indicate support of protection information.
 - A) If 00b then no protection is supported.
 - B) If 10b then protection is supported but not enabled
 - C) If 11b then protection is supported and enabled.
- h) A bit in a mode page that forces the logical unit to write to media the contents of the data block guard field.
 - A) If zero then the contents of the data block guard field shall be preserved and may be written to media.
 - B) If one then the contents of the data block guard field shall be written to media.

SBC-2 additions

3.1 Definitions

[3.1.1 default protection information: Values placed into protection information fields if an application client does not specify specific protection information values \(see 4.5.2\).](#)

[3.1.2 protection information: Fields appended to each block of data that contain a cyclic redundancy check \(CRC\), a data block application tag, and a data block reference tag.](#)

4.5 Protection information model (new section)

4.5.1 Protection information overview

This data protection model provides for protection of the data while it is being transferred between a sender and a receiver. Protection information is generated at the application layer and may be checked by any object along the I_T_L nexus. Once received, protection information is retained (e.g., write to media, store in non-volatile memory, recalculate on read back) by the device server until overwritten (e.g., power loss, hard reset, logical unit reset, and I_T nexus loss have no effect on the retention of protection information).

For commands that are using protection information, the application client buffer shall consist of data blocks with protection information.

If the logical unit is formatted with protection information and the EMDP_{bit} is set to one then checking of the data block reference tag or the data block guard within the service delivery subsystem may cause false errors because data blocks may be transmitted out of order.

4.5.2 Protection information

See figure 1 for the placement of protection information.

Table 1 — User data and protection information format

Byte\Bit	7	6	5	4	3	2	1	0
0	DATA BLOCK							
n - 1								
n	(MSB)	DATA BLOCK GUARD						
n + 1								(LSB)
n + 2	(MSB)	DATA BLOCK APPLICATION TAG						
n + 3								(LSB)
n + 4	(MSB)	DATA BLOCK REFERENCE TAG						
n + 7								(LSB)

The DATA BLOCK field shall contain user data. The contents of the DATA BLOCK field shall be used to generate and check the CRC contained in the DATA BLOCK GUARD field.

The DATA BLOCK GUARD field contains the CRC (see 4.5.3) of the contents of the DATA BLOCK field.

The DATA BLOCK APPLICATION TAG field is set by the application client. The contents of the data block application tag are not defined by this standard. The DATA BLOCK APPLICATION TAG field may be modified by a device server if the APP_TAG_OWN bit is set to zero (see 4.5.50). The contents of the DATA BLOCK APPLICATION TAG field shall not be used to generate or check the CRC contained in the DATA BLOCK GUARD field.

The DATA BLOCK REFERENCE TAG field is set to the least significant four bytes of the logical block address to which the data block is associated. The DATA BLOCK REFERENCE TAG field is set to the least significant four bytes of the logical block address to which the data block is associated. The first data block in application client data buffer shall contain the least significant four bytes of the logical block address contained in the LOGICAL BLOCK ADDRESS field of the command associated with the data being transferred. Each data block in the application client data buffer contains a DATA BLOCK REFERENCE TAG field with the data block reference tag of the previous data block plus one. The contents of the DATA BLOCK REFERENCE TAG field shall not be used to generate or check the CRC contained in the DATA BLOCK GUARD field.

4.5.3 Data block guard protection

If data protection is enabled, the data block guard shall contain a CRC that is generated from the contents of the DATA BLOCK field.

Table 2 defines the CRC polynomials.

Editor's Note 1: The seed value of the CRC and the inversion of the CRC has not yet been determined. This statement shall be placed into the SBC-2 standard until this issue is resolved.

Table 2 — CRC polynomials

Function	Definition
$F(x)$	A polynomial of degree $k-1$ that is used to represent the k bits of the data block covered by the CRC. For the purposes of the CRC, the coefficient of the highest order term shall be byte zero bit seven of the DATA BLOCK field.
$G(x)$	The generator polynomial: $G(x) = x^{16} + x^{15} + x^{11} + x^9 + x^8 + x^7 + x^5 + x^4 + x^2 + x + 1$ (i.e., $G(x) = 18BB7h$)
$R(x)$	The remainder polynomial, which is of degree less than 16.
$P(x)$	The remainder polynomial on the receive checking side, which is of degree less than 16. $P(x) = 0$ indicates no error was detected.
$Q(x)$	The greatest multiple of $G(x)$ in $(x^{16} \times F(x)) + (x^k \times L(x))$
$Q'(x)$	$x^{16} \times Q(x)$
$M(x)$	The sequence that is transmitted.
$M'(x)$	The sequence that is received.

4.5.4 CRC generation

The equations that are used to generate the CRC from $F(x)$ are as follows. All arithmetic is modulo 2.

CRC value in data block = $R(x)$

The CRC is calculated by the following equation:

$$\frac{(x^{16} \times F(x))}{G(x)} = Q(x) + \frac{R(x)}{G(x)}$$

The following equation specifies that the CRC is appended to the end of $F(x)$:

$$M(x) = x^{16} \times F(x) + \text{CRC}$$

The bit order of $F(x)$ presented to the CRC function is two bytes at a time starting with byte zero bit seven of the DATA BLOCK field until all the contents of the DATA BLOCK field are processed. An example of an even byte transfer is shown in figure 1.




Figure 1 — Even byte CRC generator bit order

4.5.5 CRC checking

The received sequence $M'(x)$ may differ from the transmitted sequence $M(x)$ if there are transmission errors. The process of checking the sequence for validity involves dividing the received sequence by $G(x)$ and testing the remainder. Mathematically, the received checking is shown by the following equation:

$$x^{16} \times \frac{M'(x)}{G(x)} = Q'(x) + \frac{P(x)}{G(x)}$$

In the absence of errors remainder $P(x)$ is zero.

The bit order of $F(x)$ presented to the CRC checking function is the same order as the CRC generation bit order (see figure 1).

4.5.6 Test cases

Using the polynomial described in table 2, the CRC calculated for a 32-byte transfer of all 00h is: 0000h,

Using the polynomial described in table 2, the CRC calculated for a 32-byte transfer of all FFh: A293h.

Using the polynomial described in table 2, the CRC calculated for a 32-byte transfer of an incrementing pattern from 00h to 1Fh is: 0224h.

Using the polynomial described in table 2, the CRC calculated for a 32-byte transfer of FFFFh followed by 30 bytes 00h: 21B8h

Using the polynomial described in table 2, the CRC calculated for a 32-byte transfer of a decrementing pattern from FFh to E0h: A0B7h

4.5.7 Application of protected data

Before an application client transmits or receives protected data it shall:

- 1) Determine if a logical unit supports protected data using the INQUIRY command (see SPC-3);
- 2) If protected data is supported then determine if the logical unit is formatted to accept protected information using the INQUIRY command;
- 3) If the logical unit supports protected information and is not formatted to accept protected information then format the logical unit with protected information usage enabled; and
- 4) If the logical unit supports protected information and is formatted to accept protected information then the read commands that support protected information may be used and write commands that support protected information should be used.

4.5.8 Protected data commands

The enabling of protection information enables fields in some commands that instruct the device server on the handling of protection information. The detailed description of each command's protection information fields are defined in the individual command descriptions.

The commands that are affected when protection information is enabled are:

- a) FORMAT UNIT;
- b) READ (6)/(10)/(12)/(16);
- c) READ LONG;
- d) REASSIGN BLOCKS;
- e) REBUILD (16)/(32);
- f) REGENERATE (16)/(32);
- g) SYNCHRONIZE CACHE (10)/(16);
- h) VERIFY (10)/(12)/(16);
- i) WRITE (6)/(10)/(12)/(16);
- j) WRITE AND VERIFY (10)/(12)/(16);
- k) WRITE LONG;
- l) WRITE SAME (10)/(12);
- m) XDREAD (10)/(32);
- n) XDWRITE (10)/(32);
- o) XDWRITE EXTENDED (16)/(32)/(64);
- p) XDWRITEREAD (10)/(32); and
- q) XPWRITE (10)/(32).

Editor's Note 2: The above list could be moved to the commands table with a new yes/no column indicating which are affected by protection information.

Commands that result in the return of the length in bytes of each logical block (e.g., MODE SENSE, READ CAPACITY) shall return the length of the user data and shall not include the length of the protection information (e.g., if the user data plus the protection information is equal to 520 bytes then 512 is returned).

4.5.9 FORMAT UNIT command

4.5.9.1 FORMAT UNIT command overview

The FORMAT UNIT command (see table 3) formats the medium into application client addressable logical blocks per the application client defined options. In addition, the medium may be certified and control structures may be created for the management of the medium and defects. The degree that the medium is altered by this command is vendor-specific.

Table 3 — FORMAT UNIT command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (04h)							
1	FMTPINFO	Reserved	ONGLIST	FMTDATA	CMPLIST	DEFECT LIST FORMAT		
2	Vendor specific							
3	<div>(MSB)INTERLEAVE(LSB)</div>							
4								
5	CONTROL							

A format protection information (FMTPINFO) bit of specifies that the device server shall format the medium to the block length specified in the mode parameter block descriptor of the Mode parameter header (see x.x.x). A FMTPINFO bit of one specifies that the device server shall format the medium block length specified in the mode parameter block descriptor of the Mode parameter header plus eight (e.g., if the block length equals 512 the formatted block length is 520). A successful format that changes whether protection information (see 4.5.2) is included shall cause the PROTECT field in the standard INQUIRY data (see SPC-3) to be changed resulting in a unit attention condition.

When protection information is written during a FORMAT UNIT command (i.e., FMTPINFO bit is set to one) protection information shall be written to a default value of FFFF FFFF FFFF FFFFh.

4.5.10 READ (6) command

The READ (6) command (see table 29) requests that the device server transfer data to the application client. The most recent data value written, or to be written if cached, in the addressed logical block shall be returned. [If protection information is enabled see table 4 for protection information rules.](#)

Table 4 — Protection information rules

Logical unit formatted with protection information	Transmit	Device server protection information validity checking rules ^c		
		Field	Checked ^d	If check fails ^b
				Additional sense code
Yes	No	DATA BLOCK GUARD	GRD_CHK = 1 ^e	DATA BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{a e}	DATA BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^e	DATA BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
No	No protection information available to check			

^a [The device server checks the data block application tag only if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.](#)

^b [If an error is reported the sense key shall be set to ABORTED COMMAND.](#)

^c [If multiple errors occur, the selection of which error to report is not defined by this standard.](#)

^d [See the Protection Information VPD page \(4.6.2\) for a description of the GRD_CHK, APP_CHK, and REF_CHK bits.](#)

^e [If the application client or device server detects a DATA BLOCK APPLICATION TAG field of FFFFh, the checking of all protection information shall be disabled for the associated data block.](#)

4.5.11 READ (10) command

The READ (10) command (see table 5) requests that the device server transfer data to the application client. The most recent data value written in the addressed logical block shall be returned.

Table 5 — READ (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (28h)							
1	RDPROTECT			DPO	FUA	Reserved		RELADR
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
5	Reserved							
6	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
7	CONTROL							
8								
9								

[The RDPROTECT field is defined in table 6.](#)

Table 6 — RDPROTECT field (part 1 of 2)

Value	Logical unit formatted with protection information	Transmit	Device server protection information validity checking rules ^f		
			Field	Checked ^g	If check fails ^d
					Additional sense code
000b	Yes	No	DATA BLOCK GUARD	GRD_CHK = 1 ^h	DATA BLOCK GUARD CHECK FAILED
				GRD_CHK = 0	No check performed
			DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{c h}	DATA BLOCK APPLICATION TAG CHECK FAILED
				APP_CHK = 0	No check performed
			DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^h	DATA BLOCK REFERENCE TAG CHECK FAILED
				REF_CHK = 0	No check performed
	No	No protection information available to check			
001b ^b	Yes	Yes ^e	DATA BLOCK GUARD	GRD_CHK = 1 ^h	DATA BLOCK GUARD CHECK FAILED
				GRD_CHK = 0	No check performed
			DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{c h}	DATA BLOCK APPLICATION TAG CHECK FAILED
				APP_CHK = 0	No check performed
			DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^h	DATA BLOCK REFERENCE TAG CHECK FAILED
				REF_CHK = 0	No check performed
	No ^a	No protection information available to transmit to the application client or for checking			

^a A read operation to a logical unit that supports protection information (see table 38) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.

^b If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.

^c The device server checks the data block application tag only if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.

^d If an error is reported the sense key shall be set to ABORTED COMMAND.

^e Transmit protection information to the application client.

^f If multiple errors occur, the selection of which error to report is not defined by this standard.

^g See the Protection Information VPD page (4.6.2) for a description of the GRD_CHK, APP_CHK, and REF_CHK bits.

^h If the application client or device server detects a DATA BLOCK APPLICATION TAG field of FFFFh, the checking of all protection information shall be disabled for the associated data block.

Table 6 — RDPROTECT field (part 2 of 2)

Value	Logical unit formatted with protection information	Transmit	Device server protection information validity checking rules ^f		
			Field	Checked ^g	If check fails ^d
					Additional sense code
010b ^b	Yes	Yes ^e	DATA BLOCK GUARD	Shall not	No check performed
			DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{c h}	DATA BLOCK APPLICATION TAG CHECK FAILED
				APP_CHK = 0	No check performed
			DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^h	DATA BLOCK REFERENCE TAG CHECK FAILED
	REF_CHK = 0	No check performed			
	No ^a	No protection information available to transmit to the application client or for checking			
011b ^b	Yes	Yes ^e	DATA BLOCK GUARD	Shall not	No check performed
			DATA BLOCK APPLICATION TAG	Shall not	No check performed
			DATA BLOCK REFERENCE TAG	Shall not	No check performed
	No ^a	No protection information available to transmit to the application client or for checking			
100b - 111b	Reserved				

^a [A read operation to a logical unit that supports protection information \(see table 38\) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.](#)

^b [If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.](#)

^c [The device server checks the data block application tag only if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.](#)

^d [If an error is reported the sense key shall be set to ABORTED COMMAND.](#)

^e [Transmit protection information to the application client.](#)

^f [If multiple errors occur, the selection of which error to report is not defined by this standard.](#)

^g [See the Protection Information VPD page \(4.6.2\) for a description of the GRD_CHK, APP_CHK, and REF_CHK bits.](#)

^h [If the application client or device server detects a DATA BLOCK APPLICATION TAG field of FFFFh, the checking of all protection information shall be disabled for the associated data block.](#)

4.5.12 READ (12) command

The READ (12) command (see table 7) requests that the device server transfer data to the application client from the medium.

Table 7 — READ (12) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (A8h)							
1	RDPROTECT			DPO	FUA	Reserved		RELADR
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
5								
6	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
9								
10	Reserved							
11	CONTROL							

4.5.13 READ (16) command

The READ (16) command (see table 8) requests that the device server transfer data to the application client.

Table 8 — READ (16) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (88h)							
1	RDPROTECT			DPO	FUA	Reserved		RELADR
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
9								
10	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
13								
14	Reserved							
15	CONTROL							

4.5.14 READ LONG command

The READ LONG command (see table 41) requests that the device server transfer data to the application client. The data passed during the READ LONG command is vendor-specific, but shall include the data bytes, [any protection information](#), and the ECC bytes recorded on the medium. The most recent data written, or to be written, in the addressed logical block shall be returned. READ LONG is independent of the Read-Write Error Recovery mode page but does allow retries.

4.5.15 READ CAPACITY (10) command

...

The short read capacity data (see table 9) shall be sent during the data-in buffer transfer of the command. The maximum value that shall be returned in the returned logical block address field is FFFFFFFEh.

Table 9 — Short read capacity data

Byte\Bit	7	6	5	4	3	2	1	0
0	(MSB) _____							
3	RETURNED LOGICAL BLOCK ADDRESS _____ (LSB)							
4	(MSB) _____							
7	BLOCK LENGTH IN BYTES (excluding protection information, if any) _____ (LSB)							

4.5.16 READ CAPACITY (16) command

...

The long read capacity data (see table 10) shall be sent during the data-in buffer transfer of the command. The maximum value that shall be returned in the RETURNED LOGICAL BLOCK ADDRESS field is FFFF FFFF FFFF FFEh.

Table 10 — Long read capacity data

Byte\Bit	7	6	5	4	3	2	1	0
0	(MSB) _____							
7	RETURNED LOGICAL BLOCK ADDRESS _____ (LSB)							
8	(MSB) _____							
11	BLOCK LENGTH IN BYTES (excluding protection information, if any) _____ (LSB)							

4.5.17 REASSIGN BLOCKS command

The REASSIGN BLOCKS command (see table 42) requests the device server to reassign the defective logical blocks [and that logical block's protection information](#) to another area on the medium set aside for this purpose. The device server should also record the location of the defective logical blocks to the grown defect list if such a list is supported. More than one physical or logical block may be relocated by each defect descriptor sent by the application client. This command does not alter the contents of the PLIST (see 4.5.9).

4.5.18 REBUILD (16) Command

The REBUILD (16) command (see table 46) requests that the target write to the medium the XOR data generated from the specified source devices. The target, acting as a temporary initiator, issues READ commands to retrieve the specified data [and protection information, if any](#). READ (10) should be used for accesses to SCSI devices supporting less than 2 Terabytes, and READ (16) should be used for accesses to SCSI devices supporting greater than or equal to 2 Terabytes

4.5.19 REBUILD (32) Command

The REBUILD (32) command (see table 50) requests that the target write to the medium the XOR data generated from the specified source devices. The target, acting as a temporary initiator, issues READ commands to retrieve the specified data [and protection information, if any](#).

4.5.20 REGENERATE (16) command

The REGENERATE (16) command (see table 53) requests that the target write to the buffer the XOR data generated from its own medium and the specified source devices. The target, acting as a temporary initiator, issues READ commands to retrieve the specified data [and protection information, if any](#). The resulting XOR data is retained in the target's buffer until it is retrieved by an XDREAD command with a starting LOGICAL

BLOCK ADDRESS and TRANSFER LENGTH that match, or are a subset of, the LOGICAL BLOCK ADDRESS and REGENERATE LENGTH of this command.

4.5.21 REGENERATE (32) command

The REGENERATE (32) command (see table 54) requests that the target write to the buffer the XOR data generated from its own medium and the specified source devices. The target, acting as a temporary initiator, issues READ commands to retrieve the specified data [and protection information, if any](#).

4.5.22 SYNCHRONIZE CACHE (10) command

The SYNCHRONIZE CACHE (10) command (see table 60) ensures that logical blocks in the cache memory, within the specified range, have their most recent data value [and protection information, if any](#), recorded on the physical medium. If a more recent data value for a logical block within the specified range exists in the cache memory than on the physical medium, then the logical block from the cache memory shall be written to the physical medium. Logical blocks may not be removed from the cache memory as a result of the synchronize cache operation. The synchronize cache function is also required implicitly by other SCSI functions as defined in other clauses of this standard.

4.5.23 SYNCHRONIZE CACHE (16) command

The SYNCHRONIZE CACHE (16) command (see table 61) ensures that logical blocks in the cache memory, within the specified range, have their most recent data value [and protection information, if any](#), recorded on the physical medium. If a more recent data value for a logical block within the specified range exists in the cache memory than on the physical medium, then the logical block from the cache memory shall be written to the physical medium. Logical blocks may not be removed from the cache memory as a result of the synchronize cache operation. The synchronize cache function is also required implicitly by other SCSI functions as defined in other clauses of this standard.

4.5.24 VERIFY (10) command

The VERIFY (10) command (see table 11) requests that the device server verify the data written on the medium.

Table 11 — VERIFY (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (2Fh)							
1	VRPROTECT			DPO	Reserved	BLKVFY	BYCHK	RELADR
2	(MSB)							
5	LOGICAL BLOCK ADDRESS (LSB)							
6	Restricted for MMC-4	Reserved						
7	(MSB)							
8	VERIFICATION LENGTH (LSB)							
9	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See 4.5.11 for a description of the cache control bit (DPO). See the LOCK UNLOCK CACHE (10) command (see 5.2.3) for a definition of the RELADR bit and the LOGICAL BLOCK ADDRESS field.

If the MODE SELECT command is implemented, and the Verify Error Recovery mode page is also implemented, then the current settings in that page specifies the verification criteria. If the Verify Error Recovery mode page is not implemented, then the verification criteria is vendor-specific.

If the byte check (BYTCHK) bit is zero, a medium verification shall be performed with no data comparison. [For protection information comparison requirements when BYTCHK is set to zero see table 12.](#) If the BYTCHK bit is one, a byte-by-byte comparison of data written on the medium and the data transferred from the application client shall be performed.

[For protection information comparison requirements when BYTCHK is set to one:](#)

- a) [see table 13 for the protection information byte-by-byte comparison requirements;](#)
- b) [see table 14 for the protection information checking requirements on data transferred from the application client; and](#)
- c) [see table 15 for the protection information checking requirements on data written on the medium.](#)

If the comparison is unsuccessful for any reason, the device server shall return CHECK CONDITION status and the sense key shall be set to MISCOMPARE with the appropriate additional sense code for the condition.

For direct access block devices, the blank verify (BLKVfy) bit shall be considered reserved. For optical and write-once block devices, the BLKVfy BIT is defined as follows. If the BLKVfy bit is zero, the device server shall not verify that the blocks are blank. If the BLKVfy bit is one, the device server shall verify that the blocks are blank. If the BYTCHK is one and the BLKVfy bit is one the device server shall return CHECK CONDITION status and the sense key shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.

[The VRPROTECT field with BYTCHK set to zero is defined in table 12.](#)

Table 12 — VRPROTECT field with BYTCHK = 0 (part 1 of 2)

Value	Logical unit formatted with protection information	Device server protection information validity checking rules ^e		
		Field	Checked ^f	If check fails ^d
				Additional sense code
000b	Yes	DATA BLOCK GUARD	GRD_CHK = 1 ^g	DATA BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{c g}	DATA BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^g	DATA BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
	No	No protection information available to check		
001b ^b	Yes	DATA BLOCK GUARD	GRD_CHK = 1 ^g	DATA BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{c g}	DATA BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^g	DATA BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
	No ^a	No protection information available to check		
<div><div><div><div><div><div>^a</div><div>A verify operation to a logical unit that supports protection information (see table 38) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.</div></div></div><div><div><div>^b</div><div>If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.</div></div></div><div><div><div>^c</div><div>The device server checks the data block application tag only if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.</div></div></div><div><div><div>^d</div><div>If an error is reported the sense key shall be set to ABORTED COMMAND.</div></div></div><div><div><div>^e</div><div>If multiple errors occur, the selection of which error to report is not defined by this standard.</div></div></div><div><div><div>^f</div><div>See the Protection Information VPD page (4.6.2) for a description of the GRD_CHK, APP_CHK, and REF_CHK bits.</div></div></div><div><div><div>^g</div><div>If the application client or device server detects a DATA BLOCK APPLICATION TAG field of FFFFh, the checking of all protection information shall be disabled for the associated data block.</div></div></div></div></div></div>				

Table 12 — VRPROTECT field with BYTCHK = 0 (part 2 of 2)

Value	Logical unit formatted with protection information	Device server protection information validity checking rules ^e		
		Field	Checked ^f	If check fails ^d
				Additional sense code
010b ^b	Yes	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{c g}	DATA BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^g	DATA BLOCK REFERENCE TAG CHECK FAILED
	REF_CHK = 0		No check performed	
	No ^a	No protection information available to check		
011b ^b	Yes	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall not	No check performed
	No ^a	No protection information available to check		
100b - 111b	Reserved			
^a A verify operation to a logical unit that supports protection information (see table 38) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.				
^b If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.				
^c The device server checks the data block application tag only if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.				
^d If an error is reported the sense key shall be set to ABORTED COMMAND.				
^e If multiple errors occur, the selection of which error to report is not defined by this standard.				
^f See the Protection Information VPD page (4.6.2) for a description of the GRD_CHK, APP_CHK, and REF_CHK bits.				
^g If the application client or device server detects a DATA BLOCK APPLICATION TAG field of FFFFh, the checking of all protection information shall be disabled for the associated data block.				

[The protection information byte-by-byte comparison requirements for protection information transferred from the application and protection information read from the medium with BYTCHK set to one is defined in table 13.](#)

Table 13 — VRPROTECT field with BYTCHK = 1 (byte-by-byte comparison) (part 1 of 2)

Value	Logical unit formatted with protection information	Device server protection information byte-by-byte comparison requirements ^d		
		Field	Byte-by-byte Comparison	If check fails ^c
				Additional sense code
000b	Yes	No protection information received from application client to compare		
	No	No protection information received from application client to compare		
001b ^b	Yes	DATA BLOCK GUARD	Shall	DATA BLOCK GUARD CHECK FAILED
		DATA BLOCK APPLICATION TAG (APP_TAG_OWN = 1) ^e	Shall	DATA BLOCK APPLICATION TAG CHECK FAILED
		DATA BLOCK APPLICATION TAG (APP_TAG_OWN = 0) ^f	Shall not	No compare performed
		DATA BLOCK REFERENCE TAG	Shall	DATA BLOCK REFERENCE TAG CHECK FAILED
	No ^a	No protection information available to compare		

^a [A verify operation to a logical unit that supports protection information \(see table 38\) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.](#)

^b [If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.](#)

^c [If an error is reported the sense key shall be set to MISSCOMPARE.](#)

^d [If multiple errors occur, the selection of which error to report is not defined by this standard.](#)

^e [The data block application tag shall not be modified by a device server.](#)

^f [The data block application tag may be modified by a device server.](#)

Table 13 — VRPROTECT field with BYTCHK = 1 (byte-by-byte comparison) (part 2 of 2)

Value	Logical unit formatted with protection information	Device server protection information byte-by-byte comparison requirements ^d		
		Field	Byte-by-byte Comparison	If check fails ^c
				Additional sense code
010b ^b	Yes	DATA BLOCK GUARD	Shall not	No compare performed
		DATA BLOCK APPLICATION TAG (APP_TAG_OWN = 1) ^e	Shall	DATA BLOCK APPLICATION TAG CHECK FAILED
		DATA BLOCK APPLICATION TAG (APP_TAG_OWN = 0) ^f	Shall not	No compare performed
		DATA BLOCK REFERENCE TAG	Shall	DATA BLOCK REFERENCE TAG CHECK FAILED
	No ^a	No protection information available to compare		
011b ^b	Yes	DATA BLOCK GUARD	Shall	DATA BLOCK GUARD CHECK FAILED
		DATA BLOCK APPLICATION TAG (APP_TAG_OWN = 1) ^e	Shall	DATA BLOCK APPLICATION TAG CHECK FAILED
		DATA BLOCK APPLICATION TAG (APP_TAG_OWN = 0) ^f	Shall not	No compare performed
		DATA BLOCK REFERENCE TAG	Shall	DATA BLOCK REFERENCE TAG CHECK FAILED
	No ^a	No protection information available to compare		
100b - 111b	Reserved			

^a [A verify operation to a logical unit that supports protection information \(see table 38\) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.](#)
^b [If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.](#)
^c [If an error is reported the sense key shall be set to MISSCOMPARE.](#)
^d [If multiple errors occur, the selection of which error to report is not defined by this standard.](#)
^e [The data block application tag shall not be modified by a device server.](#)
^f [The data block application tag may be modified by a device server.](#)

[The application client protection information validity checking requirements with BYTCHK set to one is defined in table 14.](#)

Table 14 — VRPROTECT field with BYTCHK = 1 (application client transferred checking)

Value	Logical unit formatted with protection information	Device server protection information validity checking requirements on protection information transferred from application client ^e		
		Field	Checked	If check fails ^d
				Additional sense code
000b	Yes	No protection information received from application client to check		
	No	No protection information received from application client to check		
001b ^b	Yes	DATA BLOCK GUARD	Shall	DATA BLOCK GUARD CHECK FAILED
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall	DATA BLOCK REFERENCE TAG CHECK FAILED
	No ^a	No protection information available to check		
010b ^b	Yes	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	May ^c	DATA BLOCK APPLICATION TAG CHECK FAILED
		DATA BLOCK REFERENCE TAG	May	DATA BLOCK REFERENCE TAG CHECK FAILED
	No ^a	No protection information available to check		
011b ^b	Yes	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall not	No check performed
	No ^a	No protection information available to check		
100b - 111b	Reserved			

^a [A verify operation to a logical unit that supports protection information \(see table 38\) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.](#)

^b [If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.](#)

^c [The device server may check the data block application tag if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.](#)

^d [If an error is reported the sense key shall be set to ABORTED COMMAND.](#)

^e [If multiple errors occur, the selection of which error to report is not defined by this standard.](#)

The protection information validity checking requirements for protection information read from the medium with BYTCHK set to one is defined in table 15.

Table 15 — VRPROTECT field with BYTCHK = 1 (medium data block checking)

Value	Logical unit formatted with protection information	Device server protection information validity checking requirements on protection information read from the medium ^e		
		Field	Checked ^f	If check fails ^d
				Additional sense code
000b	Yes	DATA BLOCK GUARD	GRD_CHK = 1 ^g	DATA BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		DATA BLOCK APPLICATION TAG	APP_CHK = 1 ^{c g}	DATA BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		DATA BLOCK REFERENCE TAG	REF_CHK = 1 ^g	DATA BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
	No	No protection information available to check		
001b ^b	Yes	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall not	No check performed
	No ^a	No protection information available to transmit to the application client or for checking		
010b ^b	Yes	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall not	No check performed
	No ^a	No protection information available to transmit to the application client or for checking		
011b ^b	Yes	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall not	No check performed
	No ^a	No protection information available to transmit to the application client or for checking		
100b - 111b	Reserved			

^a [A verify operation to a logical unit that supports protection information \(see table 38\) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.](#)

^b [If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.](#)

^c [The device server checks the data block application tag only if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.](#)

^d [If an error is reported the sense key shall be set to ABORTED COMMAND.](#)

^e [If multiple errors occur, the selection of which error to report is not defined by this standard.](#)

^f [See the Protection Information VPD page \(4.6.2\) for a description of the GRD_CHK, APP_CHK, and REF_CHK bits.](#)

^g [If the application client or device server detects a DATA BLOCK APPLICATION TAG field of FFFFh, the checking of all protection information shall be disabled for the associated data block.](#)

4.5.25 VERIFY (12) command

The VERIFY (12) command (see table 16) requests that the device server verify the data on the medium.

Table 16 — VERIFY (12) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (AFh)							
1	VRPROTECT			DPO	Reserved	BLKVFY	BYCHK	RELADR
2	(MSB) _____							
5	LOGICAL BLOCK ADDRESS _____ (LSB)							
6	(MSB) _____							
9	VERIFICATION LENGTH _____ (LSB)							
10	Reserved							
11	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the VERIFY (10) command (see 4.5.24) for a description of the fields in this command.

4.5.26 VERIFY (16) command

The VERIFY (16) command (see table 17) requests that the device server verify the data written on the medium.

Table 17 — VERIFY (16) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (8Fh)							
1	VRPROTECT			DPO	Reserved	BLKVFY	BYCHK	RELADR
2	(MSB) LOGICAL BLOCK ADDRESS (LSB)							
9								
10	(MSB) VERIFICATION LENGTH (LSB)							
13								
14	Reserved							
15	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the VERIFY (10) command (see 4.5.24) for a description of the fields in this command.

4.5.27 WRITE (6) command

The WRITE (6) command (see table 65) requests that the device server write the data transferred by the application client to the medium.

If a WRITE (6) command is received after protection information is enabled the device server shall insert default protection information (see 3.1.1) after each data block before writing the data block to the medium. If the device server has been formatted with protection information and is not capable of inserting default protection information it shall terminate the command with a CHECK CONDITION status and the sense data shall be set to ILLEGAL REQUEST with the additional sense code set to CANNOT WRITE MEDIUM - UNKNOWN FORMAT.

4.5.28 WRITE (10) command

The WRITE (10) command (see table 18) requests that the device server write the data transferred by the application client to the medium.

Table 18 — WRITE (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (2Ah)							
1	WRPROTECT			DPO	FUA	EBP	Reserved	RELADR
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
5	Reserved							
6	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
8	CONTROL							
9								

[The WRPROTECT field is defined in table 19.](#)

Table 19 — WRPROTECT field

Value	Logical unit formatted with protection information	Device server protection information validity checking rules ^g		
		Field	Checked	If check fails ^d
				Additional sense code
000b	Yes ^f	No protection information received from application client to check		
	No	No protection information received from application client to check		
001b ^b	Yes ^e	DATA BLOCK GUARD	Shall	DATA BLOCK GUARD CHECK FAILED
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall	DATA BLOCK REFERENCE TAG CHECK FAILED
	No ^a	No protection information available to check		
010b ^b	Yes ^e	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	May ^c	DATA BLOCK APPLICATION TAG CHECK FAILED
		DATA BLOCK REFERENCE TAG	May	DATA BLOCK REFERENCE TAG CHECK FAILED
	No ^a	No protection information available to check		
011b ^b	Yes ^e	DATA BLOCK GUARD	Shall not	No check performed
		DATA BLOCK APPLICATION TAG	Shall not	No check performed
		DATA BLOCK REFERENCE TAG	Shall not	No check performed
	No ^a	No protection information available to check		
100b - 111b	Reserved			

^a [A write operation to a logical unit that supports protection information \(see table 38\) and has not been formatted with protection information shall fail with a CHECK CONDITION status. The sense data shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB.](#)

^b [If the logical unit does not support protection information the requested command should fail, however, the specific error failure is not defined by this standard.](#)

^c [The device server may check the data block application tag if it has knowledge of the contents of the DATA BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this standard.](#)

^d [If an error is reported the sense key shall be set to ABORTED COMMAND.](#)

^e [Device server shall preserve the contents of protection information \(e.g., write to media, store in non-volatile memory\).](#)

^f [The device server shall, after each data block before writing the data block to the medium, write a properly generated CRC \(see 4.5.4\) into the DATA BLOCK field, a properly calculated data block reference tag into the DATA BLOCK REFERENCE TAG field \(see 4.5.2\), and if the APP_TAG_OWN bit is set to one, a DATA BLOCK APPLICATION TAG field set to FFFFh. If APP_TAG_OWN bit is set to zero the device server may set the data block application tag to any value.](#)

^g [If multiple errors occur, the selection of which error to report is not defined by this standard.](#)

4.5.29 WRITE (12) command

The WRITE (12) command (see table 20) requests that the device server write the data transferred from the application client to the medium.

Table 20 — WRITE (12) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (AAh)							
1	WRPROTECT			DPO	FUA	Reserved		RELADR
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
5								
6	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
9								
10	Restricted for MMC-4	Reserved						
11	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the WRITE (10) command (see 4.5.28) for a description of the fields in this command.

4.5.30 WRITE (16) command

The WRITE (16) command (see table 21) requests that the device server write the data transferred by the application client to the medium.

Table 21 — WRITE (16) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (8Ah)							
1	WRPROTECT			DPO	FUA	Reserved		RELADR
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
9								
10	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
13								
14	Reserved							
15	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the WRITE (10) command (see 4.5.28) for a description of the fields in this command.

4.5.31 WRITE AND VERIFY (10) command

The WRITE AND VERIFY (10) command (see table 22) requests that the device server write the data transferred from the application client to the medium and then verify that the data [and protection information, if any](#), is correctly written. The data is only transferred once from the application client to the device server.

Table 22 — WRITE AND VERIFY (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (2Eh)							
1	WRPROTECT			DPO	Reserved	EBP	BYTCHK	RELADR
2	(MSB) LOGICAL BLOCK ADDRESS (LSB)							
5								
6	Reserved							
7	(MSB) TRANSFER LENGTH (LSB)							
8								
9	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the LOCK UNLOCK CACHE (10) command (see 5.2.3) for a definition of the RELADR bit and the LOGICAL BLOCK ADDRESS field. See the WRITE (10) command (4.5.28) for a definition of the TRANSFER LENGTH field [and the WRPROTECT field](#). See 4.5.11 for a description of the cache control bit (DPO). See the WRITE (10) command (see 4.5.28) for a description of the EBP bit.

If the MODE SELECT command is implemented, and the Verify Error Recovery mode page is also implemented, then the current settings in that mode page (along with the AWRE bit from the Read-Write Error Recovery mode page) specify the verification error criteria. If these mode pages are not implemented, then the verification criteria is vendor-specific.

A byte check (BYTCHK) bit of zero requests a medium verification to be performed with no data comparison. A BYTCHK bit of one requests a byte-by-byte comparison of data written on the medium and the data transferred from the application client. If the comparison is unsuccessful for any reason, the device server shall return CHECK CONDITION status with the sense key set to MISCOMPARE with the appropriate additional sense code for the condition.

The WRITE AND VERIFY command specifically states that the data are not to be transferred twice (i.e., once for the write pass, and once for the verify pass) when performing a byte compare. If there is a need for two transfers to occur (e.g., to ensure the integrity of the path to the media), then the application client should issue a WRITE command with a LINK bit of one followed by a VERIFY command with a BYTCHK bit of one, transferring the same data on each command.

4.5.32 WRITE AND VERIFY (12) command

The WRITE AND VERIFY (12) command (see table 23) requests that the device server write the data transferred from the application client to the medium and then verify that the data [and protection information, if any](#), is correctly written.

Table 23 — WRITE AND VERIFY(12) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (AEh)							
1	WRPROTECT			DPO	Reserved	EBP	BYTCHK	RELADR
2	(MSB) LOGICAL BLOCK ADDRESS (LSB)							
5								
6	(MSB) TRANSFER LENGTH (LSB)							
9								
10	Reserved							
11	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the WRITE AND VERIFY (10) command (see 4.5.31) for a description of the bits in this command.

4.5.33 WRITE AND VERIFY (16) command

The WRITE AND VERIFY (16) command (see table 24) requests that the device server write the data transferred from the application client to the medium and then verify that the data [and protection information, if any](#), is correctly written. The data is only transferred once from the application client to the device server.

Table 24 — WRITE AND VERIFY (16) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (8Eh)							
1	WRPROTECT			DPO	Reserved	EBP	BYTCHK	RELADR
2	(MSB) LOGICAL BLOCK ADDRESS (LSB)							
9								
10	(MSB) TRANSFER LENGTH (LSB)							
13								
14	Reserved							
15	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the WRITE AND VERIFY (10) command (see 4.5.31) for a description of the fields in this command.

4.5.34 WRITE LONG command

The WRITE LONG command (see table 72) requests that the device server write the data transferred by the application client to the medium. The data passed during the WRITE LONG command is implementation specific, but shall include the data bytes, [any protection information](#), and the ECC bytes.

4.5.35 WRITE SAME (10) command

The WRITE SAME (10) command (see table 25) requests that the device server write the single block of data transferred by the application client to the medium multiple times to consecutive multiple logical blocks.

If the medium is formatted with protection information the value in the DATA BLOCK REFERENCE TAG field shall be placed into the DATA BLOCK REFERENCE TAG field (see 4.5.2) of the first logical block written to the medium. Into each of the following logical blocks the data block reference tag received in the data transferred by the application client, incremented by one, shall be placed into the data block reference tag of that data block (i.e., each data block written to the medium has a data block reference tag value of one greater than the previous data block). If the APP_TAG_OWN bit (see SPC-3) is set to one the data block application tag received in the single block of data shall be placed in the DATA BLOCK APPLICATION TAG field each logical block. If the APP_TAG_OWN bit is set to zero the data block application tag received in the single block of data may be placed in the DATA BLOCK APPLICATION TAG field each logical block.

Table 25 — WRITE SAME (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (41h)							
1	WRPROTECT			Reserved		PBDATA	LBDATA	RELADR
2	(MSB) _____							
5	LOGICAL BLOCK ADDRESS _____ (LSB)							
6	Reserved							
7	(MSB) _____							
8	NUMBER OF BLOCKS _____ (LSB)							
9	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the LOCK UNLOCK CACHE (10) command (see 5.2.3) for a definition of the RELADR bit and the LOGICAL BLOCK ADDRESS field. [See the WRITE \(10\) command \(4.5.28\) for a definition of the WRPROTECT field.](#)

4.5.36 WRITE SAME (16) command

The WRITE SAME (16) command (see table 26) requests that the device server write the single block of data transferred by the application client to the medium multiple times to consecutive multiple logical blocks.

If the medium is formatted with protection information the value in the DATA BLOCK REFERENCE TAG field shall be placed into the DATA BLOCK REFERENCE TAG field (see 4.5.2) of the first logical block written to the medium. Into each of the following logical blocks the data block reference tag received in the data transferred by the application client, incremented by one, shall be placed into the data block reference tag of that data block (i.e., each data block written to the medium has a data block reference tag value of one greater than the previous data block). If the APP_TAG_OWN bit (see SPC-3) is set to one the data block application tag received in the single block of data shall be placed in the DATA BLOCK APPLICATION TAG field each logical block. If the APP_TAG_OWN bit is set to zero the data block application tag received in the single block of data may be placed in the DATA BLOCK APPLICATION TAG field each logical block.

Table 26 — WRITE SAME (16) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (93h)							
1	WRPROTECT			Reserved		PBDATA	LBDATA	RELADR
2	(MSB) _____							
9	LOGICAL BLOCK ADDRESS _____ (LSB)							
10	(MSB) _____							
13	NUMBER OF BLOCKS _____ (LSB)							
14	Reserved							
15	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the WRITE SAME (10) command (see 4.5.35) for a description of the fields in this command.

4.5.37 XDREAD (10) command

The XDREAD (10) command (see table 27) requests that the target transfer to the initiator the XOR data generated by an XDWRITE or REGENERATE command.

Table 27 — XDREAD (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (52h)							
1	Reserved							XORPINFO
2	(MSB)	LOGICAL BLOCK ADDRESS						
5								(LSB)
6	Reserved							
7	(MSB)	TRANSFER LENGTH						
8								(LSB)
9	CONTROL							

See 4.2.1.8 for reservation requirements for this command.

If the XOR protection information (XORPINFO) is set to zero protection information, if any, shall not be verified or transmitted. If the XORPINFO is set to one protection information shall be transmitted but shall not be verified.

The XOR data transferred is identified by the LOGICAL BLOCK ADDRESS and TRANSFER LENGTH. The LOGICAL BLOCK ADDRESS and TRANSFER LENGTH shall be the same as, or a subset of, those specified in a prior XDWRITE or REGENERATE command. If a match is not found the command is terminated with a CHECK CONDITION status and the sense key shall be set to ILLEGAL REQUEST with the additional sense code set to INVALID FIELD IN CDB. The TRANSFER LENGTH field is constrained by the MAXIMUM TRANSFER LENGTH field in the Block Limits VPD page (see 6.1.4.2).

4.5.38 XDREAD (32) command

The XDREAD (32) command (see table 28) requests that the target transfer to the initiator the XOR data generated by an XDWRITE or REGENERATE command.

Table 28 — XDREAD (32) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
6								
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (0003h)						(LSB)
9								
10	Reserved							XORPINFO
11	Reserved							
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
19								
20	Reserved							
27								
28	(MSB)	TRANSFER LENGTH						(LSB)
31								

See 4.2.1.8 for reservation requirements for this command. See the XDREAD (10) command (see 4.5.37) and SPC-3 for a description of the fields in this command.

4.5.39 XDWRITE (10) command

The XDWRITE (10) command (see table 29) requests that the target XOR the data transferred [including protection information, if any](#), with the data on the medium. The resulting XOR data is stored by the target until it is retrieved by an XDREAD (10) command.

Table 29 — XDWRITE (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (50h)							
1	WRPROTECT			DPO	FUA	DISABLE WRITE	Reserved	
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
5								
6	Reserved							
7	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
8								
9	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the READ (10) command (see 4.5.11) for a definition of the cache control bits (DPO and FUA). [See the WRITE \(10\) command \(4.5.28\) for a definition of the WRPROTECT field.](#)

4.5.40 XDWRITE (32) command

The XDWRITE (32) command (see table 30) requests that the target XOR the data transferred [including protection information, if any](#), with the data on the medium. The resulting XOR data is stored by the target until it is retrieved by an XDREAD (32) command. [The data transferred including protection information, if any, shall be written to the medium.](#)

Table 30 — XDWRITE (32) command

Byte\Bit	7	6	5	4	3	2	1	0	
0	OPERATION CODE (7Fh)								
1	CONTROL								
2	Reserved								
6									
7	ADDITIONAL CDB LENGTH (18h)								
8	(MSB)	SERVICE ACTION (0004h)						(LSB)	
9									
10	WRPROTECT			DPO	FUA	DISABLE WRITE	Reserved		
11	Reserved								
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)	
19									
20	Reserved								
27									
28	(MSB)	TRANSFER LENGTH						(LSB)	
31									

See 4.2.1.8 for reservation requirements for this command. See the XDWRITE (10) command (see 4.5.39) and SPC-3 for a description of the fields in this command.

4.5.41 XDWRITEREAD (10) command

The XDWRITEREAD (10) command (see table 31) requests that the target XOR the data transferred (data-out) [including protection information, if any](#), with the data on the medium and return the resulting XOR data (data-in). This is the equivalent to an XDWRITE (10) followed by an XDREAD (10) with the same logical

block address and transfer length. This command is only available on transport protocols supporting bidirectional commands.

Table 31 — XDWRITEREAD (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (53h)							
1	WRPROTECT			DPO	FUA	DISABLE WRITE	Reserved	XORPINFO
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
5								
6	Reserved							
7	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
8								
9	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See the XWRITE (10) command (see 4.5.39) and XDREAD (10) command (see 4.5.37) for a description of the fields in this command.

4.5.42 XDWRITEREAD (32) command

The XDWRITEREAD (32) command (see table 32) requests that the target XOR the data transferred (data-out) [including protection information, if any](#), with the data on the medium and return the resulting XOR data (data-in). This is the equivalent to an XDWRITE (32) followed by an XDREAD (32) with the same logical

block address and transfer length. This command is only available on transport protocols supporting bidirectional commands.

Table 32 — XDWRITEREAD (32) command

Byte\Bit	7	6	5	4	3	2	1	0							
0	OPERATION CODE (7Fh)														
1	CONTROL														
2	Reserved														
6															
7	ADDITIONAL CDB LENGTH (18h)														
8	(MSB)	SERVICE ACTION (0007h)						(LSB)							
9															
10	WRPROTECT			DPO	FUA	DISABLE WRITE	Reserved	XORPINFO							
11	Reserved														
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)							
19															
20	Reserved														
27															
28	(MSB)	TRANSFER LENGTH						(LSB)							
31															

See 4.2.1.8 for reservation requirements for this command. See the XDWRITEREAD (10) command (see 4.5.41) and SPC-3 for a description of the fields in this command.

4.5.43 XDWRITE EXTENDED (16) command

The XDWRITE EXTENDED (16) command (see table 33) requests that the target XOR the data transferred including protection information, if any, with the data on the medium. The resulting XOR data including protection information, if any, may subsequently be sent to a secondary device using an XPWRITE (10) or XPWRITE (32) command. The target, acting as a temporary initiator, issues XPWRITE commands to retrieve the specified data. XPWRITE (16) should be used for access to SCSI devices supporting less than 2

Terabytes, and XPWRITE (32) should be used for accesses to SCSI devices supporting greater than or equal to 2 Terabytes.

Table 33 — XDWRITE EXTENDED (16) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (80h)							
1	WRPROTECT			DPO	FUA	DISABLE WRITE	PORT CONTROL	
2	(MSB)	LOGICAL BLOCK ADDRESS						
5								(LSB)
6	(MSB)	SECONDARY LOGICAL BLOCK ADDRESS						
9								(LSB)
10	(MSB)	TRANSFER LENGTH						
13								(LSB)
14	SECONDARY ADDRESS							
15	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See 4.5.11 for a definition of the DPO and FUA bits. [See the WRITE \(10\) command \(4.5.28\) for a definition of the WRPROTECT field.](#)

4.5.44 XDWRITE EXTENDED (32) command

The XDWRITE EXTENDED (32) command (see table 34) requests that the target XOR the data transferred including protection information, if any, with the data on the medium. The resulting XOR data may subsequently be sent to a secondary device using an XPWRITE (32) command.

Table 34 — XDWRITE EXTENDED (32) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
6								
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (0005h)						(LSB)
9								
10	WRPROTECT			DPO	FUA	DISABLE WRITE	PORT CONTROL	
11	SECONDARY ADDRESS							
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
19								
20	(MSB)	SECONDARY LOGICAL BLOCK ADDRESS						(LSB)
27								
28	(MSB)	TRANSFER LENGTH						(LSB)
31								

See 4.2.1.8 for reservation requirements for this command. See the XWRITE EXTENDED (16) command (see 4.5.43) and SPC-3 for a description of the fields in this command.

4.5.45 XDWRITE EXTENDED (64) command

The XDWRITE EXTENDED (64) command (see table 35) requests that the target XOR the data transferred [including protection information, if any](#), with the data on the medium. The resulting XOR data may subsequently be sent to a secondary device using an XPWRITE (32) command.

Table 35 — XDWRITE EXTENDED (64) command

Byte\Bit	7	6	5	4	3	2	1	0	
0	OPERATION CODE (7Fh)								
1	CONTROL								
2	Reserved								
6									
7	ADDITIONAL CDB LENGTH (18h)								
8	(MSB)	SERVICE ACTION (0005h)						(LSB)	
9									
10	WRPROTECT			DPO	FUA	DISABLE WRITE	PORT CONTROL		
12	SECONDARY ADDRESS DESCRIPTOR								
43									
44	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)	
51									
52	(MSB)	SECONDARY LOGICAL BLOCK ADDRESS						(LSB)	
59									
60	(MSB)	TRANSFER LENGTH						(LSB)	
63									

See 4.2.1.8 for reservation requirements for this command.

The SECONDARY ADDRESS DESCRIPTOR field contains the logical unit identifier of the logical unit that will receive the XOR data transfer. The format of this field conforms to one of the target descriptor formats of the EXTENDED COPY command as specified in SPC-3.

See the XWRITE EXTENDED (16) command (see 4.5.43) and SPC-3 for a description of the other fields in this command.

4.5.46 XPWRITE (10) command

The XPWRITE (10) command (see table 36) requests that the target XOR the data transferred [including protection information, if any](#), with the data on the medium and then write the XOR data to the medium.

Table 36 — XPWRITE (10) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (51h)							
1	Reserved			DPO	FUA	Reserved		XORPINFO
2	(MSB) _____ LOGICAL BLOCK ADDRESS _____ (LSB)							
5								
6	Reserved							
7	(MSB) _____ TRANSFER LENGTH _____ (LSB)							
8								
9	CONTROL							

See 4.2.1.8 for reservation requirements for this command. See 4.5.11 for a definition of the DPO and FUA bits. [See the XDREAD \(10\) command \(4.5.37\) for a definition of the XORPINFO field.](#)

The LOGICAL BLOCK ADDRESS field specifies the starting logical block address where the target shall read data from its medium. It also specifies the starting logical block address where the XOR result data shall be written to the medium.

The TRANSFER LENGTH field specifies the number of blocks that shall be read from the medium. It also specifies the number of blocks that shall be written to the medium. The TRANSFER LENGTH field is constrained by the MAXIMUM TRANSFER LENGTH field in the Block Limits VPD page (see 6.1.4.2).

4.5.47 XPWRITE (32) command

The XPWRITE (32) command (see table 37) requests that the target XOR the data transferred [including protection information, if any](#), with the data on the medium and then write the XOR data to the medium.

Table 37 — XPWRITE (32) command

Byte\Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
6								
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (0006h)						(LSB)
9								
10	Reserved			DPO	FUA	Reserved		XORPINFO
44	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
51								
52	Reserved							
59								
60	(MSB)	TRANSFER LENGTH						(LSB)
63								

See 4.2.1.8 for reservation requirements for this command. See the XPWRITE (10) command (see 4.5.46) and SPC-3 for a description of the fields in this command.

SPC-3 additions

4.5.48 Standard INQUIRY data

The standard INQUIRY data (see table 38) shall contain at least 36 bytes.

Table 38 — Standard INQUIRY data format

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	RMB	Reserved						
2	VERSION							
3	Obsolete	Obsolete	NORMACA	HiSUP	RESPONSE DATA FORMAT			
4	ADDITIONAL LENGTH (n-4)							
5	SCCS	ACC	ALUA		3PC	Reserved		PROTECT
6	BQUE	ENC SERV	VS	MULTIP	MCHNGR	Obsolete	Obsolete	ADDR16 ^a
7	RELADR	Obsolete	WBUS16 ^a	SYNC ^a	LINKED	Obsolete	CMDQUE	VS
8	(MSB) _____							
15	VENDOR IDENTIFICATION _____ (LSB)							
16	(MSB) _____							
31	PRODUCT IDENTIFICATION _____ (LSB)							
32	(MSB) _____							
35	PRODUCT REVISION LEVEL _____ (LSB)							
36	_____							
55	Vendor specific _____							
56	Reserved				CLOCKING ^a		QAS ^a	IUS ^a
57	Reserved							
58	(MSB) _____							
59	VERSION DESCRIPTOR 1 _____ (LSB)							
	⋮							
72	(MSB) _____							
73	VERSION DESCRIPTOR 8 _____ (LSB)							
74	_____							
95	Reserved _____							
	Vendor specific parameters							
96	_____							
n	Vendor specific _____							
^a The meanings of these fields are specific to SPI-5 (see 6.4.3). For SCSI protocols other than the SCSI Parallel Interface, these fields are reserved.								

[A PROTECT bit set to zero indicates that the logical unit does not support protection information \(see SBC-2\). A protect bit set to one indicates that the logical unit supports protection information.](#)

4.5.48.1 Device type specific target descriptor parameters for block device types

The format for the device type specific target descriptor parameters for block device types (device type code values 00h, 04h, 05h, 07h, and 0Eh) is shown in table 39.

Table 39 — Device type specific target descriptor parameters for block device types

Bit Byte	7	6	5	4	3	2	1	0
28	Reserved					PAD	Reserved	
29	(MSB)							
30	DISK BLOCK LENGTH							
31	(LSB)							

The PAD bit is used in conjunction with the CAT bit (see 6.3.7.1) in the segment descriptor to determine what action should be taken when a segment of the copy does not fit exactly into an integer number of destination blocks.

The DISK BLOCK LENGTH field contains the number of bytes [excluding protection information, if any. \(see SBC-2\)](#) in a disk block for the logical device being addressed.

4.5.48.2 Device type specific target descriptor parameters for block device types

The format for the device type specific target descriptor parameters for block device types (device type code values 00h, 04h, 05h, 07h, and 0Eh) is shown in table 39.

Table 40 — Device type specific target descriptor parameters for block device types

Bit Byte	7	6	5	4	3	2	1	0
28	Reserved					PAD	Reserved	
29	(MSB)							
30	DISK BLOCK LENGTH							
31	(LSB)							

The PAD bit is used in conjunction with the CAT bit (see 6.3.7.1) in the segment descriptor to determine what action should be taken when a segment of the copy does not fit exactly into an integer number of destination blocks.

The DISK BLOCK LENGTH field contains the number of bytes in a disk block [excluding protection information, if any. \(see SBC-2\)](#) for the logical device being addressed.

4.5.49 Mode parameter block descriptor formats

4.5.49.1 General block descriptor format

When the LONGLBA bit is set to zero (see 7.4.3), the mode parameter block descriptor format for all device types except direct-access is shown in table 41.

Table 41 — General mode parameter block descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	DENSITY CODE							
1	(MSB)							
2	NUMBER OF BLOCKS							
3								(LSB)
4	Reserved							
5	(MSB)							
6	BLOCK LENGTH							
7								(LSB)

...

The BLOCK LENGTH field specifies the length in bytes of each logical block [excluding protection information, if any. \(see SBC-2\)](#) described by the block descriptor. For sequential-access devices, a block length of zero indicates that the logical block size written to the medium is specified by the transfer length field in the CDB (see SSC).

4.5.49.2 Direct-access device block descriptor format for LONGLBA=0

When the LONGLBA bit is set to zero (see 7.4.3), the mode parameter block descriptor format for the direct-access device type is shown in table 42.

Table 42 — Direct-access device mode parameter block descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
1	NUMBER OF BLOCKS							
2								
3								
4	(LSB)							
5	DENSITY CODE							
6	(MSB)							
7	BLOCK LENGTH							
8								
9	(LSB)							

...

The BLOCK LENGTH field specifies the length in bytes of each logical block [excluding protection information, if any. \(see SBC-2\)](#) described by the block descriptor.

4.5.49.3 Long LBA block descriptor format

When the LONGLBA bit is set to one (see 7.4.3), the mode parameter block descriptor format for all device types is shown in table 43.

Table 43 — Long LBA mode parameter block descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
7	NUMBER OF BLOCKS (LSB)							
8	DENSITY CODE							
9	Reserved							
10	Reserved							
11	Reserved							
12	(MSB) _____							
15	BLOCK LENGTH (LSB)							

...

The BLOCK LENGTH field specifies the length in bytes of each logical block [excluding protection information, if any. \(see SBC-2\)](#) described by the block descriptor.

4.5.50 Control mode page

The Control mode page (see table 44) provides controls over several SCSI features that are applicable to all device types such as tagged queuing and error logging.

Table 44 — Control mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (0Ah)					
1	PAGE LENGTH (0Ah)							
2	TST			Reserved		D_SENSE	GLTSD	RLEC
3	QUEUE ALGORITHM MODIFIER				Reserved	QERR		DQUE
4	TAS	RAC	UA_INTLCK_CTRL		SWP	Obsolete		
5	APP_TAG_OWN	Reserved				AUTOLOAD MODE		
6	Obsolete							
7								
8	(MSB)	BUSY TIMEOUT PERIOD						(LSB)
9								
10	(MSB)	EXTENDED SELF-TEST COMPLETION TIME						(LSB)
11								

[An application tag owns \(APP_TAG_OWN\) bit set to zero specifies the contents of the DATA BLOCK APPLICATION TAG field in the protected information \(see SBC-2\) may be modified by the device server. An APP_TAG_OWN bit](#)

[set to one specifies the contents of the DATA BLOCK APPLICATION TAG field in the protected information shall not be modified by the device server.](#)

[If the APP_TAG_OWN bit is set to zero the device server shall ignore the contents of the DATA BLOCK APPLICATION TAG field in the protected information when received from the application client.](#)

4.6 Vital product data parameters

4.6.1 Vital product data parameters overview and page codes

This subclause describes the vital product data (VPD) page structure and the VPD pages (see table 45) that are applicable to all SCSI devices. These VPD pages are optionally returned by the INQUIRY command (see 6.4) and contain vendor specific product information about a target or logical unit. The vital product data may include vendor identification, product identification, unit serial numbers, device operating definitions, manufacturing data, field replaceable unit information, and other vendor specific information. This standard defines the structure of the vital product data, but not the contents.

Table 45 — Vital product data page codes

Page code	VPD Page Name	Reference	Support Requirements
82h	ASCII Implemented Operating Definition	4.6.2	Optional
01h - 7Fh	ASCII Information	7.6.3	Optional
83h	Device Identification	7.6.4	Mandatory
81h	Obsolete	3.3.7	
84h	Software Interface Identification	7.6.5	Optional
00h	Supported VPD Pages	7.6.6	Mandatory
80h	Unit Serial Number	7.6.7	Optional
xxh	Protection Information	4.6.2	Optional
85h - AFh	Reserved		
B0h - BFh	(See specific device type)		
C0h - FFh	Vendor specific		

4.6.2 Protection Information VPD page [\(this is a new section\)](#)

The Protection Information VPD page (see table 46) provides the application client with the means to obtain certain protection information parameters supported by the logical unit.

Table 46 — Protection Information VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (xxh)							
2	Reserved							
3	PAGE LENGTH (4)							
4	Reserved					GRD_CHK	APP_CHK	REF_CHK
5	Reserved							
6	Reserved							
7	Reserved							

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are as defined in 6.4.2.

The PAGE LENGTH field specifies the length of the following VPD page data. If the allocation length is less than the length of the data to be returned, the page length shall not be adjusted to reflect the truncation.

A data block guard check (GRD_CHK) bit set to zero indicates the device server does not check the DATA BLOCK GUARD field in the protected information (see SBC-2) before transmitting it to an application client. A GRD_CHK bit set to one indicates the device server does check the DATA BLOCK GUARD field in the protected information before transmitting it to an application client. If the application client or device server detects a data block application tag field of FFFFh, the checking of DATA BLOCK GUARD field in the protected information shall be disabled for the associated data block.

A data block application tag check (APP_CHK) bit set to zero indicates the device server does not check the DATA BLOCK APPLICATION TAG field in the protected information (see SBC-2) before transmitting it to an application client. A APP_CHK bit set to one indicates the device server does check the DATA BLOCK APPLICATION TAG field in the protected information before transmitting it to an application client. If the application client or device server detects a data block application tag field of FFFFh, the checking of DATA BLOCK APPLICATION TAG field in the protected information shall be disabled for the associated data block.

A data block reference check (REF_CHK) bit set to zero indicates the device server does not check the DATA BLOCK REFERENCE TAG field in the protected information (see SBC-2) before transmitting it to an application client. A REF_CHK bit set to one indicates the device server does check the DATA BLOCK REFERENCE TAG field in the protected information before transmitting it to an application client. If the application client or device server detects a data block application tag field of FFFFh, the checking of DATA BLOCK REFERENCE TAG field in the protected information shall be disabled for the associated data block.