TO: T10 Membership, SMC-3 Working Group

FROM: Rod Wideman, ADIC; rod.wideman@adic.com

DATE: June 13<sup>th</sup>, 2005

SUBJECT: SMC-3 ADIC AutoCleaning mode page (document T10/05-237r0)

## Introduction

Per T10/05-182r0, section 10, item (e), this document provides a description of an ADIC legacy mode page used for controlling autocleaning. This description is being provided for discussion purposes only.

# \_Auto Cleaning Page (2Ch)

Figure 9-11 on page 9-26 shows the format of the Auto Cleaning Page.

Bits Bytes	7	6	5	4	3	2	1	0
0	PS	RSVD	Page Code					
1	Parameter List Length = 04h							
2	Reserved						AC	DC
3	Hour							
4	Minute							
5	Reserved							

Figure 9-11 Auto Cleaning Page Format

#### PS

The value of the PS field is 1. This indicates that the page can be saved.

### Page Code

This field identifies the page code for the Auto-Cleaning page. The value of this field is 2Ch.

### Parameter List Length

This field indicates the length of the Auto-Cleaning parameter list. The value of the field is 04h which indicates 4 additional bytes of parameter data.

### AC

1 - indicates Auto-Cleaning is active

0 - indicates Auto-Cleaning is not active

#### DC

If the AC field is active, the DC field is set to 1, if Delayed Cleaning is selected, or set to 0 if Delayed Cleaning is disabled.

#### Hour

If Delayed Cleaning is activated, the hour reports at which hour Delayed Cleaning is scheduled.

#### Minute

If Delayed Cleaning is activated, the minute reports at which minute with in the hour Delayed Cleaning is scheduled.