

To: T10 Technical Committee
 From: Steve Johnson LSI Logic (steve.johnson@lsil.com), Brad Besmer LSI Logic
 Date: 6 April, 2006
 Subject: 06-037r1 SAS-2 SMP Lists (DISCOVER LIST)

Revision history

Revision 0 (9 January, 2006) First revision
 Revision 1 (6 April, 2006) Revised from January 9 and CC meeting discussions.

Related documents

sas2r03 - Serial Attached SCSI 2 revision 3

Revision Overview r0 to r1

Moved expander routing table method and associated SMP requests to 06-078r0.
 Incorporated feedback from January 9 meeting.
 Added descriptor format to fit 48 phy descriptors in a single list

Overview

SMP DISCOVER, requires a separate SMP request and response per PHY identifier. In typical SAS-1.1 topologies the overhead of discovering and configuring the topology can become a significant hindrance to active I/O and fail-over scenarios. Self discovery, zoning, supervisor elections, table to table links, all using 1.1 discovery and routing procedures would add a “boat load” more of SMPs to the SMP storm. The discussion (or requirement) of very large SAS-2 topologies containing 1000’s of end devices, dozens of self configuring expanders and initiators necessitates the need to dramatically improved the discovery and configuration mechanisms.

Part of the solution is to reduce the number of SMP request and responses by combining multiple highly used SMP operations into single requests and responses.

Suggested changes

Add new SMP DISCOVER LIST function to section 10.4.3.x SMP functions of SAS-2. The DISCOVER LIST provides all the necessary data for a self configuring expander to program it’s zoning and route tables along with supervisor election information.

[Editor’s Note 1: Need new name other than DISCOVER LIST, ,,DISCOVERY???](#)

Table 1 — SMP functions (FUNCTION field)

Code	SMP function	Description	Reference
00h	REPORT GENERAL	Return general information about the device	10.4.3.3
01h	REPORT MANUFACTURER INFORMATION	Return vendor and product identification	10.4.3.4
02h	READ GPIO REGISTER	See SFF-8485	
<u>03h</u>	<u>REPORT_ZONE_PERMISSION</u>	<u>Return zone permission table entries</u>	

Table 1 — SMP functions (FUNCTION field)

Code	SMP function	Description	Reference
04h - 0Fh	Reserved for general SMP input functions		
10h	DISCOVER	Return information about the specified phy	10.4.3.5
11h	REPORT PHY ERROR LOG	Return error logging information about the specified phy	10.4.3.6
12h	REPORT PHY SATA	Return information about a phy currently attached to a SATA phy	
13h	REPORT ROUTE INFORMATION	Return route table information	10.4.3.8
14h	REPORT PHY EVENT INFORMATION	Return phy event information for the specified phy	10.4.3.9
<u>15h</u>	<u>REPORT ZONE ROUTE TABLE</u>	Return zone information for each specified phy	
<u>16h</u>	<u>DISCOVER LIST</u>	<u>Return information about the specified list of phys</u>	
17h - 1Fh	Reserved for phy-based SMP input functions		
20h - 3Fh	Reserved for SMP input functions		
40h - 7Fh	Vendor specific		
80h	CONFIGURE GENERAL	Configure the device	10.4.3.10
81h	Reserved for a general SMP output function		
82h	WRITE GPIO REGISTER	See SFF-8485	
<u>83h</u>	<u>CONFIGURE ZONE PERMISSION</u>	<u>Change zone permission table information</u>	
84h	Reserved for general SMP output functions		
85h	ZONED BROADCAST	Transmit the specified BROADCAST on the expander ports in the specified zone group(s)	10.4.3.11
86h - 8Fh	Reserved for general SMP output functions		
90h	CONFIGURE ROUTE INFORMATION	Change route table information	10.4.3.11
91h	PHY CONTROL	Request actions by the specified phy	10.4.3.12
92h	PHY TEST FUNCTION	Request a test function by the specified phy	10.4.3.13
93h	CONFIGURE PHY EVENT INFORMATION	Configure phy event information for the specified phy	10.4.3.14
<u>94h</u>	<u>CONFIGURE PHY ZONE</u>	<u>Change phy entries within a zone route table</u>	
95h - 9Fh	Reserved for phy-based SMP output functions		
A0h - BFh	Reserved for SMP output functions		
C0h - FFh	Vendor specific		

10.4.3.x DISCOVER LIST function

The DISCOVER LIST function returns a list of phy descriptors. This SMP function shall be implemented by all SMP target ports.

Table 2 defines the request format.

Table 2 — DISCOVER LIST request

Byte\Bit	7	6	5	4	3	2	1	0
0	SMP FRAME TYPE (40h)							
1	FUNCTION (16h)							
2	Reserved							
3	REQUEST LENGTH (02h)							
4	Reserved							
7	Reserved							
8	STARTING PHY IDENTIFIER							
9	NUMBER OF DESCRIPTORS							
10	Reserved				PHY IDENTIFIER FILTER			
11	Reserved				DESCRIPTOR TYPE			
12	Reserved							
15	Reserved							
16	Vendor specific							
29	Vendor specific							
30	(MSB)	CRC						(LSB)
31								(LSB)

The SMP FRAME TYPE field shall be set to 40h.

The FUNCTION field shall be set to 16h.

The REQUEST LENGTH field shall be set to 02h.

The STARTING PHY IDENTIFIER field specifies the phy identifier of the first phy in the list of descriptors being requested.

The NUMBER OF DESCRIPTORS field specifies the number of descriptors requested starting with the value specified by the STARTING PHY IDENTIFIER field. If (STARTING PHY IDENTIFIER + NUMBER OF DESCRIPTORS) exceeds the NUMBER OF PHYS field reported in the REPORT GENERAL response (see 10.4.3.3) then

Editor's Note 2: Help, How to state if STARTING PHY IDENTIFIER + NUMBER OF DESCRIPTORS leads to an invalid phy or exceeds a 1K response buffer. Also, does this belong here or on the returned value in the response?

A PHY IDENTIFIER FILTER field set to 0h indicates the SMP target port shall return in the list of descriptors only phy identifiers with the ATTACHED SMP TARGET PORT (see 10.4.3.5) bit set to one. A PHY IDENTIFIER FILTER field

set to 1h indicates the SMP target port shall return in the list of descriptors only phy identifiers with the ATTACHED DEVICE TYPE (see 10.4.3.5) field set to a value other than zero. All other values are reserved.

.A DESCRIPTOR TYPE field set to 0h indicates the descriptor describes a DISCOVER response not including the CRC field (see 10.4.3.5). A DESCRIPTOR TYPE field set to 1h indicates the descriptor describes a Discover List descriptor (see Table 4 —). A DESCRIPTOR TYPE field set to Fh indicates the descriptor format is vendor specific. All other values are reserved.

The CRC field is defined in 10.4.3.2.

Table 3 — DISCOVER LIST response (part 1 of 2)

Byte\Bit	7	6	5	4	3	2	1	0
0	SMP FRAME TYPE (41h)							
1	FUNCTION (16h)							
2	FUNCTION RESULT							
3	RESPONSE LENGTH ((n-7)/4)							
4	Reserved							
7	Reserved							
8	STARTING PHY IDENTIFIER							
9	NUMBER OF DESCRIPTORS							
10	Reserved				PHY IDENTIFIER FILTER			
11	Reserved				DESCRIPTOR TYPE			
12	DESCRIPTOR LENGTH							
13	Reserved							
15	Reserved							
16	(MSB)							
17	EXPANDER CHANGE COUNT							
	(LSB)							
18	ZONE DEVICE	ZONE ADDRESS RESOLVE DEVICE	Reserved			CONFIGURING	CONFIGURABLE ROUTE TABLE	
19	Reserved							
22	Reserved							
23	ACTIVE ZONE SUPERVISOR PRIORITY				ZONE SUPERVISOR PRIORITY			
24	Reserved							
31	ACTIVE ZONE SUPERVISOR SAS ADDRESS							

Table 3 — DISCOVER LIST response (part 2 of 2)

Byte\Bit	7	6	5	4	3	2	1	0
32	Vendor specific							
47								
List of descriptors								
48	FIRST DESCRIPTOR							
m								
...	...							
y	LAST DESCRIPTOR							
n - 4								
n - 3	(MSB)	CRC						
n								

Editor's Note 3: What about PHY_VACANT status? How do we communicate that some phys will have this status returned? Should we add a status to descriptor? What if the format requested is DISCOVER response?

The SMP FRAME TYPE field shall be set to 41h.

The FUNCTION field shall be set to 16h.

The FUNCTION RESULT field is defined in 10.4.3.2.

The RESPONSE LENGTH field shall be set to ((n-7)/4)h.

The STARTING PHY IDENTIFIER field specifies the phy identifier of the first phy in the list of descriptors being returned. The PHY IDENTIFIERS shall be returned in order from low to high.

Editor's Note 4: Need verbiage The starting phy may not be the starting phy depending on the filter.

The NUMBER OF DESCRIPTORS field specifies the number of descriptors returned in the list.

The PHY IDENTIFIER FILTER field is defined in the DISCOVER LIST request.

The DESCRIPTOR TYPE field is defined in the DISCOVER LIST request.

The DESCRIPTOR LENGTH field is determined by the descriptor specified in the DESCRIPTOR TYPE field.

The EXPANDER CHANGE COUNT field is defined in 10.4.3.3

The CONFIGURABLE ROUTE TABLE field is defined in 10.4.3.3

The CONFIGURING field is defined in 10.4.3.3

The ZONE ADDRESS RESOLVE DEVICE field is defined in 10.4.3.3

The ZONE DEVICE field is defined in 10.4.3.3

The ZONE SUPERVISOR PRIORITY field is defined in 10.4.3.3

The ACTIVE ZONE SUPERVISOR PRIORITY field is defined in 10.4.3.3

The ACTIVE ZONE SUPERVISOR SAS ADDRESS field is defined in 10.4.3.3

The CRC field is defined in 10.4.3.2

Table 4 defines the descriptor format.

Table 4 — DISCOVER LIST descriptor

Byte\Bit	7	6	5	4	3	2	1	0
0	PHY IDENTIFIER							
1	Reserved	ATTACHED DEVICE TYPE			Reserved			
2	Reserved			NEGOTIATED PHYSICAL LINK RATE				
3	Reserved			ATTACHED SSP INITIATOR	ATTACHED STP INITIATOR	ATTACHED SMP INITIATOR	ATTACHED SATA HOST	
4	ATTACHED SATA PORT SELECTOR	Reserved		ATTACHED SSP TARGET	ATTACHED STP TARGET	ATTACHED SMP TARGET	ATTACHED SATA DEVICE	
5	Reserved							
6	VIRTUAL PHY	Reserved						
7	ATTACHED SAS ADDRESS							
15	ATTACHED SAS ADDRESS							
16	ATTACHED PHY IDENTIFIER							
17	PHY CHANGE COUNT							
18	ZONE ADDRESS RESOLVE	Reserved		ZONE PARTICIPATING	ZONE SUPERVISOR PRIORITY			
19	ZONE GROUP							
20	Reserved							

The STARTING PHY IDENTIFIER field is defined in 10.4.3.5

The ATTACHED DEVICE TYPE field is defined in 10.4.3.5

The NEGOTIATED PHYSICAL LINK RATE field is defined in 10.4.3.5

The ATTACHED SATA HOST field is defined in 10.4.3.5

The ATTACHED SMP INITIATOR field is defined in 10.4.3.5

The ATTACHED STP INITIATOR field is defined in 10.4.3.5

The ATTACHED SSP INITIATOR field is defined in 10.4.3.5

The ATTACHED SATA DEVICE field is defined in 10.4.3.5

The ATTACHED SMP TARGET field is defined in 10.4.3.5

The ATTACHED STP TARGET field is defined in 10.4.3.5

The ATTACHED SSP TARGET field is defined in 10.4.3.5

The ATTACHED SATA PORT SELECTOR field is defined in 10.4.3.5

The VIRTUAL PHY field is defined in 10.4.3.5

The ATTACHED SAS ADDRESS field is defined in 10.4.3.5

The ATTACHED PHY IDENTIFIER field is defined in 10.4.3.5

The PHY CHANGE COUNT field is defined in 10.4.3.5

The ZONE SUPERVISOR PRIORITY field is defined in 10.4.3.5

The ZONE PARTICIPATING field is defined in 10.4.3.5

The ZONE ADDRESS RESOLVE field is defined in 10.4.3.5

The ZONE GROUP field is defined in 10.4.3.5