

Capability based Command Security

SCSI commands standard proposal

07-454r2

Date: November 20, 2007

To: T10 Committee (SCSI)

From: George Penokie and Sivan Tal (IBM)

Subject: SPC-4: CbCS

Table of Contents

1	Definitions, symbols, abbreviations, and conventions	1
1.1	Definitions	1
1.1.1	Attack.....	1
1.1.2	CbCS Capability.....	1
1.1.3	CbCS capability key	1
1.1.4	CbCS Credential	1
1.1.5	CbCS management application client	1
1.1.6	CbCS management device server	1
1.1.7	CbCS master key.....	2
1.1.8	CbCS master authentication key.....	2
1.1.9	CbCS master generation key	2
1.1.10	CbCS validation tag	2
1.1.11	CbCS working key	2
1.1.12	Command standard	2
1.1.13	Cryptoperiod	2
1.1.14	Integrity check value	2
1.1.15	Shared key.....	2
1.1.16	Secure I_T nexus.....	2
1.1.17	Security token	2
1.2	Acronyms.....	3
2	Capability based Command Security	3
2.1	CbCS overview	3
2.2	Trust assumptions.....	3
2.3	CbCS Capabilities.....	4
2.3.1	Overview.....	4
2.3.2	CbCS Capability validation.....	6
2.4	CbCS credentials	6
2.4.1	CbCS credentials overview	6

2.4.2	Preparing CbCS credentials by the CbCS management device server.....	7
2.4.3	Preparing CbCS credentials by the secure CDB originator	8
2.4.4	Validating CbCS credentials by the enforcement manager	9
2.5	CbCS Methods.....	9
2.5.1	CbCS Methods Overview.....	9
2.5.2	BASIC CbCS method.....	10
2.5.3	CAPKEY CbCS method.....	10
2.6	Shared keys.....	12
2.6.1	Shared keys overview.....	12
2.6.2	Shared key usage in commands.....	13
2.6.3	Computing updated CbCS master generation keys and new CbCS authentication keys	13
2.6.4	Setting and changing shared keys	14
2.7	Association between commands and permission bits	14
2.8	Security attributes	16
3	CbCS extension	17
4	Changes in Extended INQUIRY Data VPD page	18
5	Changes in 5.13.2.2 (SA parameters).....	19
6	Changes in SECURITY PROTOCOL IN command	19
6.1	CbCS SECURITY PROTOCOL	20
6.1.1	Overview.....	20
6.1.2	SECURITY PROTOCOL IN supported CbCS page	20
6.1.3	SECURITY PROTOCOL OUT supported CbCS page	21
6.1.4	Capabilities CbCS page.....	21
6.1.5	Attributes CbCS page	23
6.1.6	Set Master Key, Seed Exchange CbCS page.....	25
7	Changes in SECURITY PROTOCOL OUT command	26
7.1	CbCS SECURITY PROTOCOL	27
7.1.1	Overview.....	27

7.1.2	Set attributes CbCS page	27
7.1.3	Set Key CbCS page	28
7.1.4	Set Master Key, Seed Exchange CbCS page	29
7.1.5	Set Master Key, Change Master Key CbCS page.....	30
8	RECEIVE CREDENTIAL command	32
8.1	RECEIVE CREDENTIAL parameter data	33
8.1.1	CbCS capability format	34
9	Misc. changes	37
9.1	Change in C.3.5 Variable length CDB service action codes.....	37
9.2	Change in Table 48 — Commands for all device types.....	37
10	Association between commands and permission bits	38
11	The PERMISSION BIT MASK descriptor field in CbCS Capability.....	39
12	Association between commands and permission bits	40
13	The PERMISSION BIT MASK descriptor field in CbCS Capability.....	40
14	Association between commands and permission bits	42
15	The PERMISSION BIT MASK descriptor field in CbCS Capability.....	42
16	References.....	43

Changes to SPC-4

Proposal 07-029 defines XCDB (extended CDB) format. This proposal is dependent on 07-029r3.

Legend for the text colors: **New text in blue.** ~~Removed text in red strikethrough.~~ **Proposer's notes in green.**

Changes in revision 5:

- 1) Added Discriminator field in the Capability
- 2) Added optional use of Volume identifier in the capability, for use by SSC devices.
- 3) Adjusted to the new XCDB revision (07-029r3)

1 Definitions, symbols, abbreviations, and conventions

(These are additions to section 3 of SPC-4.)

1.1 Definitions

(These are additions to section 3.1 of SPC-4.)

1.1.1 Attack

The act of trying to bypass security controls on a system.

1.1.2 CbCS Capability

A descriptor that specifies defined access to a logical unit for specific commands. See 2.3.

1.1.3 CbCS capability key

The integrity check value (see 1.1.14) in a CbCS credential (see 1.1.4) returned by the CbCS management device server (see 1.1.6) in response to the RECEIVE CREDENTIAL command (see 8). See 2.4.1.

1.1.4 CbCS Credential

A data structure containing a CbCS capability that is protected by an integrity check value (see 1.1.14) that is sent to and used by an application client in order to grant defined access to a logical unit for specific commands. See 2.4.

1.1.5 CbCS management application client

An application client that manages shared keys (see 1.1.15) stored in logical units. See 2.1.

1.1.6 CbCS management device server

A device server that prepares CbCS credentials (see 1.1.4) in response to application client requests. See 2.1.

1.1.7 CbCS master key

A set of shared keys (see 1.1.15) that consist of a CbCS master authentication key (see 1.1.8) and a CbCS master generation key (see 1.1.9).

1.1.8 CbCS master authentication key

A shared key (see 1.1.15) used to generate integrity check values (see 1.1.14) for CbCS credentials (see 1.1.4) that grant access to commands that sets shared keys in logical units. See 2.5.

1.1.9 CbCS master generation key

A shared key (see 1.1.15) used to generate new CbCS working keys (see 1.1.11).

1.1.10 CbCS validation tag

The integrity check value in a credential sent by the application client in a CbCS extension (see 3). See 2.4.1.

1.1.11 CbCS working key

A shared key (see 1.1.15) that is used in generating integrity check values (see 1.1.14) for CbCS credentials (see 1.1.4) for commands other than those that sets shared keys in logical units. See 2.5.

1.1.12 Command standard

A SCSI standard that defines the model, commands, and parameter data for a device type (e.g., SBC-2, SSC-2, SMC-2, MMC-4, or SES-2). See clause 1.

1.1.13 Cryptoperiod

The time span during which a cryptographic key setting remains in effect.

1.1.14 Integrity check value

A value computed using an integrity algorithm (see 7.7.3.6.4 in 06-449r6), a shared key (see 1.1.15), and an identified set of data that protects the integrity of that identified set of data. See 2.4.

1.1.15 Shared key

A cryptographically generated value that is known only to a limited set of authorized entities.

1.1.16 Secure I_T nexus

An I_T nexus that relies on the security features of a service delivery subsystem to prevent attacks.

1.1.17 Security token

Random Nonce (see 3.1.95) of at least 128 bits that is generated by the device server for each I_T nexus and discarded on detection of an I_T nexus loss (see SAM-4).

1.2 Acronyms

CbCS Capability based Command Security

2 Capability based Command Security

{{This section should be merged into SPC-4 as section 5.13.x.8 – see 07-262r5}}

2.1 CbCS overview

{{GP - This section is now in 07-430}}

2.2 Trust assumptions

After the logical unit is trusted (i.e., after a secure CDB originator authenticates that it is communicating with a specific logical unit), the secure CDB originator trusts the secure CDB processor and the enforcement manager to do the following:

- a) deny any access attempt from any application client that is not authorized by the security manager; and
- b) deny access from any application client that does not performs the protocols and functions defined by this standard.

The CbCS management device server and the CbCS management application client are trusted after:

- a) the CbCS management device server is authenticated by the secure CDB originator; and
- b) the CbCS management application client is authenticated by the CbCS Enforcement Manager.

The CbCS management device server and the CbCS management application client are trusted to do the following:

- a) Securely store long-lived shared keys and capability keys;
- b) Grant credentials to secure CDB originators according to access control policies that are outside the scope of this standard; and
- c) Perform the defined security functions.

The service delivery subsystem between the secure CDB originator and the secure CDB processor is not trusted. However, the CbCS security model is defined so that commands generated by the secure CDB originator are processed by the secure CDB processor only after the secure CDB originator interacts with both the CbCS management device server and the secure CDB processor as defined in this standard.

Communications between the CbCS management application clients, secure CDB originators, CbCS management device servers, and secure CDB processors are trusted based on the requirements shown in Table 1.

Table 1 - Communications trust requirement

Connection	Communication trust requirement
secure CDB originator <--> secure CDB processor	Cryptographic message integrity ^a
secure CDB originator <--> CbCS management device server	Cryptographic confidentiality and integrity
CbCS management application client <--> secure CDB processor	Cryptographic message integrity

CbCS management device server <--> CbCS management application client	Confidentiality and integrity
<p>Confidential communications are protected from eavesdropping by methods outside the scope of this standard.</p> <p>Cryptographic message integrity assures that the message received is the one that was sent (i.e., no tampering occurred). Messages in which tampering is detected shall be discarded.</p> <p>^a Cryptographic message integrity is sufficient for security of the CbCS access control. Confidentiality of the data transferred between the secure CDB originator and the secure CDB processor may be required to prevent passive network attacks and implemented by other means.</p>	

2.3 CbCS Capabilities

2.3.1 Overview

The CbCS extension (see 3) contains a CbCS capability descriptor that specifies the command functions (e.g., read, write, attributes setting and attributes retrieval) that the secure CDB processor is allowed to process in response to the encapsulated SCSI CDB. (See 2.7)

The secure CDB processor validates that the requested functions are allowed by the CbCS capability based on:

- a) The type of functions; and
- b) The logical unit and, optionally, a volume (see SSC-3) mounted in that logical unit.

The policies that determine which CbCS capabilities are provided to which secure CDB originator are outside the scope of this standard.

In response to requests from secure CDB originators, the CbCS management device server shall:

- a) reject the request if the decision database indicates the request is not allowed; or
- b) construct a capability based on the request and the decision database such that the capability is coordinated with other secure CDB originators capabilities and returns that capability to the requesting secure CDB originator.

If the CbCS method in use for the logical unit is BASIC (see 2.5.2), then there may be no decision database and the CbCS management device server functions may be performed by the secure CDB originator.

A CbCS capability descriptor is included in a CbCS credential returned by the CbCS management device server in response to the RECEIVE CREDENTIAL command (see 8), and in CbCS extension parameters (see 3) to enable the CbCS Enforcement Manager to verify that the secure CDB originator is allowed to perform the command functions requested by the encapsulated CDB. The capability format is defined in 8.1.1.

The CbCS capability descriptor specifies:

- a) the CbCS method to apply in validating the CbCS credential;
- b) the cryptographic parameters used in generating the CbCS credential integrity check value;
- c) an expiration time of the CbCS capability;
- d) a permission bit mask that specifies which command functions are authorized by the CbCS capability;
- e) a policy access tag which is used for CbCS credential revocation;

- f) a designation descriptor that uniquely identifies a logical unit or volume (see SSC-3). If the CbCS capability applies to a well-known logical unit, the designation descriptor applies to the target device in which it resides; and
- g) a DISCRIMINATOR field which is used to guarantee uniqueness of credentials and may be used to limit the delegation or prevent leakage of the CbCS capability to other application clients.

The CbCS capability expiration time, if used (see 8.1.1), requires synchronization between the clocks of the CbCS management device server and the enforcement manager. The method for synchronizing the clocks is outside the scope of this standard. If capability expiration time is used, the CbCS management device server should set capability lifetime that is at least an order of magnitude larger than the allowed deviation between the clocks. The protocol for synchronizing the clocks is not specified in this standard, however, the protocol should be implemented in a secure manner (e.g., it should not be possible for an adversary to set the clock in the SCSI device or in the secure CDB processor backwards to enable the reuse of expired CbCS credentials). The REPORT TIMESTAMP command and SET TIMESTAMP command extended with CbCS extension may be used by the CbCS management application client for this purpose.

The POLICY ACCESS TAG field, if used (see 8.1.1), is used for rapid revocation of credentials for a logical unit. It is a settable attribute of the logical unit. The value of the field in the CbCS capability shall match the value of the logical unit's attribute. The CbCS management device server shall set the POLICY ACCESS TAG field to the current LU attribute value. The CbCS management application client may change the logical unit attribute value (see 7.1.2) in order to invalidate outstanding credentials.

The Designation descriptor may be used to:

- a) uniquely identify a logical unit by specifying a Designation descriptor with the ASSOCIATION field set to 00b (see 7.6.3.1);
- b) uniquely identify a SCSI target device by specifying a Designation descriptor with the ASSOCIATION field set to 10b (see 7.6.3.1). The capability is then used in commands sent to a well-known logical unit; and
- c) uniquely identify a volume by specifying a medium auxiliary memory attribute (see 7.3.1) with type VOLUME IDENTIFIER to provide CbCS to volumes within sequential-access devices (see SSC-3 and SMC-3).

The DISCRIMINATOR field specifies a value that shall be used by the CbCS management device server to guarantee uniqueness of credentials. The CbCS management device server shall not return the same credential to two secure CDB originators. If multiple credentials are generated for multiple secure CDB originators, specifying identical values in all other fields (e.g., the same logical unit, the same permissions, the same expiration time) and signed with the same shared key, then the DISCRIMINATOR field shall be used to discriminate between the credentials. The same DISCRIMINATOR field value may be used in multiple credentials if the credential uniqueness requirement is satisfied. The DISCRIMINATOR field may be used to limit the delegation or prevent leakage of the CbCS capability to other application clients while satisfying the uniqueness requirement.

In order to implement CbCS credentials based on logical unit unique identifier, the same identifier type shall be:

- a) used in the CbCS decision database of the security manager (see 2.1);
- b) returned by the secure CDB processor in Device Identification VPD page (Inquiry page 83h);
- c) used by the secure CDB originator to identify the logical unit and request the corresponding CbCS credential from the CbCS management device server; and

- d) returned by the CbCS management device server in the CbCS capability in response to the secure CDB originator's CbCS credential request.

A CbCS management application client may block CbCS capability-based access to a logical unit by:

- a) changing the policy access tag attribute associated with a logical unit (see 7.1.2); or
- b) changing or invalidating the shared keys shared with the enforcement manager.

2.3.2 CbCS Capability validation

The enforcement manager shall validate the CbCS capability descriptor included in the CbCS extension (see 3) and if any of the following conditions occur, the command shall be terminated with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB:

- a) The DESIGNATION TYPE field contains any value other than those defined in Table 21;
- b) The CAPABILITY EXPIRATION TIME field contains a non-zero value and the CAPABILITY EXPIRATION TIME field value is lower than the current time value (i.e., the current number of milliseconds passed since midnight, 1 January 1970 UT);
- c) The enforcement manager is contained within the secure CDB processor, the DESIGNATION TYPE field value is set to 1h (i.e., logical unit designation descriptor), and the contents of the designation descriptor in which a logical unit name (see SAM-4) is indicated does not match the addressed logical unit.
- d) The enforcement manager is contained within the SCSI target device (i.e., addressed as a well-known logical unit), the DESIGNATION TYPE field value is set to 1h (i.e., logical unit designation descriptor), and the contents of the designation descriptor in which a SCSI target device is indicated does not match the SCSI target device that contains the addressed well-known logical unit;
- e) The DESIGNATION TYPE field value is set to 2h (MAM Attribute descriptor) and the designation descriptor does not match the MAM attribute of the volume residing in the addressed logical unit;
- f) The POLICY ACCESS TAG field in the CbCS capability descriptor contains a non-zero value and the POLICY ACCESS TAG field value does not match the Policy Access Tag of the addressed logical unit; or
- g) The encapsulated command is not permitted by the PERMISSIONS BIT MASK field.

2.4 CbCS credentials

2.4.1 CbCS credentials overview

A CbCS credential authorizes specific access to a specific logical unit and optionally to a volume (see SSC-3) mounted in that logical unit. It consists of a CbCS capability and an integrity check value. The CbCS capability descriptor (see 2.3) identifies the logical unit or volume (see SSC-3) and specifies the specific access rights and parameters specifying how it shall be validated by the enforcement manager. The integrity check value authenticates the CbCS capability and is used for validation.

In the CbCS protocol CbCS credentials are transferred as follows:

- a) A CbCS credential is transferred from the CbCS management device server to a secure CDB originator over a communications mechanism that meets the requirements specified in Table 1 with the CbCS credential being returned in response to the RECEIVE CREDENTIAL command (see 8); and

- b) A CbCS credential is transferred from the secure CDB originator to the secure CDB processor over a communications mechanism that meets the requirements specified in Table 1 with the credential being placed in the extension parameters of the CDB CbCS extension (see 3).

The RECEIVE CREDENTIAL command is used to request a CbCS credential from the CbCS management device server (see 8).

If the CAPKEY CbCS method is used, the enforcement manager shall validate each CbCS-extended command request to confirm that:

- a) The credential has not been tampered with (i.e., that the CbCS credential was generated by the CbCS management device server and includes an integrity check value generated using a shared key known only to the CbCS management device server, the CbCS management application client, and the enforcement manager);
- b) The credential was obtained from the CbCS management device server (i.e., the capability key associated with the credential provides a proper integrity check value for the command); and
- c) The requested SCSI command encapsulated in the received CDB is permitted by the capability in the credential (see 2.6.4).

If the BASIC CbCS method is used, the secure CDB processor shall validate each command received from an application client to confirm that the requested SCSI command encapsulated in the received CDB is permitted by the CbCS capability in the CbCS credential (see 2.6.4).

A CbCS credential includes a CbCS capability and an integrity check value. The integrity check value in a CbCS credential returned by the CbCS management device server in response to the RECEIVE CREDENTIAL command (see 8) is used to generate the integrity check value in a CbCS credential sent by the secure CDB originator in a CbCS extension (see 3).

The integrity check value in a CbCS credential returned by the CbCS management device server in response to the RECEIVE CREDENTIAL command is the CbCS capability key. The integrity check value in a CbCS credential sent by the secure CDB originator in a CbCS extension is the validation tag.

The validation tag allows the enforcement manager to validate a CbCS credential and determine if the CbCS capability has been tampered with (e.g., an application client that has just the CbCS capability but not the CbCS capability key is unable to generate CbCS credentials with a valid validation tag in the integrity check value). The CbCS credential may be delegated, if a secure CDB originator delegates both the CbCS capability and the CbCS capability key.

The CbCS capability keys are computed using shared keys that are shared between the CbCS management device server and the enforcement manager. The shared keys are managed by the SCSI security manager. The command integrity check values (i.e. the validation tags) are computed using CbCS capability keys.

2.4.2 Preparing CbCS credentials by the CbCS management device server

In response to a request from a secure CDB originator, the CbCS management device server shall prepare and return a CbCS credential (see Table 19) as follows:

- 1) If the information in the decision database does not authorize the secure CDB originator's request, no CbCS credential shall be returned to the requesting secure CDB originator (i.e. the CRED PRSNT bit (see 8.1)) in the returned parameter data shall be set to zero);
- 2) Prepare the CbCS capability and insert it in the CbCS credential as follows:
 - a. Shall set the CbCS METHOD field to the value of the corresponding field in the Attributes CbCS page (see 6.1.5) of the logical unit for which the credential is requested;

- b. Shall set the KEY VERSION field to the number of the working key used to compute the credential integrity check value. This value shall match one of the WORKING KEY IDENTIFIER fields in the Attributes CbCS page (see 6.1.5) of the logical unit for which the credential is requested, or for the target device in case there are no working keys set for the logical unit;
- c. Shall set the INTEGRITY CHECK VALUE ALGORITHM field to the value that specifies the algorithm used to compute all integrity check values related to this CbCS credential. The algorithm shall be one of those identified by the supported integrity check value algorithm attributes in the CbCS capabilities page (see 6.1.4) of the logical unit for which the credential is requested;
- d. Shall set the CAPABILITY EXPIRATION TIME field to a value that is consistent with the CbCS policy;
- e. May set the DISCRIMINTOR field in a vendor specific manner;
- f. Shall set the PERMISSIONS BIT MASK descriptor to a value that is consistent with the authorization information in the decision database;
- g. Shall set the POLICY ACCESS TAG field to a value that matches the POLICY ACCESS TAG attribute in the Attributes CbCS page (see 6.1.5) of the logical unit for which the CbCS credential is requested. The value zero may be used to prevent revocation by changing the policy access tag attribute of the logical unit;
- h. Shall set the DESIGNATION TYPE field, and the Designation descriptor field to those of the logical unit or volume (see SSC-3) to which the credential is requested; and
- i. If the CbCS method in use is CAPKEY, then shall compute the CbCS capability key as described in 2.5.3.2, and place it in the INTEGRITY CHECK VALUE field in the CbCS credential. If the CbCS method in use is BASIC, then shall set the INTEGRITY CHECK VALUE field to zero;

and

- 3) Return the CbCS credential to the secure CDB originator with the integrity check value serving as the CbCS capability key.

Security management commands issued by the CbCS management application client to the secure CDB processor require that the integrity check value is computed using the authentication CbCS master key rather than a CbCS working key. For a list of commands requiring use of the CbCS master key see 2.6.2. If the CbCS master key is used to compute the CbCS credential integrity check value then the KEY VERSION field in the CbCS capability descriptor shall be set to zero.

For CbCS credentials returned by the CbCS management device server in response to the RECEIVE CREDENTIAL command (see 8), only CbCS working keys shall be used in computing the INTEGRITY CHECK VALUE field.

2.4.3 Preparing CbCS credentials by the secure CDB originator

The secure CDB originator shall prepare the CbCS credential for sending it to the secure CDB processor in the CDB CbCS extension parameters as follows:

- a) If the CAPKEY CbCS method is enabled, then copy the CbCS capability descriptor received from the CbCS management device server in response to the RECEIVE CREDENTIAL command into the CbCS capability descriptor parameter of the CDB CbCS extension. If the BASIC CbCS method enabled, then prepare the CbCS capability descriptor in the CbCS capability descriptor parameter of the CDB CbCS extension (see 2.4.2); and
- b) If the CAPKEY CbCS method is enabled, then compute the validation tag as described in 2.5.3.3 and place it in the INTEGRITY CHECK VALUE parameter of the CDB CbCS extension.

2.4.4 Validating CbCS credentials by the enforcement manager

The enforcement manager shall validate CbCS credentials as follows:

- a) If the CAPKEY CbCS method is enabled and the CBCS METHOD field in the CbCS capability descriptor is other than CAPKEY, then the command shall be terminated with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB;
- b) If the CAPKEY CbCS method is enabled, then:
 - a. Compute the CbCS capability key as described in 2.5.3.2;
 - b. Compute the validation tag as described in 2.5.3.3; and
 - c. Compare the computed validation tag with the INTEGRITY CHECK VALUE field in the CbCS extension parameters. If they don't match, then the command shall be terminated with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB;

and

- c) Verify the CbCS capability descriptor as described in 2.3.2.

2.5 CbCS Methods

2.5.1 CbCS Methods Overview

This standard defines two CbCS methods (see Table 2).

Table 2 - CbCS methods

Method	Description	Without a secure I_T nexus	With a secure I_T nexus
BASIC	Protection against errors ^a	No protection against attacks	Service delivery subsystem integrity
CAPKEY	Protection against errors and attacks ^b	Verification of credentials, vulnerable to some network attacks	Verification of credentials and protection from service delivery subsystem attacks
^a The enforcement manager verifies the CbCS capability allows the command but does not verify the authenticity of the CbCS capability prior to allowing the secure CDB processor to process a command. ^b CAPKEY is based on the protocol presented and analyzed in [ACF+02]. CAPKEY verifies that the secure CDB originator rightfully obtained the credential it is presenting.			

If the secure CDB processor receives a command for a logical unit:

- a) that has CbCS enabled;
- b) the opcode field is set to 7Eh (i.e. Extended SCSI Command CDB); and
- c) the extension type is set to 00h (i.e. CbCS extension),

then the credential shall be validated before any other field in the CDB is validated.

If the secure CDB processor receives a command for a logical unit:

- a) that has CbCS enabled;
- b) the opcode is not 7Eh (i.e. not Extended SCSI Command CDB); and

- c) the received command requires authorization as described in 2.6.4,

then the command shall be terminated with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

If the secure CDB processor receives a command for a logical unit:

- a) that has CbCS enabled;
- b) the opcode is 7Eh (i.e. Extended SCSI Command CDB);
- c) the extensions do not include an extension type set to 00h (i.e. CbCS extension); and
- d) the encapsulated command requires authorization as described in 2.6.4,

then the command shall be terminated with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

2.5.2 BASIC CbCS method

The BASIC CbCS method validates that the CbCS capability authorizes the encapsulated command for each CDB. It provides centrally-managed policy-driven command access control mechanism that enforces authorized access based on capabilities.

The BASIC CbCS method does not validate the authenticity of the CbCS capability.

Preparing CbCS credentials for the BASIC CbCS method does not require the knowledge of any shared keys and may be done by the secure CDB originator without coordination with the CbCS management device server. The CbCS capability descriptor (see 2.3, 8.1.1) is set with the CBCS METHOD field set to BASIC. The integrity check value is set to zero.

The BASIC CbCS method controls access between the secure CDB originator and the secure CDB processor without requiring authentication of the secure CDB originator by the enforcement manager. It is sufficient for the secure CDB processor to verify the CbCS capabilities sent by the secure CDB originator.

Deleted: secures

The enforcement manager validates the CbCS capability as described in 2.3.2.

2.5.3 CAPKEY CbCS method

2.5.3.1 CAPKEY CbCS method overview

The CAPKEY CbCS method provides centrally-managed policy-driven command access control mechanism that enforces authorized access based on capabilities. In addition, it assures the integrity and authenticity of the CbCS capability information in each command. It provides for security of commands delivered to the secure CDB processor. When used in conjunction with a secure service delivery subsystem, it provides additional protection against intrusion (see 2.1).

The integrity of the CbCS capability shall be validated before any other command processing is done, including CbCS capability validation.

Given a CbCS credential and a secure I_T nexus (see 1.1.16), the protocol ties the CbCS credential to the secure I_T nexus via a validation tag. The validation tag is computed by the secure CDB originator as PRF(Cap-Key, SecurityToken),

Where:

PRF is a pseudorandom function.

Cap-Key is the CbCS capability key associated with the command (see 2.5.3.2).

SecurityToken identifies the communication channel and is unique to the particular I_T nexus (see 1.1.17).

An I_T nexus loss event or reset event (see SAM-4) shall cause the security token to change.

SecurityToken is chosen by the secure CDB processor. A secure CDB originator may request the value of the SecurityToken (see 6.1.5). The secure CDB processor compares the I_T nexus on which a request was received and its SecurityToken, and verifies that the validation tag attached to the request equals PRF(Cap-Key, SecurityToken).

To ensure the request is authenticated by the secure CDB originator who obtained the CbCS credential, the CbCS capability key (Cap-Key) with which the validation tag PRF(Cap-Key, SecurityToken) is computed depends on the CbCS capability.

CbCS capabilities and integrity check values may be reused as follows:

- a) The secure CDB originator may reuse the CbCS capability and Cap-Key on multiple commands for the same logical unit(s);
- b) The secure CDB originator is required to calculate the validation tag once per I_T_L nexus; and
- c) The Cap-Key and validation tag shall be calculated the first time the secure CDB processor receives a given CbCS capability on a given I_T_L nexus and may be reused in processing every command received on the I_T_L nexus.

2.5.3.2 Computing the CbCS capability key

When preparing CbCS credentials (see 2.4.2) and validating CbCS credentials (see 2.4.4), the CbCS capability key shall be computed by the CbCS management device server and the CbCS Enforcement Manager using:

- a) The algorithm specified in the INTEGRITY CHECK VALUE ALGORITHM field in the CbCS capability descriptor;
- b) If the value of the KEY VERSION field in the CbCS capability descriptor is nonzero, the shared key to be used is specified by the KEY VERSION field, otherwise the authentication master key is used as the shared key; and
- c) The CbCS capability descriptor as the input data.

The CbCS capability key is placed in the INTEGRITY CHECK VALUE field of the CbCS credential returned in the RECEIVE CREDENTIAL command.

2.5.3.3 Computing the validation tag

When preparing CbCS credentials (see 2.4.3), the validation tag shall be computed by the secure CDB originator using:

- 1) The algorithm specified in the INTEGRITY CHECK VALUE ALGORITHM field in the CbCS capability descriptor;
- 2) The CbCS capability key returned from the RECEIVE CREDENTIAL command in the INTEGRITY CHECK VALUE field;
- 3) The security token returned by the secure CDB processor in the CbCS Attributes page (see 6.1.5) as the input data.

The validation tag is placed in the INTEGRITY CHECK VALUE field of the CbCS credential passed by the secure CDB originator in the CbCS extension (see 3).

2.6 Shared keys

2.6.1 Shared keys overview

All CbCS credentials are based on shared keys that are shared between the enforcement manager, the CbCS management application client that manages its security attributes, and the CbCS management device server that grants CbCS credentials to application clients. Shared keys shall be refreshed regularly to maintain cryptoperiods (see 1.1.13) according to security policies that are outside of the scope of this standard.

Shared key management requirements are as follows:

- 1) The CbCS management application client should replace the logical unit's shared keys in a secure manner even if the I_T_L nexus it has with the logical unit is not secure;
- 2) The enforcement manager shall support multiple CbCS working keys; and
- 3) The CbCS management application client shall contain a random source for generating shared keys.

Each logical unit has a CbCS master key and a set of CbCS working keys assigned to it. A single set of shared keys may be shared among multiple logical units within a SCSI target device.

The CbCS working keys are used to generate the CbCS capability keys that are used by secure CDB originators to access logical units. CbCS working keys should have a short cryptoperiod (e.g., an hour), however, cryptoperiods are defined by security policies outside the scope of this standard. A shared key refresh shall invalidate all CbCS credentials generated by that shared key. The enforcement manager shall support up to 16 refreshed versions of the shared key as valid (i.e., define multiple shared keys that are concurrently valid). The shared key version field in the CbCS capability is used to indicate which shared key shall be used in the validation process (see 8.1.1).

When setting a new shared key, the CbCS management application client assigns the shared key with a version number. The KEY VERSION field in the CbCS capability descriptor is set to the version number of the CbCS working key used in computing the CbCS capability key (see 8.1.1). The enforcement manager uses the KEY VERSION field to determine which shared key to use in validating a CbCS credential in a CbCS extended command (see 2.4.4).

A CbCS master generation key is used to generate working shared keys. A CbCS master authentication key is used to generate CbCS credentials for commands to set and refresh keys, and modify device security attributes. The CbCS master key (i.e., the pair of CbCS master generation key and CbCS master authentication key) may be refreshed. Refreshing the CbCS master key is accomplished by a Diffie-Hellman key exchange algorithm that ensures forward secrecy of the CbCS master key. This algorithm is carried over a sequence of commands as follows:

- 1) SECURITY PROTOCOL OUT command specifying the CbCS protocol and the Set Master Key, Seed Exchange page (7.1.4);
- 2) SECURITY PROTOCOL IN command specifying the CbCS protocol and the Set Master Key, Seed Exchange page (6.1.6); and
- 3) SECURITY PROTOCOL OUT command specifying the CbCS protocol and the Set Master Key, Change Master Key page (7.1.5).

Separate sets of the CbCS master key and the CbCS working keys may be used for each logical unit, or a single set may be used for all logical units served by a security protocol well-known logical unit's secure CDB processor as follows:

- 1) A single set of CbCS master keys and CbCS working keys is used by the enforcement manager through the SECURITY PROTOCOL well-known logical unit. This set of shared keys serves all the logical units within the SCSI target device;

- 2) A separate set of CbCS master keys and CbCS working keys is used for each logical unit within the SCSI target device; and
- 3) A single set of CbCS master keys and CbCS working keys is used by the enforcement manager through the SECURITY PROTOCOL well-known logical unit. In addition, a separate set of CbCS master key and CbCS working keys may be used for any logical unit within the SCSI target device. The single set of shared keys serves any logical unit that does not have its own set of keys.

2.6.2 Shared key usage in commands

Every CbCS credential prepared by the CbCS management device server includes an integrity check value field containing a CbCS capability key that is computed using either a CbCS working key or the CbCS master authentication key associated with the logical unit.

The CbCS authentication master key shall be used in preparing CbCS credentials for commands that set shared keys. For other commands, the shared key that shall be used is one of the CbCS working keys associated with the logical unit. The KEY VERSION field in the CbCS capability descriptor shall be set to a value that identifies that particular working key (see 8.1.1).

The following commands involve setting shared keys and require using the CbCS master authentication key for preparing the credential:

- a) SECURITY PROTOCOL OUT command specifying the CbCS security protocol and the Set Key page (see 7.1.3);
- b) SECURITY PROTOCOL OUT command specifying the CbCS security protocol and the Set Master Key, Seed Exchange page (see 7.1.4);
- c) SECURITY PROTOCOL IN command specifying the CbCS security protocol and the Set Master Key, Seed Exchange page (see 6.1.6); and
- d) SECURITY PROTOCOL OUT command specifying the CbCS security protocol and the Set Master Key, Change master Key page (see 7.1.5).

If the CbCS extended command is SECURITY PROTOCOL OUT command specifying the CbCS security protocol and the Set Master Key, Change Master Key page, then the shared key that shall be used is the next CbCS authentication master key computed after GOOD status has been returned by the SECURITY PROTOCOL IN command specifying the CbCS security protocol and the Set Master Key, Seed Exchange page.

2.6.3 Computing updated CbCS master generation keys and new CbCS authentication keys

When processing the commands that involve setting shared keys (i.e., the Set Key CbCS page (see 7.1.3) and the Set Master Key CbCS pages (see 7.1.4, 6.1.6, and 7.1.5)), the enforcement manager shall compute new CbCS master generation keys and CbCS working keys as follows:

- a) The algorithm specified in the INTEGRITY CHECK VALUE ALGORITHM field in the CbCS capability descriptor;
- b) The input shared key value shall be one of the following:
 - a) For a Set Key CbCS page (see 7.1.3), the CbCS master generation key; or
 - b) For a CbCS master key computed following the processing of the Set Master Key, Change Master Key CbCS page (see 7.1.5), the previous CbCS master generation key shall be used;

and

- c) The input data (i.e., seed) shall be one of the following:
 - a) For a Set Key CbCS page, the contents of the SEED field of the Set Key CbCS page; or
 - b) For a Set Master Key, Change Master Key CbCS page, the value computed after successful completion of the SECURITY PROTOCOL IN command specifying the Set Master Key, Seed Exchange CbCS page (see 6.1.6) and updated by the Set Master Key, Change Master Key CbCS page (see 7.1.5).

When processing the commands for setting the CbCS master key (i.e., the Set Master Key CbCS pages (see 7.1.4, 6.1.6, and 7.1.5)), the enforcement manager shall compute the new CbCS master authentication key as follows:

- a) The algorithm specified in the INTEGRITY CHECK VALUE ALGORITHM field in the CbCS capability descriptor;
- b) The input key value shall be the CbCS master generation key prior to processing the command; and
- c) The input data shall be the seed value computed (see 6.1.6) with the least significant bit changed as follows:
 - a) If the seed value least significant bit is zero, then the least significant bit shall be set to one; or
 - b) If the seed value least significant bit is one, then the least significant bit shall be set to zero.

2.6.4 Setting and changing shared keys

On successful completion of a SECURITY PROTOCOL OUT command specifying the CbCS protocol and the Set Master Key, Change Master Key CbCS page, the device server shall:

- a) Replace the CbCS authentication master key with the next CbCS authentication master key computed after the return of GOOD status for the most recent SECURITY PROTOCOL IN command specifying the CbCS protocol and the Set Master Key, Seed Exchange CbCS page (see 6.1.6);
- b) Replace the CbCS generation master key with the next CbCS generation master key computed after the return of GOOD status for the most recent SECURITY PROTOCOL IN command specifying the CbCS protocol and the Set Master Key, Seed Exchange CbCS page; and
- c) Invalidate all the CbCS working keys on the logical unit.

For every shared key that is invalidated by this command, the associated key identifier attribute shall have its attribute set to zero.

The next CbCS authentication master key computed after the return of GOOD status for the most recent SECURITY PROTOCOL IN command specifying the CbCS protocol and the Set Master Key, Seed Exchange CbCS page (see 6.1.6) shall be used to compute the capability key for this command.

2.7 Association between commands and permission bits

The following commands shall, if implemented, be processed by the secure CDB processor without requiring CbCS extension (see 3):

- a) CHANGE ALIASES command;
- b) INQUIRY command;
- c) REPORT LUNS command;

- d) REPORT SUPPORTED OPERATION CODES command;
- e) REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command;
- f) REPORT TARGET PORT GROUPS command; and
- g) TEST UNIT READY command.

The RECEIVE CREDENTIAL command shall be accepted by the CbCS management device server without requiring CbCS extension.

Command standards (1.1.12) may define commands that are processed by the secure CDB processor without requiring CbCS extension. Command standards define the conditions either in the device model or in the descriptions each of specific command.

If the secure CDB processor receives a command that does not require CbCS extension and the command is extended with CbCS extension, then the command shall, if implemented, be processed by the device server.

The following commands shall not be processed by a secure CDB processor within a logical unit that has the CbCS bit set to one in the extended inquiry data:

- a) ACCESS CONTROL IN command:
- b) ACCESS CONTROL OUT command:
- c) EXTENDED COPY command: and
- d) RECEIVE COPY RESULTS command.

Command standards (1.1.12) may define commands that shall not be processed by the secure CDB processor within a logical unit that has the CbCS bit set to one in the extended inquiry data. Command standards define the conditions either in the device model or in the descriptions each of specific command.

The PERMISSIONS BIT MASK descriptor in the CbCS capability (see 2.3) specifies which commands are allowed by this CbCS capability. When processing CbCS extension commands, the enforcement manager shall verify that the bits applicable to the encapsulated SCSI command are all set to one in the PERMISSIONS BIT MASK descriptor before processing the request specified by the CbCS extended SCSI command.

The associations between commands and permission bits are specified in Table 3 for commands defined in this standard. Command standards may specify associations between commands and permission bits.

If the secure CDB processor receives a command that requires CbCS extension (see 3), and the command is not extended with CbCS extension, then the command shall be terminated with a CHECK CONDITION status, the sense key shall be set to ILLEGAL REQUEST, and the additional sense code shall be set to INVALID FIELD IN CDB.

Table 3 defines the permissions required in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor for each SCSI command defined in this standard. (See 8.1.1)

Table 3 - Associations between commands and permissions

Requested command	Permissions						
	DATA READ	DATA WRITE	PARM READ	PARM WRITE	SEC MGMT	RESRV	MGMT
LOG SELECT			v				
LOG SENSE				v			
MANAGEMENT PROTOCOL IN							v
MANAGEMENT PROTOCOL OUT							v
MODE SELECT(6)				v			

Requested command	Permissions					
MODE SELECT(10)				v		
MODE SENSE(6)			v			
MODE SENSE(10)			v			
PERSISTENT RESERVE IN			v			
PERSISTENT RESERVE OUT						v
READ ATTRIBUTE			v			
READ BUFFER					v	
READ MEDIA SERIAL NUMBER			v			
RECEIVE DIAGNOSTIC RESULTS			v			
REPORT ALIASES			v			
REPORT IDENTIFYING INFORMATION			v			
REPORT PRIORITY			v			
REPORT TIMESTAMP			v			
REQUEST SENSE			v			
SECURITY PROTOCOL IN					v	
SECURITY PROTOCOL OUT					v	
SEND DIAGNOSTIC				v		
SET IDENTIFYING INFORMATION				v		
SET PRIORITY				v		
SET TARGET PORT GROUPS				v		
SET TIMESTAMP				v	v	
WRITE ATTRIBUTE				v		
WRITE BUFFER					v	
For each cell in marked with 'v', the secure CDB processor shall process the requested command only if the corresponding bit is set in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor						

Deleted: PERFORM TASK
MANAGEMENT FUNCTION ... [1]

Deleted: TEST UNIT READY ... [2]

2.8 Security attributes

Device servers supporting CbCS may support the following security attributes:

- SCSI target device based;
- logical unit based; or
- both.

If a device server supports both target based security attributes and a logical unit based security attributes and receives both target based security attributes and a logical unit based security attributes, then the logical unit based security attribute overrides the target based security attribute on that device server.

SCSI target device attributes are queried and modified through the SECURITY PROTOCOL well-known logical unit (see 8.5 [spc4r11])

Table 4 specifies the CbCS attributes.

Table 4 - CbCS attributes

Security attribute name	Length (bytes)	SCSI target device or logical unit specific	Application client settable
Supported CbCS methods	n*2	SCSI target device	No
Default CbCS method	2	SCSI target device	Yes
CbCS method	2	SCSI target device/Logical unit	Yes

Security attribute name	Length (bytes)	SCSI target device or logical unit specific	Application client settable
Supported integrity check value algorithms	n*4	SCSI target device	No
Supported DH groups	n*4	SCSI target device	No
Clock	6	SCSI target device	Yes
CbCS master key identifier	8	SCSI target device / Logical unit	No ^c
CbCS working key identifier	16*8	SCSI target device / Logical unit	No ^c
LU initial policy access tag	4	SCSI target device	Yes
Policy access tag	4	Logical unit	Yes
Security token	Not defined ^b	Logical unit ^a	No
^a The security token returned by the device server is unique to the I_T nexus on which the security token is returned. ^b The security token length is specific to the implementation of secure channel for the I_T nexus ^c The shared key identifier is set by the application client when a new shared key is generated as described in 7.1.3 and 7.1.5. It is not settable by means of setting CbCS security attributes described in 7.1.2			

The supported CbCS methods attribute is used by the device server to report its supported CbCS methods. See 2.5.

The default CbCS method attribute is the CbCS method the device server shall apply to a newly created CbCS logical unit, if a CbCS method is not specified at logical unit creation time. The default CbCS method shall be one of the supported CbCS methods.

The supported integrity check value algorithms security attribute is used by a device server to report its supported integrity check value algorithms. Integrity check value algorithms shall be used to compute integrity check values. See 7.7.3.6.4 Table x36 in 06-449r8.

The supported DH group security attribute is used by a device server to report the DH groups it supports for the Diffie-Hellman key exchange with the application client that is processed as part of setting a new CbCS master key (see 7.1.4). See 7.7.3.6.5 Table x38 in 06-449r8.

The clock security attribute shall contain the current time in use by the device server represented as the count of the number of milliseconds elapsed since midnight, 1 January 1970 UT.

The LU initial policy access tag security attribute specifies the initial value for the policy access tag for a newly created logical unit. The initial value for this attribute shall be set to FFFF FFFFh (see 2.3).

The policy access tag security attribute specifies the expected non-zero contents of the POLICY ACCESS TAG field in any capability that allows access to this logical unit (see 2.3).

Setting and querying security attributes are used by the application client by issuing the SECURITY PROTOCOL IN command and SECURITY PROTOCOL OUT command with the CbCS security protocol (see 6.1, 7.1).

3 CbCS extension

{{Editor's note: I'm not sure where exactly this section should be added in SPC-4.}}

{{Editor's note: This section is based on 07-029r3}}

The CbCS extension allows the application of CbCS to a SCSI command using the parameters specified in this subclause.

Support for CbCS extension type is mandatory if the CbCS bit in extended INQUIRY data (see 4) is set to one.

The extended CDB may be any CDB defined in any SCSI command set standard.

Table 5 - CbCS extension descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	EXTENSION TYPE (00h)							
1	Reserved							
3								
4	CbCS capability descriptor							
75								
76	INTEGRITY CHECK VALUE							
139								

The CbCS capability descriptor is defined in 8.1.1.

The CbCS capability descriptor and the INTEGRITY CHECK VALUE field shall be prepared by the secure CDB originator as described in 2.4.3.

The enforcement manager shall validate the CbCS capability descriptor and the INTEGRITY CHECK VALUE field as described in 2.4.4.

{{Sep 18 CAP review ended here.}}

4 Changes in Extended INQUIRY Data VPD page

[Change in 7.6.4 Extended INQUIRY Data VPD page]

The Extended INQUIRY Data VPD page (see table 361) provides the application client with a means to obtain information about the logical unit.

Table 361 — Extended INQUIRY Data VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (86h)							
2	Reserved							
3	PAGE LENGTH (3Ch)							
4	Reserved		SPT			GRD_CHK	APP_CHK	REF_CHK
5	Reserved			GROUP_SUP	PRIOR_SUP	HEADSUP	ORDSUP	SIMPSUP
6	Reserved					COR_DSUP	NV_SUP	V_SUP
7	Reserved							LUICLR

Bit Byte	7	6	5	4	3	2	1	0
8	Reserved							CbCS
9	Reserved							
63	Reserved							

<Unchanged text here>

A Capability based Command Security (CbCS) bit set to one indicates that the logical unit has CbCS (see 2). A CbCS bit set to zero indicates that the logical unit does not support CbCS.

5 **Changes in 5.13.2.2 (SA parameters)**

The USAGE_TYPE SA parameter shall be one of the values shown in table 45.

Table 45 – USAGE_TYPE SA parameter values

Value	Description	Reference
0000h - 0080h	Reserved	
0081h	Tape Data Encryption	SSC-3
0082h	CbCS Credential Authentication and Encryption	xxx
0083h - FFFFh	Reserved	

6 Changes in SECURITY PROTOCOL IN command

[Changes in section 6.29 SECURITY PROTOCOL IN command]

6.29.1 SECURITY PROTOCOL IN command description

Table 186 — SECURITY PROTOCOL field in SECURITY PROTOCOL IN command

Code	Description	Reference
00h	Security protocol information	6.29.2
01h - 06h	Defined by the TCG	3.1.128
07h	CbCS	6.29.3 (6.1)
08h - 1Fh	Reserved	
20h	Tape Data Encryption	SSC-3
21h - EDh	Reserved	
EEh	Authentication in Host Attachments of Transient Storage Devices	IEEE P1667
EFh	ATA Device Server Password Security	TBD
F0h - FFh	Vendor Specific	

6.1 CbCS SECURITY PROTOCOL

(New section in SPC-4: 6.29.3)

6.1.1 Overview

(New section in SPC-4: 6.29.3.1)

The SECURITY PROTOCOL IN command specifying the CbCS protocol requests the device server to return the security attributes of the:

- a) logical unit; or
- b) SCSI target device that contains the addressed SECURITY PROTOCOL well-known logical unit.

The SECURITY PROTOCOL IN command supports CbCS pages that may be requested one at a time. An application client requests a CbCS page by using a SECURITY PROTOCOL IN command with the SECURITY PROTOCOL field set to 07h (i.e., CbCS protocol) and the SECURITY PROTOCOL SPECIFIC field set to the requested CbCS page code.

The SECURITY PROTOCOL SPECIFIC field (see Table 6) specifies the CbCS pages.

Table 6 – SECURITY PROTOCOL SPECIFIC field

Code	Description	Support	Reference
0000h	SECURITY PROTOCOL IN supported CbCS page	M	6.1.2
0001h	SECURITY PROTOCOL OUT supported CbCS page	M	6.1.3
0002h-000Fh	Reserved		
0010h	Capabilities CbCS page	M	6.1.4
0011h	Attributes CbCS page	M	6.1.5
0012h	Set Master Key, Seed Exchange CbCS page	M	6.1.6
0013h – FFFFh	Reserved		
Support key: M – Mandatory for device servers that support CbCS. O – Optional			

6.1.2 SECURITY PROTOCOL IN supported CbCS page

(New section in SPC-4: 6.29.3.2)

Table 7 specifies the format of the SECURITY PROTOCOL IN supported CbCS page.

Table 7 - SECURITY PROTOCOL IN supported CbCS page

Bit Byte	7	6	5	4	3	2	1	0
0	PAGE CODE (0000h)							(LSB)
1	PAGE LENGTH (n-3)							
2	(MSB)							

Bit Byte	7	6	5	4	3	2	1	0
3								(LSB)
4	(MSB)	SECURITY PROTOCOL IN supported CbCS page (first)						
5								(LSB)
	⋮							
n-1	(MSB)	SECURITY PROTOCOL IN supported CbCS page (last)						
n								(LSB)

The SECURITY PROTOCOL IN supported CbCS page shall contain a list of all of the CbCS pages the device server supports for the SECURITY PROTOCOL IN command specifying the CbCS protocol in ascending order beginning with page code 0000h.

6.1.3 SECURITY PROTOCOL OUT supported CbCS page

(New section in SPC-4: 6.29.3.3)

Table 8 specifies the format of the SECURITY PROTOCOL OUT supported CbCS page.

Table 8 - SECURITY PROTOCOL IN supported CbCS page format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PAGE CODE (0001h)						
1								(LSB)
2	(MSB)	PAGE LENGTH (n-3)						
3								(LSB)
4	(MSB)	SECURITY PROTOCOL IN supported CbCS page (first)						
5								(LSB)
	⋮							
n-1	(MSB)	SECURITY PROTOCOL IN supported CbCS page (last)						
n								(LSB)

The SECURITY PROTOCOL OUT supported CbCS page shall contain a list of all of the CbCS pages that the device server supports for the SECURITY PROTOCOL OUT command specifying the CbCS protocol in ascending order.

6.1.4 Capabilities CbCS page

(New section in SPC-4: 6.29.3.4)

Table 9 specifies the format of the Capabilities CbCS page.

Table 9 – Capabilities CbCS page format

Byte \ Bit	7	6	5	4	3	2	1	0	
0	(MSB) PAGE CODE (0010h)								
1									(LSB)
2	(MSB) PAGE LENGTH ($i*2+j*4+k*4+8$)								
3									(LSB)
4	GKS	LUKS	GCMS	LUCMS	Reserved				
5	Reserved								
6	Number of supported CbCS methods (i)								
7									(LSB)
8	SUPPORTED CBCS METHOD (first)								
9									(LSB)
	.								
$i*2+6$	SUPPORTED CBCS METHOD (last)								
$i*2+7$									(LSB)
$i*2+8$	Number of supported integrity check value algorithms (j)								
$i*2+9$									(LSB)
$i*2+10$	SUPPORTED INTEGRITY CHECK VALUE ALGORITHM (first)								
$i*2+13$									(LSB)
	.								
$i*2+j*4+6$	SUPPORTED INTEGRITY CHECK VALUE ALGORITHM (last)								
$i*2+j*4+9$									(LSB)
$i*2+j*4+10$	Number of supported D-H groups (k)								
$i*2+j*4+11$									(LSB)
$i*2+j*4+12$	SUPPORTED D-H GROUP (first)								
$i*2+j*4+15$									(LSB)
	.								
$i*2+j*4+k*4+8$	SUPPORTED D-H GROUP (last)								
$i*2+j*4+k*4+11$									(LSB)

A Global Keys Support (GKS) bit set to one specifies that the device server supports a single CbCS master key and a set of CbCS working keys for the SCSI target device. A GKS bit set to zero specifies

that the device server does not support single CbCS master key and a set of CbCS working keys for the SCSI target device.

A Logical Unit Keys Support (LUKS) bit set to one specifies that the device server supports separate sets of the CbCS master key and the CbCS working keys for each logical unit. A LUKS bit set to zero specifies that the device server does not support separate sets of the CbCS master key and the CbCS working keys for each logical unit.

A Global CbCS method Support (GCMS) bit set to one specifies that the SCSI target device that contains this logical unit supports global CbCS method (i.e., contains a SECURITY PROTOCOL well known logical unit). A GCMS bit set to zero specifies that the device server requires the CbCS methods to be assigned to each logical unit.

A Logical Unit CbCS method Support (LUCMS) bit set to one specifies that the device server supports per-logical unit CbCS method. A LUCMS bit set to zero specifies that the device server does not support per-logical unit CbCS method.

The SUPPORTED CBCS METHOD fields contain coded values of the CbCS methods (see 2.5) supported by the device server. The coded values are specified in Table 22.

The SUPPORTED INTEGRITY CHECK VALUE ALGORITHM fields contain coded values of the algorithm to compute integrity check values supported by the device server (see 2.4). The coded values are specified in 7.7.3.6.4 Table x36 in 06-449r8.

The SUPPORTED DH GROUP attributes contain coded values identifying the supported values in the DH_GROUP field of Set Master Key, Seed Exchange page (see 7.1.4). The coded values are specified in 7.7.3.6.5 Table x38 in 06-449r8.

6.1.5 Attributes CbCS page

(New section in SPC-4: 6.29.3.5)

Table 10 specifies the format of the Attributes CbCS page.

Table 10 - Attributes CbCS page format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB) PAGE CODE (0010h)								
1								(LSB)	
2	(MSB) PAGE LENGTH (n-3)								
3								(LSB)	
4	(MSB) CBCS METHOD								
5								(LSB)	
6	(MSB) POLICY ACCESS TAG								
9								(LSB)	
10	(MSB) MASTER KEY IDENTIFIER								
17								(LSB)	
18	(MSB) WORKING KEY IDENTIFIER 0								
25								(LSB)	

Bit Byte	7	6	5	4	3	2	1	0
	.							
138	WORKING KEY IDENTIFIER 15							
145								
146	CLOCK							
151								
152	Reserved							
153	SECURITY TOKEN LENGTH							
154	SECURITY TOKEN							
n								

If the addressed logical unit is the SECURITY PROTOCOL well-known logical unit:

- a) the CBCS METHOD field is the CbCS method that shall be assigned by the W-LUN's device manager to a new logical unit within the SCSI target device;
- b) the POLICY ACCESS TAG field is the initial policy access tag that shall be assigned by the W-LUN's device server to a new logical unit within the SCSI target device;
- c) if the device server does not support global CbCS method (i.e., the GCMS bit is set to zero in the Capabilities CbCS page), then the CBCS METHOD field is undefined; and
- d) if the device server does not support global keys (i.e., the GKS bit is set to zero in the Capabilities CbCS page), then the MASTER KEY IDENTIFIER field and all the WORKING KEY IDENTIFIER fields should contain FFFF FFFFh

If the addressed logical unit is not the SECURITY PROTOCOL well-known logical unit:

- a) the CBCS METHOD field is the current CbCS method used for the addressed logical unit;
- b) the POLICY ACCESS TAG field is the current policy access tag assigned to the addressed logical unit;
- c) if the device server does not support per-logical unit CbCS method (i.e., the LUCMS bit is set to zero in the Capabilities CbCS page), then the CBCS METHOD field is undefined; and
- d) if the device server does not support per-logical unit keys (i.e., the LUKS bit is set to zero in the Capabilities CbCS page), the MASTER KEY IDENTIFIER field and all the WORKING KEY IDENTIFIER fields should contain FFFF FFFFh.

CbCS methods are described in detail in 2.5.

Shared keys are described in 2.5.

If shared keys are supported for the addressed logical unit, the values of those fields are as follows:

- a) The MASTER KEY IDENTIFIER field shall contain the key identifier value from the most recent successful SECURITY PROTOCOL OUT command specifying the CbCS security protocol and the Set Master Key, Change Master Key page (see 7.1.5). If that command has never been processed, then the MASTER KEY IDENTIFIER field shall contain FFFF FFFEh; and
- b) Each KEY IDENTIFIER field contains the key identifier value from the most recent successful SECURITY PROTOCOL OUT command specifying the CbCS security protocol and the Set Key page, with the KEY VERSION field set to the pertinent key (0-15) (see 7.1.3). If a shared key is

invalid (e.g., never set, invalidated by a Set Master Key, Change Master Key page, or invalidated by a Set Key page), the pertinent KEY IDENTIFIER field should contain 0000 0000h.

The CLOCK field shall be set to the TIMESTAMP field format and value defined in 5.12.

Deleted: contain the current time in use by the device server represented as the count of the number of milliseconds elapsed since midnight, 1 January 1970 UT

The SECURITY TOKEN field (see 1.1.16) contains a value that is unique to the I_T nexus or I_T_L nexus on which the SECURITY PROTOCOL IN command was sent. See 2.5.3.

If the CBCS METHOD field value is BASIC, then the MASTER KEY IDENTIFIER field, the KEY IDENTIFIER fields and the SECURITY TOKEN field are undefined.

6.1.6 Set Master Key, Seed Exchange CbCS page

(New section in SPC-4: 6.29.3.6)

Table 11 specifies the format of the Set Master Key, Seed Exchange CbCS page.

Table 11 - Set Master Key, Seed Exchange CbCS page format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) PAGE CODE (0012h)							(LSB)
1								
2	(MSB) PAGE LENGTH (n-3)							(LSB)
3								
4	DH DATA							
n								

If a SECURITY PROTOCOL IN command specifying Set Master Key, Seed Exchange CbCS page is received and no SECURITY PROTOCOL OUT command specifying Set Master Key, Seed Exchange CbCS page (see 7.1.4) has been completed successfully on the same I_T_L nexus during the past ten seconds, the command shall be terminated with a CHECK CONDITION status, the sense key shall be set to ILLEGAL REQUEST, and the additional sense code shall be set to INVALID FIELD IN CDB.

A device server that receives a SECURITY PROTOCOL OUT command specifying Set Master Key, Seed Exchange CbCS page on one I_T_L nexus may terminate the command with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to SYSTEM RESOURCE FAILURE if any of the following command processing is incomplete on a different I_T_L nexus:

- SECURITY PROTOCOL OUT command specifying Set Master Key, Seed Exchange CbCS page (see 7.1.4);
- SECURITY PROTOCOL IN command specifying Set Master Key, Seed Exchange CbCS page (see 6.1.6); or
- SECURITY PROTOCOL OUT command specifying Set Master Key, Change Master Key CbCS page (see 7.1.5).

The DH DATA field contains the device server DH_data computed as follows:

- A random number, y , is generated having a value between zero and DH_prime minus one observing the requirements in RFC 1750; and
- The device server DH_data is equal to $DH_generator^y$ modulo DH_prime .

The DH_generator and DH_prime values are identified by the Diffie-Hellman group specified in the DH GROUP field in the most recent SECURITY PROTOCL OUT command specifying the Set Master Key, Seed Exchange page (see 7.1.4) that was received on the same I_T_L nexus.

After GOOD status has been returned for SECURITY PROTOCOL OUT command and before the SECURITY PROTOCOL OUT command specifying the Set Master Key, Change Master Key page is processed, the next CbCS authentication master key and next CbCS generation master key shall be computed as described in 2.6.3, using a seed value that is the concatenation of the following:

- 1) $DH_generator^{xy}$ modulo DH_prime ; and
- 2) The whole content of the Device Identification VPD page (83h) returned from the addressed logical unit for the INQUIRY command (see 7.6.3 [spc4r09]).

The value of $[DH_generator^{xy} \text{ modulo } DH_prime]$ is computed by the device server using the formula $[(DH_generator^x \text{ modulo } DH_prime)^y \text{ modulo } DH_prime]$, where $[DH_generator^x \text{ modulo } DH_prime]$ is the content of the DH DATA field in the last SECURITY PROTOCL OUT command specifying the Set Master Key, Seed Exchange page (see 7.1.4) that was received on the same I_T_L nexus.

{{Editor's note: Proof for $(DH_generator^x \text{ modulo } DH_prime)^y \text{ modulo } DH_prime = DH_generator^{xy} \text{ modulo } DH_prime$:

Claim: $(g^x \text{ mod } p)^y \text{ mod } p = g^{xy} \text{ mod } p$

Proof:

Denote $g^x = a*p + b$, where a is in integer and $0 \leq b < p$

1. Thus, $g^x \text{ mod } p = b$, and so $(g^x \text{ mod } p)^y \text{ mod } p = b^y \text{ mod } p$

2. $g^{xy} \text{ mod } p = (a*p + b)^y \text{ mod } p$. Ppening $(a*p + b)^y$ we get a list of addends in which all addends but one are divisible by p . the only addend which is not divided by p is b^y and so

$$g^{xy} \text{ mod } p = b^y \text{ mod } p$$

}}

7 Changes in SECURITY PROTOCOL OUT command

[Changes in section 6.30 SECURITY PROTOCOL OUT command]

<Unchanged text here>

The SECURITY PROTOCOL field (see table 191) specifies which security protocol is being used.

Table 191 — SECURITY PROTOCOL field in SECURITY PROTOCOL OUT command

Code	Description	Reference
00h	Reserved	
01h - 06h	Defined by the TCG	3.1.128
07h	CbCS	
08h - 1Fh	Reserved	
20h	Tape Data Encryption	SSC-3
21h - EDh	Reserved	
Eeh	Authentication in Host Attachments of Transient Storage Devices	IEEE P1667

Code	Description	Reference
EFh	ATA Device Server Password Security	TBD
F0h - FFh	Vendor Specific	

7.1 CbCS SECURITY PROTOCOL

(New section in SPC-4: 6.30.1)

7.1.1 Overview

The SECURITY PROTOCOL OUT command specifying CbCS protocol is used to configure the CbCS shared keys and attributes in the device server.

The command supports CbCS pages that may be sent one at a time. An application client requests to send a CbCS page by using a SECURITY PROTOCOL OUT command with the SECURITY PROTOCOL field set to 07h (CbCS protocol) and the SECURITY PROTOCOL SPECIFIC field set to the CbCS page code requested.

The SECURITY PROTOCOL SPECIFIC field (see Table 12) specifies the type of CbCS page that the application client is sending.

Table 12 - SECURITY PROTOCOL SPECIFIC field values

Code	Description	Support	Reference
0000h – 0010h	Reserved		
0011h	Set Attributes CbCS page	O	7.1.2
0012h	Set Key CbCS page	M	7.1.3
0013h	Set Master Key, Seed Exchange CbCS page	M	7.1.4
0014h	Set Master Key, Change Master Key CbCS page	M	7.1.5
0015h – FFFFh	Reserved		
Support key: M – Mandatory for device servers that support the CbCS protocol O – Optional			

If the SECURITY PROTOCOL SPECIFIC field is set to a reserved or unsupported value, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

7.1.2 Set attributes CbCS page

(New section in SPC-4: 6.30.1.2)

Table 13 specifies the format of the Set Attributes CbCS page.

Table 13 – Set Attributes CbCS page format

Bit Byte	7	6	5	4	3	2	1	0
-------------	---	---	---	---	---	---	---	---

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) PAGE CODE (0011h) (LSB)							
1								
2	(MSB) PAGE LENGTH (6) (LSB)							
3								
4	(MSB) CBCS METHOD (LSB)							
5								
6	(MSB) POLICY ACCESS TAG (LSB)							
9								

The PAGE LENGTH field indicates the number of bytes of parameter data to follow. If the page length value is any value other than 6, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

The CBCS METHOD field specifies the CbCS method to apply to the addressed logical unit (see 2.5). The CBCS METHOD field shall be set to:

- the reserved value FFFFh to specify no change shall be made to the current CbCS method;
- a value equal to the current CbCS method shall not be considered an error; and
- a value that does not match any of the supported CbCS methods reported in the Capabilities CbCS page (see 6.1.4), shall cause the device server to terminate the SECURITY PROTOCOL OUT command with CHECK CONDITION status and set the sense key to ILLEGAL REQUEST and the additional sense code to INVALID FIELD IN PARAMETER DATA.

The list of coded values of CbCS methods is defined in Table 22.

The POLICY ACCESS TAG field specifies a new policy access tag for the addressed logical unit. The value set to 0000 0000h specifies no change shall be made to the current policy access tag value. If the addressed logical unit is the SECURITY PROTOCOL well-known logical unit and the POLICY ACCESS TAG field contains any value other than 0000 0000h, the device server shall terminate the SECURITY PROTOCOL OUT command with CHECK CONDITION status and set the sense key to ILLEGAL REQUEST and the additional sense code to INVALID FIELD IN PARAMETER DATA.

This command shall be authorized and shall be sent extended by a CbCS extension (see 3).

7.1.3 Set Key CbCS page

(New section in SPC-4: 6.30.1.3)

Table 14 specifies the Set Key CbCS page format.

Table 14 - Set Key CbCS page format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) PAGE CODE (0012h) (LSB)							
1								
2	(MSB) PAGE LENGTH (30)							

Bit Byte	7	6	5	4	3	2	1	0
3	(LSB)							
4	Reserved							
5	Reserved				KEY VERSION			
6	(MSB)	KEY IDENTIFIER						(LSB)
13	(LSB)							
14	(MSB)	SEED						(LSB)
33	(LSB)							

The KEY VERSION field specifies the key version to be updated.

The KEY IDENTIFIER field specifies a unique identifier to be associated with the new shared key. The shared key identifier value shall be associated with the attribute specified in the Attributes CbCS page (see 6.1.5).

The SEED field contains a random number generated from a good source of entropy (e.g., as described in RFC 1750).

The updated shared key value shall be computed as described in 2.6.3.

This command shall be authorized and shall be sent extended with CbCS extension (see 3).

7.1.4 Set Master Key, Seed Exchange CbCS page

(New section in SPC-4: 6.30.1.4)

Table 15 specifies the Set Master Key, Seed Exchange CbCS page format.

Table 15 - Set Master Key CbCS page format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PAGE CODE (0013h)						(LSB)
1	(LSB)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3	(LSB)							
4	(MSB)	DH GROUP						(LSB)
5	(LSB)							
6	(MSB)	DH DATA LENGTH						(LSB)
9	(LSB)							
10	(LSB)							
n	(LSB)							

A device server that receives a SECURITY PROTOCOL OUT command specifying Set Master Key, Seed Exchange CbCS page on one I_T_L nexus may terminate the command with a CHECK

CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to SYSTEM RESOURCE FAILURE if any of the following command processing is incomplete on a different I_T_L nexus:

- a) SECURITY PROTOCOL OUT command specifying Set Master Key, Seed Exchange CsCB page (see 7.1.4);
- b) SECURITY PROTOCOL IN command specifying Set Master Key, Seed Exchange CsCB page (see 6.1.6); or
- c) SECURITY PROTOCOL OUT command specifying Set Master Key, Change Master Key CsCB page (see 7.1.5).

The DH GROUP field contains the Diffie-Hellman group (see 7.7.3.6.5 in 06-449r6) that identifies the DH_generator value and DH_prime value to be used in the seed exchange. If the value in the DH GROUP field is not listed in one of the SUPPORTED D-H GROUP fields in the Capabilities CbCS page (see 6.1.4), then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The DH DATA LENGTH field specifies the number of bytes of the DH DATA field.

The DH_DATA field contains the DH data and is computed as follows:

$$DH\ data = DH_generator^x \text{ modulo } DH_prime$$

Where:

- X is a random value between zero and DH_prime minus one as defined in RFC 4086;
- DH_generator is defined by the DH GROUP field; and
- DH_prime is defined by the DH GROUP field.

Deleted: 1750

7.1.5 Set Master Key, Change Master Key CbCS page

(New section in SPC-4: 6.30.1.5)

Table 16 specifies the format of the Set Master Key, Change Master Key CbCS page.

Table 16 - Set Master Key, Change Master Key CbCS page format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB) PAGE CODE (0014h)								
1								(LSB)	
2	(MSB) PAGE LENGTH (n-3)								
3								(LSB)	
4	(MSB) KEY IDENTIFIER								
11								(LSB)	
6	(MSB) APPLICATION CLIENT DATA LENGTH (k-9)								
9								(LSB)	
10	APPLICATION CLIENT DH DATA								
k									

Bit Byte	7	6	5	4	3	2	1	0
k+1	(MSB)							
k+4	DEVICE SERVER DATA LENGTH (n-(k+4))							(LSB)
k+5	DEVICE SERVER DH DATA							
n								

If a SECURITY PROTOCOL OUT command specifying Set Master Key, Change Master Key CbCS page is received and no SECURITY PROTOCOL IN command specifying Set Master Key, Seed Exchange CbCS page has completed successfully on the same I_T_L nexus during the past ten seconds, the command shall be terminated with a CHECK CONDITION status, the sense key shall be set to ILLEGAL REQUEST, and the additional sense code shall be set to INVALID FIELD IN CDB.

A device server that receives a SECURITY PROTOCOL OUT command specifying Set Master Key, Change master Key CbCS page on one I_T_L nexus may terminate the command with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to SYSTEM RESOURCE FAILURE if any of the following command processing is incomplete on a different I_T_L nexus:

- a) SECURITY PROTOCOL OUT command specifying Set Master Key, Seed Exchange CsCB page (see 7.1.4);
- b) SECURITY PROTOCOL IN command specifying Set Master Key, Seed Exchange CsCB page (see 6.1.6); or
- c) SECURITY PROTOCOL OUT command specifying Set Master Key, Change Master Key CsCB page (see 7.1.5).

The KEY IDENTIFIER field specifies a unique identifier to be associated with the new CbCS master key. The shared key identifier value shall be placed into the MASTER KEY IDENTIFIER field in the Attributes CbCS page (see 6.1.5) before the command completes.

Table 17 specifies special shared key identifiers that shall not be used when setting shared keys. Any value not listed in the table is permitted for use by the application client when setting shared keys.

Table 17 – Special shared key identifiers

Value	Description
0000 0000h	A shared key that was never set or was invalidated
FFFF FFEh	An initial shared key set by the device server
FFFF FFFFh	Pertinent shared key is not supported by the device server

If the value of the KEY IDENTIFIER field contains a value that is listed in Table 17, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

The APPLICATION CLIENT DATA LENGTH field specifies the number of bytes that follow in the APPLICATION CLIENT DH DATA field.

The APPLICATION CLIENT DH_DATA field contains the DH_data from the last SECURITY PROTOCOL OUT command specifying CbCS Set Master Key, Seed Exchange CbCS page on the same I_T_L nexus on which this command was received.

The DEVICE SERVER DATA LENGTH field contains the length in bytes of the DEVICE SERVER DH DATA field.

The DEVICE SERVER DH DATA field contains the device server DH_data from the last SECURITY PROTOCOL IN command specifying Set Master Key, Seed Exchange CbCS page on the same I_T_L nexus on which this command was received.

If the content of the APPLICATION CLIENT DATA LENGTH field of the SECURITY PROTOCOL OUT commands Set Master Key, Seed Exchange CbCS page does not match the content of the:

- a) DH DATA LENGTH field in a SECURITY PROTOCOL OUT Set Master Key, Seed Exchange CbCS page that was processed on this I_T_L nexus since a I_T nexus loss event, logical unit reset event, or reset event (see SAM-4);
- b) DH DATA field in a SECURITY PROTOCOL OUT Set Master Key, Seed Exchange CbCS page that was processed on this I_T_L nexus since a I_T nexus loss event, logical unit reset event, or reset event;
- c) PAGE LENGTH field in a SECURITY PROTOCOL IN Set Master Key, Seed Exchange CbCS page that was processed on this I_T_L nexus since a I_T nexus loss event, logical unit reset event, or reset event; or
- d) DH DATA field in a SECURITY PROTOCOL IN Set Master Key, Seed Exchange CbCS page that was processed on this I_T_L nexus since a I_T nexus loss event, logical unit reset event, or reset event,

then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

8 RECEIVE CREDENTIAL command

[A new sub-section in section 6 of SPC-4]

The RECEIVE CREDENTIAL command (see Table 18) allows the application client to receive a CbCS credential for use in the CbCS extension (see 3).

Table 18 - RECEIVE CREDENTIAL CDB format

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
6	-----							
7	ADDITIONAL CDB LENGTH (18h or 3Dh)							
8	(MSB)	SERVICE ACTION (1800h)						-----
9	-----						(LSB)	
10	(MSB)	ALLOCATION LENGTH						-----
11	-----						(LSB)	
12	-----							
31	Designation descriptor							
32	MAM Attribute							

Bit Byte	7	6	5	4	3	2	1	0
68								

If a RECEIVE CREDENTIAL command is received before a SECURITY PROTOCOL IN command has completed successfully on the same I_T_L nexus as the RECEIVE CREDENTIAL command was received with the following field settings:

- a) SECURITY PROTOCOL field set to xxh (i.e., IKEv2-SCSI); and
- b) the SECURITY PROTOCOL SPECIFIC field set to 0103h (i.e., Authentication step),

then the command shall be terminated with a CHECK CONDITION status, the sense key set to NOT READY, and the additional sense code set to LOGICAL UNIT NOT READY, SECURITY INITIALIZATION REQUIRED.

GP – The above is a new ASCQ. It should be the next free 04h xxh value. All devices should be indicated}}

If before a SECURITY PROTOCOL IN command has completed successfully on the same I_T_L nexus as the RECEIVE CREDENTIAL command was received with the following field settings:

- a) SECURITY PROTOCOL field set to xxh (i.e., IKEv2-SCSI);
- b) the SECURITY PROTOCOL SPECIFIC field set to 0102h (i.e., Key Exchange step); and
- c) the SCSI Cryptographic Algorithms payload contains a cryptographic algorithm descriptor of type Encryption Algorithm (ENCR) (i.e., ALGORITHM TYPE 01h) and an identifier other than ENCR_NULL (i.e., ALGORITHM IDENTIFIER other than 8001_000Bh),

then the command shall be terminated with a CHECK CONDITION status, the sense key set to NOT READY, and the additional sense code set to LOGICAL UNIT NOT READY, SECURITY INITIALIZATION REQUIRED.

The ALLOCATION LENGTH field is defined in 4.3.4.6 [spc4r11].

The format of the Designation descriptor field is defined in Table 346 [spc4r11]. The size of the Designation descriptor shall not exceed 24 bytes. The DESIGNATOR TYPE field value shall be set to 3h (NAA). If the DESIGNATOR TYPE field contains any value other than 3h (NAA), this command shall be terminated with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The MAM Attribute field is optional. The format of the MAM Attribute field is specified in 7.3.1 [spc4r11]. If the MAM Attribute field is present and the ATTRIBUTE IDENTIFIER within the MAM Attribute contains any value other than 0008h (VOLUME IDENTIFIER), this command shall be terminated with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

8.1 RECEIVE CREDENTIAL parameter data

The RECEIVE CREDENTIAL parameter data is defined in Table 19.

Table 19 - Credential format

Bit Byte	7	6	5	4	3	2	1	0
0	CRED PRSNT	Reserved			CREDENTIAL FORMAT (1h)			
1	Reserved							

Comment: Look into changing all this into essentially a reference to the IKE-2 SA like it was done for tape. See proposal 06-225r7 for an example on the bottom of page 3. GP-1 don't understand this comment

Comment: This needs to be filled in now that 07-437 has passed.

Deleted: INITIALIZING COMMAND REQUIRED.

Comment: This needs to be filled in now that 07-437 has passed.

Deleted: 0000

Deleted: I

Deleted: INITIALIZING COMMAND REQUIRED.

Bit Byte	7	6	5	4	3	2	1	0
2	(MSB) CREDENTIAL LENGTH (n-3)							(LSB)
3								
4	(MSB) CAPABILITY LENGTH (k-5)							(LSB)
5								
6	CbCS capability descriptor							
k								
k+1	(MSB) INTEGRITY CHECK VALUE LENGTH (n-(k+4))							(LSB)
k+4								
k+5	INTEGRITY CHECK VALUE							
n								

If the Credential Present (CRED PRSNT) bit is set to zero, no CbCS credential shall be returned, and the rest of the parameter data is undefined. If the Credential Present (CRED PRSNT) bit is set to one, a CbCS credential is returned in the parameter data.

The CREDENTIAL FORMAT field specifies the format of the CbCS credential. It shall be set to 1h.

The CREDENTIAL LENGTH field indicates the length in bytes of the rest of the data (i.e. the CbCS credential) that follows.

The CAPABILITY LENGTH specifies the length in bytes of the CbCS capability descriptor field.

The format of the CbCS capability descriptor is defined in 8.1.1.

INTEGRITY CHECK VALUE LENGTH specifies the length of the INTEGRITY CHECK VALUE field.

The INTEGRITY CHECK VALUE field contains a value that the application client shall use for preparing CbCS credentials (see 2.4.3).

8.1.1 CbCS capability format

The format of the CbCS capability descriptor is defined in Table 20.

Table 20 - Capability descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	DESIGNATION TYPE				KEY VERSION			
1	CBCS METHOD							
2	(MSB) INTEGRITY CHECK VALUE ALGORITHM							(LSB)
5								
6	(MSB) CAPABILITY EXPIRATION TIME							(LSB)
11								
12	PERMISSIONS BIT MASK descriptor							
15								

Bit Byte	7	6	5	4	3	2	1	0
16	(MSB) POLICY ACCESS TAG (LSB)							
19								
20	Designation descriptor							
55								
56	DISCRIMINATOR							
71								

The DESIGNATION TYPE field (see Table 21) specifies the format of the Designation descriptor

Table 21 – DESIGNATION TYPE field

Code	Description	Reference
0h	Reserved	
1h	Logical unit designation descriptor	7.6.3.2.1 and 7.6.3.2.2
2h	MAM Attribute descriptor	7.3.1 Table 278
3h - Fh	Reserved	

If the DESIGNATION TYPE field contains any value other than the ones defined in Table 21, then this command shall be terminated with a CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The KEY VERSION field specifies which shared key, from the set of CbCS working keys, is being used to compute the integrity check value.

The CBCS METHOD field should be set a valid CbCS security method (see Table 22). The CbCS security methods are described in detail in 2.5.

Table 22 – The CbCS Security methods

Code	CbCS method	Reference
0000h	BASIC	2.5.2
0001h	CAPKEY	2.5.3
0002h – 0FFFh	Reserved	
1000h – FFFEh	Vendor specific	
FFFFh	Reserved	

The INTEGRITY CHECK VALUE ALGORITHM field specifies the algorithm used to compute the integrity check value for this CbCS capability (see 2.4). It shall be set to a value defined in Table x27 in 06-449r6.

The CAPABILITY EXPIRATION TIME field specifies expiration time of the CbCS capability. The time is the number of milliseconds that have elapsed since midnight, 1 January 1970 UT. If the CAPABILITY EXPIRATION TIME field is non-zero and is less than the current time set in the device

server when processing the command, the command shall be terminated with a CHECK CONDITION status, the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

If the CAPABILITY EXPIRATION TIME field contains zero, the capability has no expiration time.

The PERMISSIONS BIT MASK descriptor (see Table 23) specifies the permissions allowed by this CbCS capability. More than one permissions bit may be set. The device server shall verify that the bits applicable to the encapsulated command are all set to one in the PERMISSIONS BIT MASK descriptor before performing the encapsulated SCSI command.

The association of permissions to SCSI commands is defined in 2.7 for commands defined in this standard. Associations for specific commands are defined in the specific command standards.

In Table 23 byte 0 and byte 1 specify the command functions for all SCSI commands. In Table 23 byte 2 and byte 3 may be used by command standards to specify permissions. Other command set standards shall not override the definition of Table 23 byte 0 and byte 1 as defined in this standard.

Deleted: command functions

The associations between the permissions specified in the permissions bit mask descriptor and SCSI commands defined in this standard are specified in 2.7.

Deleted: command functions

Table 23 – PERMISSIONS BIT MASK descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	DATA READ	DATA WRITE	PARM READ	PARM WRITE	SEC MGMT	RESRV	MGMT	Reserved
1	Reserved							
2	For device type specific use							
3								

A DATA READ bit set to zero indicates the encapsulated SCSI command has no read permission for user data and protection information. A DATA READ bit set to one indicates the encapsulated SCSI command has read permission.

A DATA WRITE bit set to zero indicates the encapsulated SCSI command has no write permission for user data and protection information. A DATA WRITE bit set to one indicates the encapsulated SCSI command has write permission.

A parameter data read (PARM READ) bit set to zero indicates the encapsulated SCSI command has no parameter data read permission. A PARM READ bit set to one indicates the encapsulated SCSI command has parameter data read permission.

A parameter data write (PARM WRITE) bit set to zero indicates the encapsulated SCSI command has no parameter data write permission. An PARM WRITE bit set to one indicates the encapsulated SCSI command has parameter data write permission.

A security management (SEC MGMT) bit set to zero indicates the encapsulated SCSI command has no security management permission. A SEC MGMT bit set to one indicates the encapsulated SCSI command has security management permission.

A reservation (RESRV) bit set to zero indicates the encapsulated SCSI command has no persistent reservation permission. A RESRV bit set to one indicates the encapsulated SCSI command has persistent reservation permission.

A management (MGMT) bit set to zero indicates the encapsulated SCSI command has no storage management permission. A MGMT bit set to one indicates the encapsulated SCSI command has storage management permission. Informative note: The management permission is provided for

authorizing the use of SMI-S operations wrapped in MANAGEMENT_PROTOCOL_IN and MANAGEMENT_PROTOCOL_OUT commands.

If the POLICY ACCESS TAG field contains a value other than zero, the policy access tag attribute of the logical unit (see 6.1.5) is compared to the POLICY ACCESS TAG field contents as part of verifying the capability. If the POLICY ACCESS TAG field contains zero, then no comparison is made to the policy access tag attribute of the logical unit.

If the non-zero value in the CDB POLICY ACCESS TAG field is not identical to the value in the policy access tag attribute of the logical unit (see 6.1.5), then the command shall be terminated with a CHECK CONDITION status, the sense key shall be set to ILLEGAL REQUEST, and the additional sense code shall be set to INVALID FIELD IN CDB.

The format of the Designation descriptor field is defined by the value of the DESIGNATION TYPE field. The size of the Designation descriptor shall not exceed 36 bytes.

The DISCRIMINATOR field provides uniqueness to the Capability descriptor structure (see 2.3.1).

9 Misc. changes

9.1 Change in C.3.5 Variable length CDB service action codes

The variable length CDB service action codes assigned by this standard are shown in table C.8.

Service Action Code	Description
1800h	RECEIVE CREDENTIAL
1801h – 1FFFh	Reserved

9.2 Change in Table 48 — Commands for all device types

In section 6.1, add the RECEIVE CREDENTIAL command to table 48.

Changes to SBC-3

Legend for the text colors: New text in blue. ~~Removed text in red strikethrough.~~ Proposer's notes in green.

10 Association between commands and permission bits

Table 24 defines the permissions required in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor (see SPC-4) for each SCSI command defined in this standard.

Table 24 - Associations between commands and CbCS permissions

Requested command	Permissions							
	DATA READ	DATA WRITE	PARM READ	PARM WRITE	SEC MGMT	RESRV	MGMT	ACC MGMT
FORMAT UNIT		v		v				
ORWRITE (16)		v						
PRE-FETCH (10)	v							
PRE-FETCH (16)	v							
PREVENT ALLOW MEDIUM REMOVAL								v
READ (6)	v							
READ (10)	v							
READ (12)	v							
READ (16)	v							
READ (32)	v							
READ CAPACITY (10)			v					
READ CAPACITY (16)			v					
READ DEFECT DATA (10)			v					
READ DEFECT DATA (12)			v					
READ LONG (10)	v							
READ LONG (16)	v							
REASSIGN BLOCKS								
START STOP UNIT								v
SYNCHRONIZE CACHE (10)		v						
SYNCHRONIZE CACHE (16)		v						
VERIFY (10)	v							
VERIFY (12)	v							
VERIFY (16)	v							
VERIFY (32)	v							
WRITE (6)		v						
WRITE (10)		v						
WRITE (12)		v						
WRITE (16)		v						
WRITE (32)		v						
WRITE AND VERIFY (10)		v						
WRITE AND VERIFY (12)		v						
WRITE AND VERIFY (16)		v						
WRITE AND VERIFY (32)		v						
WRITE LONG (10)		v						
WRITE LONG (16)		v						
WRITE SAME (10)		v						
WRITE SAME (16)		v						

Requested command	Permissions						
WRITE SAME (32)		v					
XDREAD (10)	v						
XDREAD (32)	v						
XDWRITE (10)		v					
XDWRITE (32)		v					
XDWRITEREAD (10)	v	v					
XDWRITEREAD (32)	v	v					
XPWRITE (10)		v					
XPWRITE (32)		v					

For each cell in marked with 'v', the secure CDB processor shall process the requested command only if the corresponding bit is set in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor

11 The PERMISSION BIT MASK descriptor field in CbCS Capability

The CbCS capability format is defined in SPC-4. The PERMISSIONS BIT MASK descriptor (see Table 25) specifies the permissions allowed by this CbCS capability. More than one permissions bit may be set. The secure CDB processor shall verify that the bits applicable to the encapsulated command are all set to one in the PERMISSIONS BIT MASK descriptor before performing the encapsulated SCSI command.

The association of permissions to commands is defined in 10 for commands defined in this standard. Associations for other commands are defined in the specific command standards.

In Table 25 byte 0 and byte 1 specify the command functions for all SCSI commands (see SPC-4). In Table 25 byte 2 and byte 3 are used by this command standard to specify permissions. Other command set standards shall not override the definition of Table 25 byte 0 and byte 1 as defined in this standard. The associations between the command functions specified in the permissions bit mask descriptor and SCSI commands defined in this standard are specified in 10.

Table 25 – PERMISSIONS BIT MASK descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	DATA READ	DATA WRITE	PARAM READ	PARAM WRITE	SEC MGMT	RESRV	MGMT	Reserved
1	Reserved							
2	ACC MGMT	Reserved						
3	Reserved							

An ACC MGMT bit set to zero indicates the encapsulated SCSI command has no access management permission. An ACC MGMT bit set to one indicates the encapsulated SCSI command has access management permission.

Changes to SSC-3

Legend for the text colors: New text in blue. ~~Removed text in red strikethrough.~~ Proposer's notes in green.

12 Association between commands and permission bits

Table 26 defines the permissions required in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor (see SPC-4) for each SCSI command defined in this standard.

Table 26 - Associations between commands and CbCS permissions

Requested command	Permissions				
	DATA READ	DATA WRITE	PARM READ	PARM WRITE	ACC MGMT
ERASE(6)		v			
ERASE(16)		v			
FORMAT MEDIUM		v		v	
LOAD/UNLOAD					v
LOCATE(10)	v	v			
LOCATE(16)	v	v			
PREVENT ALLOW MEDIUM REMOVAL					v
READ(6)	v				
READ(16)	v				
READ BLOCK LIMITS			v		
READ POSITION	v	v			
READ REVERSE(6)	v				
READ REVERSE(16)	v				
RECOVER BUFFERED DATA	v				
REPORT DENSITY SUPPORT			v		
REWIND	v	v			
SET CAPACITY				v	
SPACE(6)	v	v			
SPACE(16)	v	v			
VERIFY(6)	v				
VERIFY(16)	v				
WRITE(6)		v			
WRITE(16)		v			
WRITE FILEMARKS(6)		v			
WRITE FILEMARKS(16)		v			

For each cell in marked with 'v', the secure CDB processor shall process the requested command only if the corresponding bit is set in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor

13 The PERMISSION BIT MASK descriptor field in CbCS Capability

The CbCS capability format is defined in SPC-4. The PERMISSIONS BIT MASK descriptor (see Table 27) specifies the permissions allowed by this CbCS capability. More than one permissions bit may be set. The secure CDB processor shall verify that the bits applicable to the encapsulated command are all set to one in the PERMISSIONS BIT MASK descriptor before performing the encapsulated SCSI command.

The association of permissions to commands is defined in 12 for commands defined in this standard. Associations for other commands are defined in the specific command standards.

In Table 27 byte 0 and byte 1 specify the command functions for all SCSI commands (see SPC-4). In Table 27 byte 2 and byte 3 are used by this command standard to specify permissions. Other command set standards shall not override the definition of Table 27 byte 0 and byte 1 as defined in this standard. The associations between the command functions specified in the permissions bit mask descriptor and SCSI commands defined in this standard are specified in 12.

Table 27 - PERMISSIONS BIT MASK descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	DATA READ	DATA WRITE	PARM READ	PARM WRITE	SEC MGMT	RESRV	MGMT	Reserved
1	Reserved							
2	ACC MGMT	Reserved						
3	Reserved							

An ACC MGMT bit set to zero indicates the encapsulated SCSI command has no access management permission. An ACC MGMT bit set to one indicates the encapsulated SCSI command has access management permission.

Changes to SMC-3

Legend for the text colors: **New text in blue.** ~~Removed text in red strikethrough.~~ Proposer's notes in green.

14 Association between commands and permission bits

Table 28 defines the permissions required in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor (see SPC-4) for each SCSI command defined in this standard.

Table 28 - Associations between commands and CbCS permissions

Requested command	Permissions				
	DATA READ	DATA WRITE	ACC MGMT	ACC ROBOT	ACC MEDIUM
EXCHANGE MEDIUM					<u>v</u>
INITIALIZE ELEMENT STATUS				<u>v</u>	
INITIALIZE ELEMENT STATUS WITH RANGE				<u>v</u>	
MOVE MEDIUM					<u>v</u>
OPEN/CLOSE IMPORT/EXPORT ELEMENT			<u>v</u>		
POSITION TO ELEMENT					<u>v</u>
PREVENT ALLOW MEDIUM REMOVAL			<u>v</u>		
READ ELEMENT STATUS				<u>v</u>	
REPORT VOLUME TYPES SUPPORTED	<u>v</u>				
REQUEST DATA TRANSFER ELEMENT INQUIRY	<u>v</u>				
REQUEST VOLUME ELEMENT ADDRESS	<u>v</u>				
SEND VOLUME TAG		<u>v</u>			

For each cell in marked with 'v', the secure CDB processor shall process the requested command only if the corresponding bit is set in the PERMISSIONS BIT MASK field in the CAPABILITY descriptor of a CbCS extension descriptor

15 The PERMISSION BIT MASK descriptor field in CbCS Capability

The CbCS capability format is defined in SPC-4. The PERMISSIONS BIT MASK descriptor (see Table 29) specifies the permissions allowed by this CbCS capability. More than one permissions bit may be set. The secure CDB processor shall verify that the bits applicable to the encapsulated command are all set to one in the PERMISSIONS BIT MASK descriptor before performing the encapsulated SCSI command.

The association of permissions to commands is defined in 14 for commands defined in this standard. Associations for other commands are defined in the specific command standards.

In Table 29 byte 0 and byte 1 specify the command functions for all SCSI commands (see SPC-4). In Table 29 byte 2 and byte 3 are used by this command standard to specify permissions. Other command set standards shall not override the definition of Table 29 byte 0 and byte 1 as defined in this standard. The associations between the command functions specified in the permissions bit mask descriptor and SCSI commands defined in this standard are specified in 14.

Table 29 - PERMISSIONS BIT MASK descriptor

Bit	<u>7</u>	<u>6</u>	<u>5</u>	<u>4</u>	<u>3</u>	<u>2</u>	<u>1</u>	<u>0</u>
Byte								

Bit Byte	7	6	5	4	3	2	1	0
0	<u>DATA READ</u>	<u>DATA WRITE</u>	<u>PARM READ</u>	<u>PARM WRITE</u>	<u>SEC MGMT</u>	<u>RESRV</u>	<u>MGMT</u>	<u>Reserved</u>
1	<u>Reserved</u>							
2	<u>ACC MGMT</u>	<u>ACC ROBOT</u>	<u>ACC MEDIUM</u>	<u>Reserved</u>				
3	<u>Reserved</u>							

An ACC MGMT bit set to zero indicates the encapsulated SCSI command has no access management permission. An ACC MGMT bit set to one indicates the encapsulated SCSI command has access management permission.

An ACC ROBOT bit set to zero indicates the encapsulated SCSI command has no permission to access the robot. An ACC ROBOT bit set to one indicates the encapsulated SCSI command has permission to access the robot.

An ACC MEDIUM bit set to zero indicates the encapsulated SCSI command has no permission to access the medium. An ACC MEDIUM bit set to one indicates the encapsulated SCSI command has permission to access the medium.

16 References

- [ObsSec05] Michael Factor, David Nagle, Dalit Naor, Erik Riedel, and Julian Satran. The OSD Security Protocol, September 2005. <http://ieeiea.org/sisw/2005/PreProceedings/04.pdf>
- [OSD04] R. O. Weber. SCSI Object-Based Storage Device Commands – 2 (OSD-2), Date: 2004/10/04, Rev: 00. InterNational Committee for Information Technology Standards (formerly NCITS), October 2004. <http://www.t10.org/drafts.htm>.
- [BCK96] M. Bellare, R. Canetti, and H. Krawczyk. Message authentication using hash functions: The hmac construction. RSA Laboratories' Crypto-Bytes, 2(1), Spring 1996.
- [FIPS180-02] Federal Information Processing Standards Publication 180-2: SECURE HASH STANDARD.
Date: August 1, 2002.
<http://csrc.nist.gov/publications/fips/fips180-2/fips180-2.pdf>
- [FIPS198-02] Federal Information Processing Standards Publication 198: The Keyed-Hash Message Authentication Code (HMAC).
Date: March 6, 2002.
<http://csrc.nist.gov/publications/fips/fips198/fips-198a.pdf>
- [HKN05] Shai Halevi, Paul A. Karger and Dalit Naor. Enforcing confinement in distributed storage and a cryptographic model for access control, 2005. Cryptology ePrint Archive: Report 2005/169.
- [ACF+02] Alain Azagury, Ran Canetti, Michael Factor, Shai Halevi, Ealan Henis, Dalit Naor, Noam Rinetzky, Ohad Rodeh, and Julian Satran. A two layered approach for securing an object store network. In Proceedings of the First International IEEE Security in Storage Workshop, pages 10–23, Greenbelt, MD, 11 December 2002.