

memorandum



Hewlett-Packard Company  
3000 Hanover Street  
Palo Alto, CA 94304-1185  
USA  
www.hp.com

T10/08-066r1

To INCITS T10 Committee  
From Curtis Ballard, HP  
Michael Banther, HP  
Subject Report Element Information

Date  
13 January, 2008

**Revision History [for original document number 06-272](#)**

Revision 0 – Initial document, split off from 06-046r1

Revision 1 – Changes from September 2006 T10  
Changed to 16 Byte CDB to reuse number of elements concept from RES and removed “SINGLE” bit  
Updated to SMC3r04  
Completed element characteristics page  
Added element state page

Revision 2 – Moved Page Code field in CDB  
Corrected Opcode in CDB table and command table  
Removed complete descriptors requirement and added note about difference from RES  
Added requirement that element address be ignored if the supported pages list is requested  
Renamed Element Characteristics page to Element Static Information page  
Added requirement for supported pages order in return data  
Added length fields to pages with fixed length descriptors  
Removed “Offline” concept and all bits – disabled with UA’s will be used instead  
Added Import and Operator Intervention bits to element state  
Change Exception Cause field to ASC/ASCQ as in RES  
Added support column to page code list

Revision 3 – Changes requested in Feb. 2007 T10 meeting  
Moved “see SPC-3” for allocation and control field to the correct location.  
Changed ELEMENT TYPE CODE field to reference 6.10.1 directly  
Moved truncated descriptors not an error statement to normative text in allocation length description  
Wording corrections on supported element information pages description  
Moved location of single supported pages descriptor for each element type requirement  
Changed return data to allow grouping of elements by starting address and number of elements  
Changed location length descriptor to 4 bytes and location parameter length to 4 bytes  
Removed list of proposed location types  
Corrected location of PARAMETERS LENGTH in element location descriptor.  
Changed supported volume types list to supported volume types parameters  
Added ability to report a supported volume type as read only when in the described data transfer element  
Added a volume index to the state information.

Revision 4 – Changed background to better describe this as part of a two command replacement for RES  
Simplified the header to conform to working group standards of no company logo on pages 2+  
Added text to clarify element can be disabled bit  
Added text to clarify removed bit  
Added CURDATA bit to CDB

Revision 5 – Several wording changes from June 2007 conference call  
Rewrote paragraph on setting volume types and qualifiers in supported volume types list  
Changed read only setting on volumes in drives to reference write OK bit in drive report density codes page  
Added text to each descriptor that may contain variable information to specify behavior when CURDATA=1

Revision 6 – Changes from July 2007 T10 meeting  
Revised definitions for Discovery and Inventory Scan  
Added UPG bit to CDB to allow optional selection of elements available with an upgrade  
Changed definition of write capable to not tie directly to tape WRTOK bit  
Split expansion concept in static descriptor to add-on and COD types of expansion  
Replaced virtual bit with can not be exported bit in static descriptor

Revision 7 – Changes from September 2007 T10 meeting  
Changed CONTROL byte reference  
Changed element state descriptor to only be able to return a single element instead of a range  
Changed all pages to be able to wait or return OPERATION IN PROGRESS when CURTDATA = 0  
Removed “can not be exported” bit – use volume type/qualifier to create type incompatible with I/O instead  
Several minor clarifications and corrections

## [Revision History for new document number 08-066](#)

[Revision 0 – Identical to 06-272r7 new number automatically assigned](#)

[Revision 1 – Changes from January, 2008 working group meeting Santa Ana, CA](#)

## Related Documents

smc3r04 – SCSI Media Changer Commands - 3 revision 04

spc3r23 – SCSI Primary Commands -3 revision 23

## Background

The Read Element Status command is used by applications to describe which elements of a media changer device are full and empty. Some information about the element compatibility has been added to the Read Element Status command in SMC and other information is provided using various vendor unique methods. Some of the characteristics that are currently reported in vendor unique methods are medium type, and element location which are frequently returned in a vendor specific section at the end of the Read Element Status data. Much of the information currently returned in Read Element Status is static information that does not change and does not need read every time the full/empty status needs refreshed. There are also several element characteristics that are not currently returned in Read Element Status. Further expansion of Read Element Status to include more static information would add complexity to an already complex command and increase the already large return data.

This document proposes the first half of a change to SMC-3 that creates two new media changer commands, “REPORT ELEMENT INFORMATION” and “REPORT VOLUME INFORMATION” which will provide an alternate method to retrieve all of the information currently returned by “READ ELEMENT STATUS”. These new commands will provide a mechanism that allows for easier extension in the future and allows selective or all inclusive retrieval of the data. Following the standardization of these commands “READ ELEMENT STATUS” may be deprecated.

The “REPORT ELEMENT INFORMATION” command specified in this proposal reports data pages containing information about a medium changer element. One page describes the dynamic information about the elements and all describe semi-static information that will not change without a device configuration change. Using the page code mechanism to select information pages about an element allows an application client to select only the information it needs at the time and to get back only that information rather than the monolithic data block used by Read Element Status. By using this command an application client can determine the type and capabilities of an element including volume types that are compatible with this element and the location of this element.

The Read Element Status mechanism for specifying a starting element address and number of elements is leveraged for this command as well as the element type filter to allow requesting information on a single element or range of elements of a specific type or all elements of all types.

The proposed command is intended to be the first of a set of commands to fully describe the elements and the media in the elements. A companion to this command for reporting information about the volume in the element will return the volume tag and other volume characteristics currently reported with the element information in Read Element Status.

In the proposed changes that follow, new text appears in blue or purple, deleted text appears in red strikeout, and editorial comments appear in green.

## Proposed Changes to SMC-3

Changes to 3.1:

**3.1.x Discovery:** An action performed by a media changer where values describing the elements in the media changer are determined. The values are determined by vendor specific methods (e.g., loaded from memory or detected by transport movement). Discovery may be performed at startup or following any event which may change the physical characteristics of the media changer.

**3.1.x Inventory Scan:** An action performed by a media changer where the inventory of volumes and the element address at which they may be found is determined. The inventory is determined by vendor specific methods (e.g., transport movement or optical scanning). An inventory scan may occur at startup or following a change that may effect the inventory of the media changer. An inventory scan may scan all elements in the media changer or may scan only elements that may have changed.

Changes to table 3 – Volume Type Codes:

Table 3 has the following changes:

**Table 3 – Volume type codes**

Code	Description
00h	<del>Reserved</del> All Types
01h – 7Fh	Vendor-specific
80h – <del>FFh</del> FEh	Reserved
FFh	Unknown

If the volume type is set to All Types or Unknown, then the volume qualifier shall be set to All Qualifiers.

Changes to 6.1:

Table 5 has the following addition (the entire table is not reproduced here):

Command	Operation Code	Type	Reference
REPORT ELEMENT INFORMATION	9Eh/10h <sup>a</sup>	○	6.x

Changes to 6.2:

Table 6 has the following addition (the entire table is not reproduced here):

REPORT ELEMENT INFORMATION	Allowed	Allowed	Allowed	Allowed	Allowed	Allowed
----------------------------	---------	---------	---------	---------	---------	---------

New sub-clause 6.x:

(Note: existing sub-clauses 6.x and above shift to become 6.x+1 and above with the addition of this new sub-clause)

### 6.x REPORT ELEMENT INFORMATION command

#### 6.x.1 REPORT ELEMENT INFORMATION command introduction

The REPORT ELEMENT INFORMATION command (see table y) requests information pages that describe an element or a set of elements.

**Table y – REPORT ELEMENT INFORMATION command**

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (10h)				
2	PAGE CODE							
3	Reserved		UPG	CURDATA	ELEMENT TYPE CODE			
4	(MSB)	STARTING ELEMENT ADDRESS						(LSB)
5								
6	(MSB)	NUMBER OF ELEMENTS						(LSB)
7								
8	Reserved							
9	Reserved							
10	(MSB)							(LSB)
11								
12	ALLOCATION LENGTH							
13							(LSB)	
14	Reserved							
15	CONTROL							

See SPC-3 for the definition of the OPERATION CODE field and the SERVICE ACTION field. The OPERATION CODE and SERVICE ACTION fields shall be set to the values shown in table y.

The PAGE CODE field specifies the element information page requested (see table y+1) by the application client. If the device server detects a PAGE CODE field set to an unsupported value, then it shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

If the upgrade (UPG) bit is set to one, then the device server may use the EXP bit and the COD bit in the element static information page to return information for elements that are not currently accessible but may be purchased or licensed.

If the current data (CURDATA) bit is set to one, then the device server shall return the requested element information page without causing device motion (e.g., using cached discovery and inventory information). If the CURDATA bit is set to zero, then the device server may cause device motion to validate the element information (e.g., perform an inventory scan or other actions). Support for the CURDATA bit set to one is mandatory.

**Comment:** The intent is that the return data be sent back without delays if CURDATA =1 and be verified before returning if CURDATA=0.

See 6.10.1 for the definition of the ELEMENT TYPE CODE field

The STARTING ELEMENT ADDRESS field specifies the lowest element address to report. Only elements with an element type code selected by the ELEMENT TYPE CODE field, and an element address greater than or equal to the value specified in the STARTING ELEMENT ADDRESS field shall be reported. The device server shall not report element information descriptors for undefined element addresses. If the PAGE CODE field is set to 00h (i.e., Supported Element Information Pages), then the STARTING ELEMENT ADDRESS field shall be ignored.

The NUMBER OF ELEMENTS field specifies the maximum number of elements to be reported. The value specified by this field is not the range of element addresses to be considered for reporting but rather the number of defined elements to report. If the PAGE CODE field is set to 00h (i.e., Supported Element Information Pages), then the NUMBER OF ELEMENTS field shall be ignored.

See SPC-3 for the definition of the ALLOCATION LENGTH field. If the descriptors are truncated because of the allocation length this shall not be considered an error.

See SAM-3 for a description of the CONTROL byte.

**Table y + 1: Element Information Page Codes**

PAGE CODE	Definition	Reference	Support
00h	Supported Element Information Pages	6.x.2	Mandatory
01h	Supported Volume Types	6.x.3	Optional
02h	Element Location	6.x.4	Optional
03h	Element Static Information	6.x.5	Optional
04h	Element State	6.x.6	Mandatory
05h-7Eh	Reserved		
7Fh	Return All Supported Pages	6.x.7	Optional
80h-FFh	Vendor Specific		

**6.x.2 Supported Element Information Pages**

The Supported Element Information Pages information page (see table y + 2) returns the list of element information pages supported by the device server for the element type specified in the report element information command. If all element types are specified, then the device server shall return one supported pages descriptor for each element type.

**Table y + 2: Supported Element Information Pages**

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE (00h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (n-3)							
3	(LSB)								
Supported pages descriptors									
4	First supported pages descriptor (see table y + 3)								
⋮									
n	Last supported pages descriptor (see table y + 3)								

The PAGE CODE field shall be set to the value shown in table y+2.

The value in the PAGE LENGTH field indicates the length in bytes of the supported pages descriptors that follow. If the descriptors are truncated because of the allocation length, the PAGE LENGTH field shall not be affected.

One supported pages descriptor shall be returned for each selected element type. Supported pages descriptors shall be returned in ascending order by element type code.

**Table y + 3: Supported Pages descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved				ELEMENT TYPE CODE			
1	Reserved							
2	(MSB)	DESCRIPTOR LENGTH (n-3)						(LSB)
3								
4	Supported element information page code list							
n								

The ELEMENT TYPE CODE field shall contain the element type code for the element type that supports the following list of pages.

The value in the DESCRIPTOR LENGTH field is the length in bytes of the data that follows. If the descriptor is truncated because of the allocation length, the DESCRIPTOR LENGTH field shall not be affected.

The supported element information page code list contains a list of element information page codes (see table y + 1) implemented by the logical unit for the specified element type code in ascending order beginning with page code 00h.

**6.x.3 Supported Volume Types**

Table y + 4 shows the format of the Supported Volumes information page.

**Table y + 4: Supported Volume Types page**

Bit Byte	7	6	5	4	3	2	1	0
0	PAGE CODE (01h)							
1	Reserved							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Supported volume types descriptors								
4	First supported volume types descriptor (see table y + 5)							
⋮								
n	Last supported volume types descriptor (see table y + 5)							

The PAGE CODE field shall be set to the value shown in table y + 4.

The value in the PAGE LENGTH field is the length in bytes of the supported volume types descriptors that follow. If the descriptors are truncated because of the allocation length, the PAGE LENGTH field shall not be affected.

**Table y + 5: Supported Volume Types descriptor**

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB) FIRST ELEMENT ADDRESS REPORTED								
1								(LSB)	
2	(MSB) NUMBER OF ELEMENTS								
3								(LSB)	
4	Reserved			ELEMENT TYPE CODE					
5	Reserved								
6	(MSB) PARAMETERS LENGTH (n-7)								
7								(LSB)	
Supported volume types parameters									
8	First supported volume type parameter (See table y + 6)								
11									
									⋮
n-1	Last supported volume type parameter (See table y + 6)								
n									

The FIRST ELEMENT ADDRESS REPORTED field indicates the lowest element address being reported.

The NUMBER OF ELEMENTS field indicates the number of contiguous elements with element addresses greater than or equal to the value specified in the STARTING ELEMENT ADDRESS field in the command, and with the same set of supported volume type parameters.

The ELEMENT TYPE CODE field shall contain the element type code for the element being described.

The PARAMETERS LENGTH field is the length in bytes of the parameter data to follow. If the data is truncated because of the allocation length, the PARAMETERS LENGTH field shall not be affected.

The supported volume types parameters indicate the volume types that may be moved to or from the specified element. Table y + 6 shows the supported volume type parameter format.

**Table y + 6: Supported Volume Type parameter**

Bit Byte	7	6	5	4	3	2	1	0
0	VOLUME TYPE							
1	VOLUME QUALIFIER							
2	Reserved					WRITE CAPABLE		
3	Reserved							

See 5.4 for the definition of the VOLUME TYPE field and the VOLUME QUALIFIER field.

If the device server is unable to determine the volume types supported by the specified element, then the VOLUME TYPE field shall be set to FFh (i.e., Unknown) and the VOLUME QUALIFIER field shall be set to 00h (i.e., All Qualifiers). If all volume types supported by the device may be moved to or from the element described, then the device server may set the VOLUME TYPE field to 00h (i.e., All Types) and the VOLUME QUALIFIER field to 00h (All Qualifiers). If all volume qualifiers for a volume type supported by the device may be moved to or from the element described, then the device server shall set VOLUME TYPE field to the value for the specified volume type and may set the VOLUME QUALIFIER field to 00h (All Qualifiers).

If the ELEMENT TYPE CODE field in the supported volume types descriptor is set to 4h (i.e., data transfer element), then the WRITE CAPABLE field specifies whether the selected data transfer element is capable of writing to a volume with the specified volume type and volume qualifier. (e.g., for SSC devices the data transfer device server reports a WRTOK bit set to one in a density

support data block descriptor for a volume with this volume type and volume qualifier in response to a REPORT DENSITY SUPPORT command, see SSC-3). The WRITE CAPABLE field values are defined in table y + 7.

**Table y + 7: WRITE CAPABLE field values**

WRITE CAPABLE	Description
00b	Unknown
01b	Data transfer device is capable of writing to this volume type.
10b	Data transfer device is not capable of writing to this volume type.
11b	Reserved

If the CURDATA bit in the REPORT VOLUME INFORMATION command is set to zero and a discovery is in progress or is required to update the volume support information, then the device server shall

- a) complete the discovery before returning any descriptors; or
- b) terminate the command with CHECK CONDITION status with the sense key set to NOT READY, and the additional sense code set to LOGICAL UNIT NOT READY, OPERATION IN PROGRESS.

If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to one, then the device server shall not perform a discovery to update the volume support information about any elements and shall use cached values for the VOLUME TYPE field, VOLUME QUALIFIER field, and WRITE CAPABLE field or shall set the VOLUME TYPE field, VOLUME QUALIFIER field, and WRITE CAPABLE field to Unknown. If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to one and discovery is incomplete, then the device server shall only return descriptors for elements that have been discovered.

Note: The device server only returns information for discovered elements if CURDATA is set to one. That list of elements may not be the complete list of elements.

**6.x.4 Element Location Page**

Table y + 8 shows the format of the Element Location page.

**Table y + 8: Element Location page**

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE (02h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (n-3)							
3								(LSB)	
	Element location descriptors								
4		First element location descriptor (see table y + 9)							
n		Last element location descriptor (see table y + 9)							

The PAGE CODE field shall be set to the value shown in table y + 8.

The value in the PAGE LENGTH field is the length in bytes of the element location descriptors that follow. If the descriptors are truncated because of the allocation length, the PAGE LENGTH field shall not be affected.



**Table y +9: Element Location descriptor**

Bit	7	6	5	4	3	2	1	0	
Byte									
0	(MSB)	FIRST ELEMENT ADDRESS REPORTED							
1									(LSB)
2	(MSB)	NUMBER OF ELEMENTS							
3									(LSB)
4	Reserved			ELEMENT TYPE CODE					
5	Reserved								
6	(MSB)	PARAMETERS LIST LENGTH (n -9)							
9									(LSB)
Location parameters									
10	First element location parameter (see table y + 10)								
	⋮								
n	Last element location parameter (see table y + 10)								

The FIRST ELEMENT ADDRESS REPORTED field indicates the lowest element address being reported.

The NUMBER OF ELEMENTS field indicates the number of contiguous elements with element addresses greater than or equal to the value specified in the STARTING ELEMENT ADDRESS field in the command and with the same set of location parameters.

The ELEMENT TYPE CODE field shall contain the element type code for the element being described.

The PARAMETERS LIST LENGTH field is the length in bytes of the data to follow. If the data is truncated because of the allocation length, the PARAMETERS LIST LENGTH field shall not be affected.

The LOCATION PARAMETERS COUNT field shall contain a count of the location parameters to follow.

The location parameters list contains a list of location parameters for the specified element.

Table y + 10 shows the element location parameter format.

**Table y + 10: Element location parameter**

Bit	7	6	5	4	3	2	1	0	
Byte									
0	(MSB)	ELEMENT LOCATION LENGTH (w-3)							
3									(LSB)
4	Reserved			CODE SET					
5	LOCATION TYPE CODE								
w bytes	LOCATION								

The ELEMENT LOCATION LENGTH field indicates the length in bytes of the element location data to follow.

The CODE SET field indicates the code set used for the LOCATION field in the element location descriptor. The CODE SET is described in table y + 11. This field is intended to be an aid to software that displays the LOCATION field.

**Table y + 11: CODE SET field**

Code	Description
0h	Reserved
1h	The LOCATION field shall contain binary values.
2h	The LOCATION field contains ASCII printable characters (i.e., code values 20h through 7Eh)
3h	The LOCATION field contains UTF-8 codes (see SPC-3)
4h-Eh	Reserved
Fh	The LOCATION field contains an ASCII representation of a decimal value (i.e., code values 30h through 39h, 2Dh through 2Eh)

The LOCATION TYPE CODE field indicates which type of location value the device server returns in the LOCATION field. Table y + 12 defines the location type codes.

**Table y + 12: LOCATION TYPE CODE values**

LOCATION TYPE CODE	Description
00h	Unknown
01h	Bin
02h	Cabinet
03h	Column
04h	Frame
05h	Mailslot
06h	Magazine
07h	Module
08h	Panel
09h	Row
0Ah	Tier
01-EFh	Reserved
F0h-FFh	Vendor specific

Note: A vendor specific location type code may be given a name and a value by reporting a name in the first descriptor with that location type code and ASCII or UTF-8 characters in the description field then reporting a value in the second descriptor with the same location type code.

The LOCATION field reports a vendor specified location value of the type specified in the LOCATION TYPE CODE field using the CODE SET specified in the Element Location Identifier header.

If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to zero and a discovery is in progress or is required to update the location information, then the device server shall

- c) complete the discovery before returning any descriptors; or
- d) terminate the command with CHECK CONDITION status with the sense key set to NOT READY, and the additional sense code set to LOGICAL UNIT NOT READY, OPERATION IN PROGRESS.

Comment: operation in progress seems like the best currently defined ASC/ASCQ. Could use SELF TEST IN PROGRESS, REBUILD IN PROGRESS, or RECALCULATION IN PROGRESS but those don't seem quite right.

If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to one, then the device server shall not perform a discovery to update the location information about any elements and shall return location descriptors using cached data. If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to one and discovery is incomplete, then the device server shall only return descriptors for elements that have been discovered.

T10/08-066r1

Hewlett-Packard Company  
3000 Hanover Street  
Palo Alto, CA 94304-1185  
USA  
[www.hp.com](http://www.hp.com)

Note: The device server only returns information for discovered elements if CURDATA is set to one. That list of elements may not be the complete list of elements.

**6.x.5 Element Static Information Page**

Table y + 13 shows the format of the Element Static Information page.

**Table y + 13: Element Static Information page**

Bit Byte	7	6	5	4	3	2	1	0
0	PAGE CODE (03h)							
1	Reserved							
2	(MSB)	DESCRIPTOR LENGTH						(LSB)
3								
4	Reserved							
5	Reserved							
6	(MSB)	PAGE LENGTH (n-7)						(LSB)
7								
Element static data descriptors								
4	First element static information descriptor (see table y + 14)							
	⋮							
n	Last element static information descriptor (see table y + 14)							

The PAGE CODE field shall be set to the value shown in table y + 13.

The value in the PAGE LENGTH field is the length in bytes of the element static data descriptors that follow. If the descriptors are truncated because of the allocation length, the PAGE LENGTH field shall not be affected.

The DESCRIPTOR LENGTH field shall contain the length of each element static information descriptor. The DESCRIPTOR LENGTH shall be a multiple of 4. The element static information descriptors shall be zero padded.

**Table y + 14: Element Static Information descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	FIRST ELEMENT ADDRESS REPORTED						(LSB)
1								
2	(MSB)	NUMBER OF ELEMENTS						(LSB)
3								
4	Reserved				ELEMENT TYPE CODE			
5	Reserved	EXP	COD	CNXP	MDO	IESTOR	EDC	
6	Reserved							
n	Reserved							

The FIRST ELEMENT ADDRESS REPORTED field indicates the lowest element address being reported.

The NUMBER OF ELEMENTS field indicates the number of contiguous elements with element addresses greater than or equal to the value specified in the STARTING ELEMENT ADDRESS field in the command and with the same ELEMENT TYPE CODE field, EXP bit, COD bit, CNXP bit, MDO bit, IESTOR bit, and EDC bit values.

The ELEMENT TYPE CODE field shall contain the element type code for the element being described.

An expansion (EXP) bit set to one indicates that the specified element is in an expansion module that is not present. An EXP bit set to zero indicates that the specified element is not in an expansion module that is not present. If the UPG bit in the CDB is set to zero, then the EXP bit shall be set to zero.

A capacity on demand (COD) bit set to one indicates that the specified element is an unlicensed capacity on demand element and may be made accessible by licensing. A COD bit set to zero indicates that the specified element is not an unlicensed capacity on demand element. If the UPG bit in the CDB is set to zero, then the COD bit shall be set to zero.

A moves during operation (MDO) bit set to one indicates that the physical position of the specified element is not fixed and the element moves during normal operation. A MDO bit set to zero indicates that the physical position of the specified element is fixed and the element does not move during normal operation. (e.g. the media changer moves a magazine as part of the process of opening an import/export element and all elements in that magazine have the MDO bit set to one).

An import/export or storage (IESTOR) bit set to one indicates that the specified element is configurable as either an import/export element or as a storage element. An IESTOR bit set to zero indicates that the specified element is not configurable as an import/export element or as a storage element. If the IESTOR bit is set to one, then the EDC bit shall be set to one.

An element disabled capable (EDC) bit set to one indicates that the specified element is capable of being disabled. An EDC bit set to zero indicates that the specified element is not capable of being disabled.

If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to zero and a discovery is in progress or is required to update the element static information, then the device server shall

- a) complete the discovery before returning any descriptors; or
- b) terminate the command with CHECK CONDITION status with the sense key set to NOT READY, and the additional sense code set to LOGICAL UNIT NOT READY, OPERATION IN PROGRESS.

If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to one, then the device server shall not perform a discovery to update the static information, and shall return element static descriptors using cached values. If the CURDATA bit in the REPORT VOLUME INFORMATION CDB is set to one and discovery is incomplete, then the device server shall only return descriptors for elements that have been discovered.

Note: The device server only returns information for discovered elements if CURDATA is set to one. That list of elements may not be the complete list of elements.

Comment: this page currently does not allow returning information on import export element reporting whether they are import only or export only but that functionality is in RES. Do we need that?

**6.x.6 Element State**

Table y + 15 shows the format of the Element State page.

**Table y + 15: Element State page**

Bit Byte	7	6	5	4	3	2	1	0
0	PAGE CODE (04h)							
1	Reserved							
2	(MSB)	DESCRIPTOR LENGTH						(LSB)
3								
4	Reserved							
5	Reserved							
6	(MSB)	PAGE LENGTH (n-7)						(LSB)
7								
Element state descriptors								
8	First element state descriptor (see table y + 16)							
⋮								
n	Last element state descriptor (see table y + 16)							

The PAGE CODE field shall be set to the value shown in table y + 15.

The value in the PAGE LENGTH field is the length in bytes of the element state descriptors that follow. If the descriptors are truncated because of the allocation length, the PAGE LENGTH field shall not be affected.

The DESCRIPTOR LENGTH field shall contain the length of each element state descriptor. The DESCRIPTOR LENGTH shall be a multiple of 4. The element state descriptors shall be zero padded.

**Table y + 16: Element State descriptor**

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	ELEMENT ADDRESS						(LSB)
1								
2	Reserved							
3								
4	Reserved				ELEMENT TYPE CODE			
5	Reserved	INVALID	IMP	OIR	FULL	ED	EXCPT	ACCESS
6	ADDITIONAL SENSE CODE							
7	ADDITIONAL SENSE CODE QUALIFIER							
8	(MSB)	VOLUME INDEX						(LSB)
9								
10	Reserved							
n								

The ELEMENT ADDRESS field indicates the element address being reported.

The ELEMENT TYPE CODE field shall contain the element type code for the element being described.

An index valid (IVALID) bit set to one indicates that the volume index field is valid. An IVALID bit set to zero indicates that the volume index field is not valid.

An IMP bit set to one indicates that the medium in this element was not present during the previous scan and was not moved to this element by the medium changer (e.g. a user bulk load or medium inserted into import/export element). An IMP bit set to zero indicates that the medium in this element was present during the previous scan, was moved to this element by the medium changer, or the previous scan results are not known.

Comment: Do we want the IMP bit to be zero if there is no previous scan results or should it be 1. If there are no previous scan results the library won't know if the volume has been imported so it could be zero, but if it is the trigger for an ISV to perform a scan of that volume, then the safer path would be to mark it as imported when unknown.

An operator intervention required (OIR) bit set to one indicates that operator intervention is required to make the element accessible (e.g. a mailslot or access panel must be closed). An OIR bit set to zero indicates that operator intervention is not required. If the OIR bit is set to one, then the ED bit shall be set to one and the ACCESS bit shall be set to zero.

A FULL bit set to one indicates that the specified element contains a volume. A FULL bit set to zero indicates that the specified element does not contain a volume.

An element disabled (ED) bit set to one indicates that the specified element is disabled. An ED bit set to zero indicates that the specified element is not disabled. Support of the ED bit set to one is required. If the ED bit is set to one, then the ACCESS bit shall be set to zero. If the ED bit is set to one, then the ECBDBIT in the static data descriptor for this element shall be set to one.

An exception (EXCPT) bit set to one indicates that an exception has occurred at the specified element. An EXCPT bit set to zero indicates that no exception has occurred at the specified element or any previous exception has been cleared. If the EXCPT bit is set to one, then the ACCESS bit shall be set to one if the element is still accessible and shall be set to zero if the element is not accessible. If the EXCPT bit is set to one, then the additional sense code and additional sense code qualifier fields shall contain additional information about the exception.

Comment: At the last review there was a request to modify the above paragraph and remove the statement about the ACCESS bit shall be set to one or zero and replace it with a statement that the ACCESS bit shall be supported if this bit is supported. Stating that ACCESS shall be supported isn't necessary because that bit is mandatory. Having that clause is intended to make it clear that an element may have an exception and still be accessible so the bit does not cause ISV's to make the volume in the element as bad. The exception may be something like a damaged barcode which shouldn't cause the ISV to quit using the volume but should be addressed by the operator.

An accessible (ACCESS) bit set to one indicates that access to the specified element by a medium transport element is allowed. An ACCESS bit set to zero indicates that access to the specified element by a medium transport element is not allowed. Support for the ACCESS bit set to one is mandatory.

The ADDITIONAL SENSE CODE field may provide additional information about the specified element. The values in this field are as defined for the ADDITIONAL SENSE CODE field of REQUEST SENSE command response data (see SPC-3). This field shall be set to 00h if there is no additional sense information available.

The ADDITIONAL SENSE CODE QUALIFIER field may provide more detailed additional information about the specified element. The values in this field are as defined for the ADDITIONAL SENSE CODE QUALIFIER field of REQUEST SENSE command response data (see SPC-3). This field shall be set to 00h if there is no additional sense code qualifier information available.

If the specified element contains a volume and the IVALID bit is set to one, then the VOLUME INDEX field shall contain a device server assigned index value which may be used with the REPORT VOLUME INFORMATION command to retrieve information about the volume in the specified element. The device server shall report the same volume index value for the volume in the specified element when that volume is in any element. If the IVALID bit is zero, then the VOLUME INDEX field shall be ignored. If an event occurs which causes the volume index values to change (e.g. the device is reset and volume index values are not retained across a reset), then the device server shall establish a unit attention (see SAM-4) condition for every L\_T nexus with the additional sense code set to VOLUME INDEX VALUES CHANGED.

If the CURDATA bit in the REPORT ELEMENT INFORMATION command is set to zero, and a discovery or inventory scan is in progress or is required to update the element state information, then the device server shall

- a) complete the discovery before returning any descriptors; or
- b) terminate the command with CHECK CONDITION status with the sense key set to NOT READY, and the additional sense code set to LOGICAL UNIT NOT READY, OPERATION IN PROGRESS.

If the CURDATA bit in the REPORT ELEMENT INFORMATION command is set to one and a discovery is in progress or is required to update the element state information, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to NOT READY, and the additional sense code set as described in SPC-3.

If the CURDATA bit in the REPORT ELEMENT INFORMATION command is set to one and an inventory scan is in progress or is required to update the element state information, then the device server shall

- a) set the EXCPT to one;
- b) set the ADDITIONAL SENSE CODE field and ADDITIONAL SENSE CODE QUALIFIER field to LOGICAL UNIT IS IN PROCESS OF BECOMING READY; and
- c) set the INVALID bit, IMP bit, FULL bit, ED bit, RMVD bit, and ACCESS bit to the last cached values or to zero.

Note: The device server is required to complete discovery before returning descriptors with CURDATA set to one and the list of elements is always the complete list of elements.

Comment: An additional sense code value for VOLUME INDEX VALUES CHANGED does not yet exist.

Comment: The above paragraph refers to the REPORT VOLUME INFORMATION command for the definition of the volume index value but that command does not yet exist. A follow on proposal will introduce that command.

Comment:

The following characteristics can or previously could be reported in READ ELEMENT STATUS but are not represented here.

- Primary Voltag – media information
- Secondary Voltag – media information
- Source Valid – media information
- Source Address – media information
- Invert – media information
- Medium Type – media information
- VPD Identifier – could be here but covered by “REPORT DTD ELEMENT INQUIRY”
- Import Enable – believed obsolete
- Export Enable – believed obsolete
- On Bus – Could be good information but needs different format from SCSI-2 RES command
- Address – Similar to on bus – would need updated format

### 6.x.7 Return All Supported Pages

If the Return All Supported Pages information page code is requested, then the device server shall return all of the pages supported by the elements selected by the STARTING ELEMENT ADDRESS field in the command and the ELEMENT TYPE CODE field in the command in ascending order by page code (i.e. all page code 01h pages shall be returned before any page code 02h pages).