

**From:** Gerry Houlder, Seagate Technology <gerry.houlder@seagate.com>  
**Subj:** SPC-4 SBC-3 Adding more low power options  
**Date:** June 16, 2008

---

## Overview

The existing Power Condition Mode Page Allows for two low power modes (idle and standby). This proposal increases the number of low power modes to four (adds idle2 and idle3) and adds a recovery time parameter for each of the low power modes.

Elements included in this proposal are:

- a) additions to the Power Condition mode page to add two more idle modes and add a recovery time parameter for each power mode;
- b) changes to START STOP command wording to clarify how to immediately enter the new idle power modes;
- c) addition to the power condition model to allow REQUEST SENSE to return new ASC values for the new idle modes;
- d) define 4 new ASC values; and
- e) add new log parameters to count transitions to low power modes.

Rev. 1: Added details of power condition model changes for SBC and SPC; split the power condition transition log parameters into a new log page; combined two tables into one to clarify START STOP UNIT command behavior; added new options to START STOP UNIT; and editorial changes in various other places.

## SPC-4 changes:

[Note: Some folks may think updates are needed to the power condition model (clause 5.9) to add two more power conditions. My preference is just to handle IDLE2 and IDLE3 as lower power modes of IDLE and not create separate states for them. This means we don't have to change the power condition model except for a few editorial nits.]

### 7.4.12 Power Condition mode page

The Power Condition mode page provides an application client with methods to control the power condition of a logical unit (see 5.9). These methods include:

- a) Specifying that the logical unit transition to a power condition without delay; and
- b) **Activating enabling** and **setting initializing any** of ~~idle condition and standby~~ the power condition timers to specify that the logical unit wait for a period of inactivity before transitioning to a specified power condition.

The mode page policy (see 6.9) for this mode page shall be shared.

When a device server receives a command while in a power condition based on a setting in the Power Condition mode page, the logical unit ~~shall~~ **should** transition to the power condition that allows the command to be processed. **Protocol standards (e.g., SAS) may impose additional requirements before allowing a power condition transition to a higher power condition.** If ~~either the idle condition timer or the standby~~ **any** power condition timer ~~has been set~~ **is enabled**, then they shall be ~~reset~~ **stopped** on receipt of the command. On completion of the command, ~~the any enabled timer(s)~~ shall be **initialized and** started.

The power conditions should be ordered from least power savings (i.e., shortest recovery time) to most power savings (i.e., longest recovery time) as follows: active >= idle >= idle2 >= idle3 > standby >= stopped.

[Note: Should the power condition order be stated as an equation or as an ordered list?]

Logical units that contain cache memory shall write all cached data to the medium for the logical unit (e.g., as a logical unit does in response to a SYNCHRONIZE CACHE command as described in SBC-2) prior to entering into any power condition that prevents accessing the media (e.g., before a hard drive stops its spindle motor during transition to the standby power condition).

The logical unit shall use the values in the Power Condition mode page to control its power condition after a power on or a hard reset until a START STOP UNIT command setting a power condition is received.

Table 319 defines the Power Condition mode page.

**Table 319 -- Power Condition Mode Page**

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF(0b)	Page Code (1Ah)					
1	Page Length							
2	Reserved							
3	Reserved				IDLE3	IDLE2	IDLE	STANDBY
4	IDLE CONDITION TIMER							
5								
6								
7								
8	STANDBY CONDITION TIMER							
9								
10								
11								
12	IDLE2 CONDITION TIMER							
13								
14								
15								
16	IDLE3 CONDITION TIMER							
17								
18								
19								
20	RESERVED							
21								
22								
23								
24	IDLE CONDITION RECOVERY TIME							
25	STANDBY CONDITION RECOVERY TIME							
26								
27	IDLE2 CONDITION RECOVERY TIME							
28								
29	IDLE3 CONDITION RECOVERY TIME							
30								
31	RESERVED							
32								
40								

The PS bit, SPF bit, PAGE CODE field, and PAGE LENGTH field are described in 7.4.5.

The IDLE, IDLE2, IDLE3, and STANDBY bits specify which timers are **active enabled**.

If the IDLE bit is set to one ~~and the STANDBY bit is set to zero~~, then the idle condition timer is **active enabled** and the device server shall transition to the idle power condition when **the time specified by the IDLE CONDITION TIMER ~~is-zero~~ field has expired and the logical unit is in a power condition higher than idle.**

If the IDLE bit is set to zero, then the device server shall ignore the idle condition timer.

If the STANDBY bit is set to one ~~and the IDLE bit is set to zero~~, then the standby condition timer is **active enabled** and the device server shall transition to the standby power condition when **the time specified by the STANDBY CONDITION TIMER ~~is-zero~~ field has expired and the logical unit is in a power condition higher than standby.**

If the STANDBY bit is set to zero, then the device server shall ignore the standby condition timer.

If the IDLE2 bit is set to one then the idle2 condition timer is enabled and the device server shall transition to the idle2 power condition when the time specified by the IDLE2 CONDITION TIMER field has expired and the logical unit is in a power condition higher than idle2.

If the IDLE2 bit is set to zero, then the device server shall ignore the idle2 condition timer.

If the IDLE3 bit is set to one then the idle3 condition timer is enabled and the device server shall transition to the idle3 power condition when the time specified by the IDLE3 CONDITION TIMER field has expired and the logical unit is in a power condition higher than idle3.

If the IDLE3 bit is set to zero, then the device server shall ignore the idle3 condition timer.

If ~~both~~ more than one of the IDLE, IDLE2, IDLE3, and STANDBY bits are set to one, then ~~both~~ all of the enabled timers are active and run concurrently. When each timer expires, the device server should transition to the power condition associated with that timer. Timer expirations shall only cause the device server to transition from higher power conditions to lower power conditions (e.g., if the standby timer expires before the idle2 timer, the device server shall remain in the standby condition when the idle2 timer expires). ~~the idle condition timer is zero the device server shall transition to the idle power condition. When the standby condition timer is zero the device server shall transition to the standby power condition. If the standby condition timer is zero before the idle condition timer is zero, then the logical unit shall transition to the standby power condition.~~

The value in the IDLE CONDITION TIMER field specifies the inactivity time in 100 millisecond increments that the logical unit shall wait before transitioning to the idle power condition when the IDLE bit is set to one. The idle condition timer is expired when:

- a) The IDLE CONDITION TIMER field is set to zero; or
- b) The ~~number of milliseconds~~ time specified by the value in the IDLE CONDITION TIMER field times 100 milliseconds has elapsed since the last activity (e.g., processing a command that requires the active power condition or performing a self test).

The value in the STANDBY CONDITION TIMER field specifies the inactivity time in 100 millisecond increments that the logical unit shall wait before transitioning to the standby power condition when the STANDBY bit is set to one. The standby condition timer is expired when:

- a) The STANDBY CONDITION TIMER field is set to zero; or

- b) The ~~number of milliseconds~~ time specified by the value in the STANDBY CONDITION TIMER field times 100 milliseconds has elapsed since the last activity (e.g., processing any command or performing a self test).

The value in the IDLE2 CONDITION TIMER field specifies the inactivity time in 100 millisecond increments that the logical unit shall wait before transitioning to the idle2 power condition when the IDLE2 bit is set to one. The idle2 condition timer is expired when:

- a) The IDLE2 CONDITION TIMER field is set to zero; or
- b) The time specified by the value in the IDLE2 CONDITION TIMER field times 100 milliseconds has elapsed since the last activity (e.g., processing a command that requires the active power condition or performing a self test).

The value in the IDLE3 CONDITION TIMER field specifies the inactivity time in 100 millisecond increments that the logical unit shall wait before transitioning to the idle3 power condition when the IDLE3 bit is set to one. The idle3 condition timer is expired when:

- a) The IDLE3 CONDITION TIMER field is set to zero; or
- b) The time specified by the value in the IDLE3 CONDITION TIMER field times 100 milliseconds has elapsed since the last activity (e.g., processing a command that requires the active power condition or performing a self test).

The IDLE CONDITION RECOVERY TIME field specifies the typical time in 100 millisecond increments that the logical unit takes to transition from the idle power condition to the active power condition. This time does not include processing time for the command that caused this transition to occur. A value of zero indicates that the recovery time is not specified.

The STANDBY CONDITION RECOVERY TIME field specifies the typical time in 100 millisecond increments that the logical unit takes to transition from the standby power condition to the active power condition. This time does not include processing time for the command that caused this transition to occur. A value of zero indicates that the recovery time is not specified.

The IDLE2 CONDITION RECOVERY TIME field specifies the typical time in 100 millisecond increments that the logical unit takes to transition from the idle2 power condition to the active power condition. This time does not include processing time for the command that caused this transition to occur. A value of zero indicates that the recovery time is not specified.

The IDLE3 CONDITION RECOVERY TIME field specifies the typical time in 100 millisecond increments that the logical unit takes to transition from the idle3 power condition to the active power condition. This time does not include processing time for the command that caused this transition to occur. A value of zero indicates that the recovery time is not specified.

### Sense code changes for Table 40 and Table D.1:

Sense	ASCQ	Description
2Ch	05h DT LPWRO A BK	ILLEGAL POWER CONDITION REQUEST
5Eh	00h DT LPWRO A BK	LOW POWER CONDITION ON
5Eh	01h DT LPWRO A K	IDLE CONDITION ACTIVATED BY TIMER
5Eh	02h DT LPWRO A K	STANDBY CONDITION ACTIVATED BY TIMER
5Eh	03h DT LPWRO A BK	IDLE CONDITION ACTIVATED BY COMMAND
5Eh	04h DT LPWRO A BK	STANDBY CONDITION ACTIVATED BY COMMAND
5Eh	05h DT LPWRO A K	IDLE2 CONDITION ACTIVATED BY TIMER
5Eh	06h DT LPWRO A K	IDLE2 CONDITION ACTIVATED BY COMMAND
5Eh	07h DT LPWRO A K	IDLE3 CONDITION ACTIVATED BY TIMER
5Eh	08h DT LPWRO A K	IDLE3 CONDITION ACTIVATED BY COMMAND

#### 7.2.11 Start-Stop Cycle Counter log page

This subclause defines the Start-Stop Cycle Counter log page (page code 0Eh). A device server that implements the Start-Stop Cycle Counter log page shall implement one or more of the defined parameters. Table 286 shows the Start-Stop Cycle Counter log page with all parameters present.

**Table 286 – Start-Stop Cycle Counter log page**

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF(0b)	PAGE CODE (0Eh)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (34h)						(LSB)
3								
4	(MSB)	PARAMETER CODE (0001h)						(LSB)
5	Date of Manufacture							
6	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
7	PARAMETER LENGTH (06h)							
8	(MSB)	YEAR OF MANUFACTURE (4 ASCII characters)						(LSB)
11								
12	(MSB)	WEEK OF MANUFACTURE (2 ASCII characters)						(LSB)
13								
14	(MSB)	PARAMETER CODE (0002h)						(LSB)
15	Accounting Date							
16	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
17	PARAMETER LENGTH (06h)							
18	(MSB)	ACCOUNTING DATE YEAR (4 ASCII characters)						(LSB)
21								
22	(MSB)	ACCOUNTING DATE WEEK (2 ASCII characters)						(LSB)
23								
24	(MSB)	PARAMETER CODE (0003h)						(LSB)
25	Specified cycle count over device lifetime							
26	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
27	PARAMETER LENGTH (04h)							
28	(MSB)	SPECIFIED CYCLE COUNT OVER DEVICE LIFETIME						(LSB)
31	(4 byte binary number)							
32	(MSB)	PARAMETER CODE (0004h)						(LSB)
33	Accumulated start-stop cycles							
34	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
35	PARAMETER LENGTH (04h)							
36	(MSB)	ACCUMULATED START-STOP CYCLES						(LSB)
39	(4 byte binary number)							
40	(MSB)	PARAMETER CODE (0005h)						(LSB)
41	Specified load-unload count over device lifetime							
42	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
43	PARAMETER LENGTH (04h)							
44	(MSB)	SPECIFIED LOAD-UNLOAD COUNT OVER DEVICE LIFETIME						(LSB)
47	(4 byte binary number)							
48	(MSB)	PARAMETER CODE (0006h)						(LSB)
49	Accumulated load-unload cycles							

50	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING
51	PARAMETER LENGTH (04h)					
52	(MSB)	ACCUMULATED LOAD-UNLOAD CYCLES				
55	(4 byte binary number)				(LSB)	

[Note: Text describing parameters 0001h and 0002h is unchanged and not repeated here.]

The parameter value in the specified cycle count over device lifetime ~~and specified load-unload count over device lifetime~~ log parameters (parameter codes 0003h and 0005h, respectively) shall contain a four-byte binary value that indicates how many stop-start and load-unload cycles may typically be performed over the lifetime of the SCSI target device without degrading the SCSI target device's operation or reliability outside the limits specified by the manufacturer of the SCSI target device. If a LOG SELECT command attempts to change the value of ~~the specified cycle count over device lifetime~~ these log parameters, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST. For the log parameters in which the parameter code value is 0003h or 0005h, the values of the parameter control bits are defined in table 289.

**Table 289 – Parameter control bits for parameters 0003h through 0006h**

Bit or field	Value	Description
DU	0b	Value provided by device server
TSD	0b	Device server manages saving of parameter
ETC	0b	No threshold comparison is made on this value
TMC	xx	Ignored <del>when because</del> the ETC bit is set to zero
FMT&LINKING	11b	The parameter is a binary format list parameter

~~The parameter value in the accumulated start-stop cycles log parameter (parameter code 0004h) shall contain a four-byte binary value that indicates how many stop-start cycles the SCSI target device has detected since its date of manufacture. The accumulated start-stop cycles counter is a saturating counter. If a LOG SELECT command attempts to change the value of the accumulated start-stop cycles log parameter, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST. The time at which the count is incremented during a start-stop cycle is vendor specific.~~

The parameter value in the accumulated start stop cycles and accumulated load unload cycles log parameters (parameter codes 0004h and 0006h, respectively) contain a four-byte binary value that indicates a number of cycles the SCSI target has detected since its date of manufacture. These counters are saturating counters. The count is incremented by one for each complete cycle. The time in the cycle at which the count is incremented is vendor specific. For these log parameters the values of the parameter control bits are defined in table 289. If a LOG SELECT command attempts to change the value of any of these log parameters, the command shall be terminated with CHECK CONDITION status, with sense key set to ILLEGAL REQUEST and additional sense code set to INVALID FIELD IN PARAMETER LIST.

For rotating magnetic storage devices supporting the accumulated start-stop cycles log parameter (parameter code 0004h), a single start-stop cycle is defined as an operational cycle that begins with the disk spindle at rest, continues while the disk accelerates to its normal operational rotational rate, continues during the entire period the disk is rotating, continues as the disk decelerates toward a resting state, and ends when the disk is no longer rotating. For devices without a spindle or with multiple spindles, the definition of a single start-stop cycle is vendor

specific. ~~The count is incremented by one for each complete start-stop cycle.~~ No comparison with the value of parameter 0003h shall be performed by the device server. ~~For the log parameter in which the parameter code value is 0004h, the values of the parameter control bits are defined in table 289.~~

For rotating magnetic storage devices supporting the accumulated load-unload cycles log parameter (parameter code 0006h), a single load-unload cycle is defined as an operational cycle that begins with the heads unloaded from the medium, continues while the heads are loaded onto the spinning medium, and ends when the heads are unloaded from the medium. For devices without unloadable heads, this parameter is not applicable. No comparison with the value of parameter 0005h shall be performed by the device server.

**7.2.x Power Transitions log page**

This subclause defines the Power Transitions log page (page code 1Ah). A device server that implements the Power Transitions log page shall implement one or more of the defined parameters. Table new1 shows the Power Transitions log page with all parameters present.

**Table new1 – Power Transitions log page**

Byte	Bit 7	6	5	4	3	2	1	0
0	DS	SPF(0b)	PAGE CODE (1Ah)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (20h)						(LSB)
3								
4	(MSB)	PARAMETER CODE (0001h)						(LSB)
5	Accumulated transitions to idle state (LSB)							
6	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
7	PARAMETER LENGTH (04h)							
8	(MSB)	ACCUMULATED TRANSITIONS TO IDLE STATE						(LSB)
11	(4 byte binary number)							
12	(MSB)	PARAMETER CODE (0002h)						(LSB)
13	Accumulated transitions to idle2 state (LSB)							
14	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
15	PARAMETER LENGTH (04h)							
16	(MSB)	ACCUMULATED TRANSITIONS TO IDLE2 STATE						(LSB)
19	(4 byte binary number)							
20	(MSB)	PARAMETER CODE (0003h)						(LSB)
21	Accumulated transitions to idle3 state (LSB)							
22	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
23	PARAMETER LENGTH (04h)							
24	(MSB)	ACCUMULATED TRANSITIONS TO IDLE3 STATE						(LSB)
27	(4 byte binary number)							
28	(MSB)	PARAMETER CODE (0008h)						(LSB)
29	Accumulated transitions to standby state (LSB)							
30	DU	Obsolete	TSD	ETC	TMC	FMT&LINKING		
31	PARAMETER LENGTH (04h)							
32	(MSB)	ACCUMULATED TRANSITIONS TO STANDBY STATE						(LSB)
35	(4 byte binary number)							

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 7.2.1.

The parameter value for parameter codes 0001h, 0002h, 0003h, and 0008h contain a four-byte binary value that indicates a number of cycles the SCSI target has detected since its date of manufacture. These counters are saturating counters. The count is incremented by one for each complete cycle. The time in the cycle at which the count is incremented is vendor specific. For these log parameters the values of the parameter control bits are defined in table new2. If a LOG SELECT command attempts to change the value of any of these log parameters, the command shall be terminated with CHECK CONDITION status, with sense key set to ILLEGAL REQUEST and additional sense code set to INVALID FIELD IN PARAMETER LIST.

**Table new2 – Parameter control bits for parameters 0001h, 0002h, 0003h, and 0008h**

Bit or field	Value	Description
DU	0b	Value provided by device server
TSD	0b	Device server manages saving of parameter
ETC	0b	No threshold comparison is made on this value
TMC	xx	Ignored because the ETC bit is set to zero
FMT&LINKING	11b	The parameter is a binary format list parameter

For SCSI target devices that support the accumulated transitions to idle state log parameter (parameter code 0001h), a single idle power transition count is defined as an operational cycle that begins in a power condition other than idle and transitions to idle power condition.

For SCSI target devices that support the accumulated transitions to idle2 state log parameter (parameter code 0002h), a single idle2 power transition count is defined as an operational cycle that begins in a power condition other than idle2 and transitions to idle2 power condition.

For SCSI target devices that support the accumulated transitions to idle3 state log parameter (parameter code 0003h), a single idle3 power transition count is defined as an operational cycle that begins in a power condition other than idle3 and transitions to idle3 power condition.

For SCSI target devices that support the accumulated transitions to standby state log parameter (parameter code 0008h), a single standby power transition count is defined as an operational cycle that begins in a power condition other than standby and transitions to standby power condition.

## 5.9 Power conditions

### 5.9.1 Power conditions overview

The optional Power Condition mode page (see 7.4.12) allows an application client to control the power condition of a logical unit in a manner that may reduce power consumption of the SCSI target device. This control is invoked by enabling and **setting initializing** the idle condition **timer timers** and/or the standby condition timer using the mode page. A change in the power condition of any logical unit in a SCSI target device may result in a change in the SCSI target device's power consumption. **If a SCSI target device contains multiple logical units, the SCSI target device's power consumption may not decrease until a group of the logical units have transitioned to a lower power condition. Any grouping of logical units for power condition management is vendor specific.**

In addition to the Power Condition mode page, the power condition of a logical unit may be controlled by the START STOP UNIT command (see SBC-3 or RBC). If both the Power Condition



mode page and the START STOP UNIT command methods are being used to control the power condition of the same logical unit, then any START STOP UNIT command's power condition specification shall override the Power Condition mode page's power control and may disable the idle condition and standby condition timers.

There shall be no notification to the application client that a logical unit has transitioned from one power condition to another. The REQUEST SENSE command (see 6.28) indicates if a logical unit is in the idle power condition or the standby power condition.

Command standards (see 3.1.18) may define for their peripheral device types additional power conditions (e.g., the stopped power condition defined by SBC-3 for direct-access block devices) and extensions to the REQUEST SENSE command for reporting power conditions.

Receipt of a command that requires a higher power level for processing should cause a transition to the higher power condition. Protocol standards may impose additional requirements (e.g., the NOTIFY (ENABLE SPINUP) primitive defined by SAS-2) before allowing a transition from a lower power condition to a higher power condition.

No power condition shall affect the supply of any power required for proper operation of a service delivery subsystem.

Logical units that contain cache memory shall write all cached data to the medium for the logical unit (e.g., as a logical unit would do in response to a SYNCHRONIZE CACHE command as described in SBC-2) prior to entering into any power condition that prevents accessing the media (e.g., before a hard drive stops its spindle motor during transition to the standby power condition).

The power conditions are described in table 51.

**Table 51 — Power Conditions**

Power Condition	Description
active	While in the active power condition (see 3.1.5): a) A device server is capable of responding to all of its supported commands including media access requests; b) A logical unit completes processing of operations in the shortest time when compared to the time required for completion while in the idle or standby power conditions; and c) The SCSI target device may consume more power than when the logical unit is in the idle power condition (e.g., a disk drive's spindle motor may be active).
idle	While in the idle power condition (see 3.1.54): a) A device server is capable of responding to all of its supported commands including media access requests; b) A logical unit may take longer to complete processing a command than it would while in the active power condition (e.g., the device may have to activate some circuitry before processing a command); <del>and</del> [Note: Should we add a rule requiring that transition from idle to active shall not exceed the maximum power limit of active power condition?] c) The power consumed by the SCSI target device should be less than or equal to the power consumed when the logical unit is in the active power condition and may be greater than the power consumed when the logical unit is in the standby power condition; and d) A device server may implement more than one idle power condition (e.g., idle, idle2, idle3) to provide progressively lower power consumption (i.e., power consumption for active >= idle >= idle2 >= idle3). All idle power conditions have the characteristics described for the idle power condition.

standby	While in the standby power condition (see 3.1.155): a) A device server is <del>not</del> capable of processing media access commands <b>but the device server may take longer to complete processing a command</b> ; and b) The power consumed by the SCSI target device should be less than or equal to the power consumed when the logical unit is in the idle power condition (e.g., a disk drive's spindle motor is stopped).
---------	---

### 6.28 REQUEST SENSE command

The REQUEST SENSE command (see table 226) requests that the device server transfer parameter data containing sense data to the application client.

[Tables and unchanged CDB description text are not shown here.]

Sense data shall be available and cleared under the conditions defined in SAM-4. If the device server has no sense data available to return, it shall:

- 1) Return parameter data containing sense data with the sense key set to NO SENSE and the additional sense code set to NO ADDITIONAL SENSE INFORMATION; and
- 2) Complete the REQUEST SENSE command with GOOD status.

If the logical unit is in the idle power condition (see 5.9), the device server shall process a REQUEST SENSE command by:

- 1) Returning parameter data containing sense data with the sense key set to NO SENSE and the additional sense code set to one of the following:
  - A) LOW POWER CONDITION ON if the reason for entry into the idle power condition is unknown;
  - B) IDLE CONDITION ACTIVATED BY TIMER if the logical unit entered the idle power condition due to the idle condition timer (see 7.4.12); ~~and~~
  - C) IDLE CONDITION ACTIVATED BY COMMAND if the logical unit entered the idle power condition due to receipt of a command requiring the idle power condition while it was in the **idle2, idle3, or** standby power condition;
  - D) **IDLE2 CONDITION ACTIVATED BY TIMER if the logical unit entered the idle2 power condition due to the idle2 condition timer (see SPC-4);**
  - E) **IDLE2 CONDITION ACTIVATED BY COMMAND if the logical unit entered the idle2 power condition due to receipt of a command requiring the idle2 power condition while it was in the idle3 or standby power condition;**
  - F) **IDLE3 CONDITION ACTIVATED BY TIMER if the logical unit entered the idle3 power condition due to the idle3 condition timer (see SPC-4); or**
  - G) **IDLE3 CONDITION ACTIVATED BY COMMAND if the logical unit entered the idle3 power condition due to receipt of a command requiring the idle3 power condition while it was in the standby power condition;**

and

- 2) Complete the REQUEST SENSE command with GOOD status.

If the logical unit is in the standby power condition, the device server shall process a REQUEST SENSE command by:

- 1) Return parameter data containing sense data with the sense key set to NO SENSE and the additional sense code set to one of the following:
  - A) LOW POWER CONDITION ON if the reason for entry into the standby power condition is unknown; ~~and or~~
  - B) **STANDBY CONDITION ACTIVATED BY TIMER if the logical unit entered the standby power condition due to the standby condition timer (see 7.4.12);**

and

2) Complete the REQUEST SENSE command with GOOD status.

Upon completion of the REQUEST SENSE command, the logical unit shall return to the same power condition that was active before the REQUEST SENSE command was received. A REQUEST SENSE command shall not reset any power condition timers.

The device server shall return CHECK CONDITION status for a REQUEST SENSE command only to report exception conditions specific to the REQUEST SENSE command itself. Examples of conditions that cause a REQUEST SENSE command to return a CHECK CONDITION status are:

[Remainder of clause 6.28 is unchanged.]

**SBC-3 changes:**

**5.19 START STOP UNIT command**

**Table 60 – START STOP UNIT command**

Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (1Bh)							
1	Reserved							IMMED
2	Reserved							
3	Reserved				POWER CONDITION MODIFIER			
4	POWER CONDITION				Resvd	N_FLUSH	LOEJ	START
5	CONTROL							

The OPERATION CODE field is defined in SPC-4 and shall be set to the value defined in table 60.

If the immediate (IMMED) bit is set to zero, then the device server shall return status after the operation is completed. If the IMMED bit set to one, then the device server shall return status as soon as the CDB has been validated.

~~The POWER CONDITION MODIFIER field defined in table 61 is used to specify additional information about the power condition specified in the POWER CONDITION field.~~

~~**Table 61 – power condition modifier field**~~

<del>power condition field value</del>	<del>Code</del>	<del>Description</del>
<del>All values that are not reserved</del>	<del>0h</del>	<del>Reserved Perform the power condition action specified by the power condition field.</del>
<del>02h (i.e., idle)</del>	<del>0h</del>	<del>Transition the logical unit into the idle power condition.</del>
	<del>1h</del>	<del>Specifies that the device server shall increase the tolerance of the direct access block device to external physical forces Transition the logical unit into the idle2 power condition (e.g., causes a device that has movable read/write heads to move those heads to a safe position).</del>

	2h	<del>Specifies that the device server shall increase the tolerance of the direct access block device to external physical forces (e.g., causes a device that has movable read/write heads to move those heads to a safe position) and should cause the device to use less power than when this field is set to 1h. Transition the logical unit into the idle3 power condition (e.g., cause a device that has rotating media to rotate the media at a lower RPM).</del>
All other combinations		Reserved

~~The power condition field is used to specify that the logical unit be placed into a power condition or to adjust a timer as defined in table 62. If this field is supported and is set to a value other than 0h, then the start and loej bits shall be ignored.~~

**Table 62—power condition field**

Code	Name	Description
0h	START_VALID	<del>Process the START and LOEJ bits.</del>
1h	ACTIVE	<del>Place Transition the device logical unit into the active power condition.</del>
2h	IDLE	<del>Place Transition the device logical unit into the idle power condition.</del>
3h	STANDBY	<del>Place Transition the device logical unit into the standby power condition.</del>
4h	Reserved	Reserved
5h	Obsolete	Obsolete
6h	Reserved	Reserved
7h	LU_CONTROL	<del>Transfer control of power conditions to the logical unit.</del>
8h—9h	Reserved	Reserved
Ah	FORCE_IDLE_0	<del>Force the idle condition timer to zero.</del>
Bh	FORCE_STANDBY_0	<del>Force the standby condition timer to zero.</del>
Ch—Fh	Reserved	Reserved

The POWER CONDITION field and POWER CONDITION MODIFIER field are used to specify that the logical unit be placed into a power condition as defined in table 61. If the POWER CONDITION field is supported and is set to a value other than 0h, then the START and LOEJ bits shall be ignored.

**Table 61 – POWER CONDITION and POWER CONDITION MODIFIER fields**

POWER CONDITION field value	POWER CONDITION MODIFIER value	Description
0h (START_VALID)	0h	Process the START and LOEJ bits.
1h (ACTIVE)	0h	<del>Place</del> Transition the <del>device</del> logical unit into the active power condition and disable device server control of power conditions.
02h (IDLE)	0h	Transition the logical unit into the idle power condition and disable device server control of power conditions.
	1h	<del>Specifies that the device server shall increase the tolerance of the direct access block device to external physical forces</del> Transition the logical unit into the idle2 power condition (e.g., cause a device that has movable read/write heads to move those heads to a safe position) and disable device server control of power conditions.
	2h	<del>Specifies that the device server shall increase the tolerance of the direct access block device to external physical forces (e.g., causes a device that has movable read/write heads to move those heads to a safe position) and should cause the device to use less power than when this field is set to 1h</del> Transition the logical unit into the idle3 power condition (e.g., cause a device that has rotating media to rotate the media at a lower RPM) and disable device server control of power conditions.
3h (STANDBY)	0h	<del>Place</del> Transition the <del>device</del> logical unit into the standby power condition and disable device server control of power conditions.
5h	0h	Obsolete
7h (LU_CONTROL)	0h	Transfer control of power conditions to the <del>logical-unit</del> device server.
Ah (FORCE_IDLE_0)	0h	Force the idle condition timer to <del>zero</del> , be expired and transfer control of power conditions to the device server.
	1h	Force the idle2 condition timer to be expired and transfer control of power conditions to the device server.
	2h	Force the idle3 condition timer to be expired and transfer control of power conditions to the device server.
Bh (FORCE_STANDBY_0)	0h	Force the standby condition timer to <del>zero</del> , be expired and transfer control of power conditions to the device server.
All other combinations		Reserved

If the START STOP UNIT command is processed with the POWER CONDITION field set to ACTIVE, IDLE, or STANDBY then:

- a) the logical unit shall transition to the specified power condition; and
- b) the device server shall disable ~~all of~~ the idle condition ~~timer if it is~~ timers that are enabled ~~active~~ (see SPC-4) and disable the standby condition timer if it is ~~active~~ enabled (see SPC-4) until another START STOP UNIT command is processed that returns control of the power condition to the logical unit, or a logical unit reset occurs.

If the START STOP UNIT command is processed with the POWER CONDITION field set to LU\_CONTROL, then the device server shall **enable activate all** the idle condition **timer if it is active timers that are enabled** (see SPC-4) and **disable activate** the standby condition timer if it is **active enabled** (see SPC-4). **The logical unit may not change to a different power condition as a result of processing this command.**

If the START STOP UNIT command is processed with the POWER CONDITION field set to FORCE\_IDLE\_0 or FORCE\_STANDBY\_0, then the device server shall:

- a) force the specified timer to **zero be expired**, **may** cause the logical unit to transition to the specified power condition, and return control of the power condition to the device server; or
- b) terminate a START STOP UNIT command that selects a timer that is not supported by the device server or a timer that is not **active enabled**. The device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

**If the START STOP UNIT command is processed with POWER CONDITION and POWER CONDITION MODIFIER field values that are supported but cannot be performed due to a conflicting request (e.g. the device server has a media access command in queue when a START STOP UNIT command is processed) then the device server may terminate the command with CHECK CONDITION status, the sense key set to ILLEGAL REQUEST, and the additional sense code set to ILLEGAL POWER CONDITION REQUEST.**

It is not an error to specify that the logical unit transition to its current power condition.

If the NO\_FLUSH bit is set to zero, then logical units that contain cache shall write all cached logical blocks to the medium (e.g., as they would do in response to a SYNCHRONIZE CACHE command (see 5.20 and 5.21) with the SYNC\_NV bit set to zero, the LOGICAL BLOCK ADDRESS field set to zero, and the NUMBER OF LOGICAL BLOCKS field set to zero) prior to entering into any power condition that prevents accessing the medium (e.g., before the rotating media spindle motor is stopped during transition to the stopped power condition). If the NO\_FLUSH bit is set to one, then cached logical blocks should not be written to the medium by the logical unit prior to entering into any power condition that prevents accessing the medium.

If the load eject (LOEJ) bit is set to zero, then the logical unit shall take no action regarding loading or ejecting the medium. If the LOEJ bit is set to one, then the logical unit shall unload the medium if the START bit is set to zero. If the LOEJ bit is set to one, then the logical unit shall load the medium if the START bit is set to one.

If the START bit is set to zero, then the logical unit shall:

- a) transition to the stopped power condition;
- b) **disable all** the idle condition **timer if it is active timers if they are enabled** (see SPC-4); and
- c) **disable** the standby condition timer if it is **active enabled** (see SPC-4).

If the START bit set to one, then the logical unit shall:

- 1) transition to the active power condition;
- 2) **enable activate all** the idle condition **timer if it is active timers if they are enabled**; and
- 3) **enable activate** the standby condition timer if it is **active enabled**.

**[Note: I changed the abc list to a 123 list. It is important that the transition to active power condition occur before the timers are activated.]**

#### 4.16.1 START STOP UNIT and power conditions overview

The START STOP UNIT command (see 5.19) allows an application client to control the power condition of a logical unit. This method includes specifying that the logical unit transition to a power condition.

In addition to the START STOP UNIT command, the power condition of a logical unit may be controlled by the Power Condition mode page (see SPC-4). If both the START STOP UNIT command and the Power Condition mode page methods are being used to control the power condition of the same logical unit, then the power condition specified by any START STOP UNIT command shall override the Power Condition mode page's power control.

There shall be no notification to the application client that a logical unit has transitioned from one power condition to another. The REQUEST SENSE command (see SPC-4) indicates if a logical unit is in the idle power condition or the standby power condition and may indicate if a logical unit is in the stopped power condition.

If the logical unit is in the idle power condition, then the device server shall process a REQUEST SENSE command by:

- 1) returning parameter data containing sense data with the sense key set to NO SENSE and the additional sense code set to:
  - A) LOW POWER CONDITION ON if the reason for entry into the idle power condition is unknown;
  - B) IDLE CONDITION ACTIVATED BY TIMER if the logical unit entered the idle power condition due to the idle condition timer (see SPC-4); ~~and~~
  - C) IDLE CONDITION ACTIVATED BY COMMAND if the logical unit entered the idle power condition due to a START STOP UNIT command or receipt of a command requiring the idle power condition while it was in the [idle2](#), [idle3](#), or standby power condition;
  - D) [IDLE2 CONDITION ACTIVATED BY TIMER](#) if the logical unit entered the [idle2](#) power condition due to the [idle2](#) condition timer (see SPC-4);
  - E) [IDLE2 CONDITION ACTIVATED BY COMMAND](#) if the logical unit entered the [idle2](#) power condition due to a START STOP UNIT command or receipt of a command requiring the [idle2](#) power condition while it was in the [idle3](#) or standby power condition;
  - F) [IDLE3 CONDITION ACTIVATED BY TIMER](#) if the logical unit entered the [idle3](#) power condition due to the [idle3](#) condition timer (see SPC-4); or
  - G) [IDLE3 CONDITION ACTIVATED BY COMMAND](#) if the logical unit entered the [idle3](#) power condition due to a START STOP UNIT command or receipt of a command requiring the [idle3](#) power condition while it was in the standby power condition;

and

- 2) completing the REQUEST SENSE command with GOOD status.

If the logical unit is in the standby power condition, then the device server shall process a REQUEST SENSE command by:

- 2) returning parameter data containing sense data with the sense key set to NO SENSE and the additional sense code set to:
  - A) LOW POWER CONDITION ON if the reason for entry into the standby power condition is unknown;
  - B) STANDBY CONDITION ACTIVATED BY TIMER if the logical unit entered the standby power condition due to the standby condition timer (see SPC-4); ~~and~~ or
  - C) STANDBY CONDITION ACTIVATED BY COMMAND if the logical unit entered the standby power condition due to a START STOP UNIT command;

and

- 3) completing the REQUEST SENSE command with GOOD status.

If the logical unit is in the stopped power condition, then the device server shall process a REQUEST SENSE command by:

- 1) returning parameter data containing sense data with:
  - A) the sense key set to NO SENSE and the additional sense code set to NO ADDITIONAL SENSE INFORMATION; or
  - B) the sense key set to NOT READY and the additional sense code set to LOGICAL UNIT NOT READY, INITIALIZING COMMAND REQUIRED;
- and
- 2) completing the REQUEST SENSE command with GOOD status.

No power condition shall affect the supply of any power required for proper operation of a service delivery subsystem.