

Date: January 12, 2009

To: T10 Committee

From Brad Besmer, LSI

Subject: SPL Power Management Reporting and Control

Revision History

r0 - Original revision

r1 - Added ATTACHED SLUMBER CAPABLE, ATTACHED PARTIAL CAPABLE and PHY POWER MANAGEMENT CONDITION to DISCOVER. Changed bytes used in DISCOVER, since bytes 66 & 67 are reserved for self-config

r2 - Changed SAS SLUMBER ENABLE to ENABLE SAS SLUMBER, SAS PARTIAL ENABLE to ENABLE SAS PARTIAL, SATA SLUMBER ENABLE to ENABLE SATA SLUMBER, SATA PARTIAL ENABLE to ENABLE SATA PARTIAL. Fixed field name in SMP DISCOVER Response.

Overview

This proposal adds SMP reporting and control of SAS and SATA Power Management (see 08-015, 08-206 and 08-249).

SPL Changes

SMP PHY CONTROL Changes:

Table 336 defines the request format.

Table 336 — PHY CONTROL request

Byte\Bit	7	6	5	4	3	2	1	0				
0	SMP FRAME TYPE (40h)											
1	FUNCTION (91h)											
2	ALLOCATED RESPONSE LENGTH											
3	REQUEST LENGTH (00h or 09h)											
4	(MSB) EXPECTED EXPANDER CHANGE COUNT											
5												
6	Reserved											
8												
9	PHY IDENTIFIER											
10	PHY OPERATION											
11	Reserved											
12	Reserved											
23												
24	ATTACHED DEVICE NAME											
31												
32	PROGRAMMED MINIMUM PHYSICAL LINK RATE				Reserved							
33	PROGRAMMED MAXIMUM PHYSICAL LINK RATE				Reserved							
34	<u>ENABLE SAS SLUMBER</u>	<u>ENABLE SAS PARTIAL</u>	<u>ENABLE SATA SLUMBER</u>	<u>ENABLE SATA PARTIAL</u>								
35	Reserved											
36	Reserved				PARTIAL PATHWAY TIMEOUT VALUE							
37	Reserved											
39												
40	(MSB) CRC											
43												

.....

Table 337 defines the ENABLE SAS SLUMBER field.

Table 337 — ENABLE SAS SLUMBER field

Code	Description
00b	No change
01b	Enable SAS slumber phy power condition
10b	Disable SAS slumber phy power condition
11b	Reserved

If the ENABLE SAS SLUMBER field is set to an unsupported or reserved value, then the management device server shall not change the SAS slumber power management and shall return a function result of SMP FUNCTION FAILED in the response frame (see table 247 in 10.4.3.3). If the management device server returns a function result of SMP FUNCTION FAILED, then it shall not perform the requested phy operation.

Table 338 defines the ENABLE SAS PARTIAL field.

Table 338 — ENABLE SAS PARTIAL field

Code	Description
00b	No change
01b	Enable SAS partial phy power condition
10b	Disable SAS partial phy power condition
11b	Reserved

If the ENABLE SAS PARTIAL field is set to an unsupported or reserved value, then the management device server shall not change the SAS partial power management and shall return a function result of SMP FUNCTION FAILED in the response frame (see table 247 in 10.4.3.3). If the management device server returns a function result of SMP FUNCTION FAILED, then it shall not perform the requested phy operation.

Table 339 defines the ENABLE SATA SLUMBER field.

Table 339 — ENABLE SATA SLUMBER field

Code	Description
00b	No change
01b	Enable SAS slumber phy power condition
10b	Disable SAS slumber phy power condition
11b	Reserved

If the ENABLE SATA SLUMBER field is set to an unsupported or reserved value, then the management device server shall not change the SATA slumber power management and shall return a function result of

SMP FUNCTION FAILED in the response frame (see table 247 in 10.4.3.3). If the management device server returns a function result of SMP FUNCTION FAILED, then it shall not perform the requested phy operation.

Table 349 defines the ENABLE SATA PARTIAL field.

Table 340 — ENABLE SATA PARTIAL field

Code	Description
00b	No change
01b	Enable SATA partial phy power condition
10b	Disable SATA partial phy power condition
11b	Reserved

If the ENABLE SATA PARTIAL field is set to an unsupported or reserved value, then the management device server shall not change the SATA partial power management and shall return a function result of SMP FUNCTION FAILED in the response frame (see table 247 in 10.4.3.3). If the management device server returns a function result of SMP FUNCTION FAILED, then it shall not perform the requested phy operation.

SMP DISCOVER Changes to SMP Response:

33	Reserved	<u>ATTACHED SLUMBER CAPABLE</u>	<u>ATTACHED PARTIAL CAPABLE</u>	ATTACHED INSIDE ZPSDS PERSISTENT	ATTACHED REQUESTED INSIDE ZPSDS	ATTACHED BREAK_REPLY CAPABLE
----	----------	---------------------------------	---------------------------------	----------------------------------	---------------------------------	------------------------------

The ATTACHED SLUMBER CAPABLE bit indicates that the value of the SLUMBER CAPABLE bit received in the IDENTIFY address frame (see x.x.x) from the attached phy during the identification sequence.

The ATTACHED PARTIAL CAPABLE bit indicates that the value of the PARTIAL CAPABLE bit received in the IDENTIFY address frame (see x.x.x) from the attached phy during the identification sequence.

48	<u>PHY POWER MANAGEMENT CONDITION</u>	Reserved	<u>SAS SLUMBER CAPABLE</u>	<u>SAS PARTIAL CAPABLE</u>	<u>SATA SLUMBER CAPABLE</u>	<u>SATA PARTIAL CAPABLE</u>
49		Reserved	<u>SAS SLUMBER ENABLED</u>	<u>SAS PARTIAL ENABLED</u>	<u>SATA SLUMBER ENABLED</u>	<u>SATA PARTIAL ENABLED</u>

The PHY POWER MANAGEMENT CONDITION field indicates that the power management condition for the phy and is described in table xxx.

Table <xxx> — PHY POWER MANAGEMENT CONDITION field

Code	Description
00b	Active power condition
01b	Partial power condition
10b	Slumber power condition
11b	Reserved

The SAS SLUMBER CAPABLE bit, SAS PARTIAL CAPABLE bit, SATA SLUMBER CAPABLE bit and SATA PARTIAL CAPABLE bit indicate that the corresponding phy power management mode is supported on the indicated phy.

The SAS SLUMBER ENABLED bit, SAS PARTIAL ENABLED bit, SATA SLUMBER ENABLED bit and SATA PARTIAL ENABLED bit indicate that the corresponding phy power management mode is enabled on the indicated phy.

Editor's Note 1: Need SATA power management control functionality to be more defined.
