X3T10/97-170 revision 1 5/6/97

To: T10 Committee (SCSI)

From: George Penokie (IBM)

Subject: Additional Device Types for ASC/ASCQs for SCC-2

The following ASC/ASCQs are required for SCC-2 to report unit attention conditions that may occur in SCSI storage arrays:

- D DIRECT ACCESS DEVICE (SBC) Device column key
- T SEQUENTIAL ACCESS DEVICE (SSC) blank = reserved
- L PRINTER DEVICE (SSC) not blank = allowed
- P PROCESSOR DEVICE (SPC)
- W WRITE ONCE READ MULTIPLE DEVICE (SBC)
- R -CDDEVICE (MMC)
- S SCANNER DEVICE (SGC)
- O OPTICAL MEMORY DEVICE (SBC)
- M MEDIA CHANGER DEVICE (SMC)
- C COMMUNICATION DEVICE (SSC)
- A-STORAGE ARRAY DEVICE (SCC)

E - ENCLOSURE SERVICES DEVICE (SES)

ASC	ASCQ	DTLPWRSOMCAE			Description
3F	04	DT	WR	OMCAE	COMPONENT DEVICE ATTACHED
3F	05	DT	WR	OMCAE	DEVICE IDENTIFIER CHANGED
3F	06	DT	WR	OMCAE	REDUNDANCY GROUP CREATED OR MODIFIED
3F	07	DT	WR	OMCAE	REDUNDANCY GROUP DELETED
3F	80	DT	WR	OMCAE	SPARE CREATED OR MODIFIED
3F	09	DT	WR	OMCAE	SPARE DELETED
3F	0A	DT	WR	OMCAE	VOLUME SET CREATED OR MODIFIED
3F	0B	DT	WR	OMCAE	VOLUME SET DELETED
3F	0C	DT	WR	OMCAE	VOLUME SET DEASSIGNED
3F	0D	DT	WR	OMCAE	VOLUME SET REASSIGNED