

TO: T10 Membership
FROM: Paul A. Suhler, Certance
DATE: 6 May 2003
SUBJECT: T10/03-165r2, ADC NOTIFY DATA TRANSFER DEVICE Command

Revision 2:

- Incorporated changes as requested by the working group meeting.
- Use service action code 1Fh, as requested by Ralph Weber.

Revision 1:

- Moved text describing use of the command for bridging to ADC model section in 03-077.
- In an effort to clarify that caching is optional, local SMC device server actions are changed from "shall" to "may."
- Added requirement to complete all status refresh command before returning status on the NOTIFY DTD command, in order to avoid races.
- Prohibit returning of Check Condition to the command, using text borrowed from the INQUIRY command.

Revision 0:

- Separated from sense data masking.
- Incorporated Automation AER IU contents

Purpose:

This command replaces the Automation AER IU. It is based upon the SERVICE ACTION OUT(16) command

SPC-3 Table 5 (typical 16-byte CDB) states that the parameter list length field need be included only if required. I propose to leave bytes 10 – 13 Reserved in case we need to add parameters in the future.

New command in ADC clause 5:

New line in Table 2:

Command:	NOTIFY DATA TRANSFER DEVICE
Required:	M
Reference:	5.x
Notes:	(no note)

New command description:

5.x NOTIFY DATA TRANSFER DEVICE command

The NOTIFY DATA TRANSFER DEVICE command (see table x) is sent by the automation device to notify the data transfer device (DTD) of specific events. It does not represent the complete current state of the automation device and is not intended to be sent upon every change in the device's state. Implementation of this command is mandatory.

Table x – NOTIFY DATA TRANSFER DEVICE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Fh)							
1	Reserved			SERVICE ACTION (1Fh)				
2	Reserved							LdFAIL
3	Reserved				BUA	NRSC	IDC	MDC

4	ASC
5	ASCQ
6	Reserved
7	Reserved
8	Reserved
9	Reserved
10	Reserved
11	Reserved
12	Reserved
13	Reserved
14	Reserved
15	CONTROL

The LOAD FAILED (LDFAIL) field is set to one if the automation device has detected a failure of the data transfer device to load a medium, and the automation device will not retry the load.

The fields in byte 3 are collectively known as the bridging status byte and are used to indicate that cached SMC data may require refreshing.

A value of one in the Mode Data Changed (MDC) field indicates that the contents of a mode page or mode parameter header reported by the remote SMC device server has been changed. Upon receipt of this notification, the use of any cached mode data shall be discontinued until it has been refreshed.

A value of one in the Inquiry Data Changed (IDC) field indicates that the contents of the standard inquiry data or of any vital product data page reported by the remote SMC device server has changed. Upon receipt of this notification, the use of any cached inquiry data or VPD pages shall be discontinued until it has been refreshed.

A value of one in the Not Ready Status Changed (NRSC) field indicates that the remote SMC device server has entered the not accessible state, as in the description of caching SMC data and status in 4.2.x.3. It can also indicate that the remote SMC device server was already in the not accessible state and the sense data changed. When NRSC is one, the ASC and ASCQ fields shall contain sense data appropriate to the condition. Upon receipt of this notification, the cached ready status and additional sense code shall be updated.

When the BROADCAST UNIT ATTENTION (BUA) field is set to one, the ASC and ASCQ fields shall contain the additional sense code to be used by the local SMC device server to establish a unit attention condition for all initiators accessible via its DTD primary ports. When the sense data is NOT READY TO READY CHANGE, MEDIUM MAY HAVE CHANGED, it indicates that the remote SMC device server has entered the accessible state.

It is not valid for both the NRSC and BUA fields to be set to one. If both the NRSC and the BUA fields are set to zero, then it is not valid for either the ASC and ASCQ field to be set to a non-zero value. If both fields are set to one or if both are set to zero and either the ASC or ASCQ field is not zero, then the command shall be terminated with a CHECK CONDITION status. The sense key shall be set to ILLEGAL REQUEST and the additional sense code shall be set to INVALID FIELD IN CDB.

If a NOTIFY DATA TRANSFER DEVICE command is received from an initiator with a pending unit attention condition (i.e., before the device server reports CHECK CONDITION status), the

device server shall perform the NOTIFY DATA TRANSFER DEVICE command and shall not clear the unit attention condition.